

APTER POWER PRODUCT MANUAL

6ES7288-1SR60-0AA1

SIMATIC S7-200 SMART CPU SR60

The Siemens 6ES7288-1SR60-0AA1 is a SIMATIC S7-200 SMART SR60 standard CPU with 36 integrated 24 V DC digital inputs, 24 relay outputs, and 50 KB of program/data memory.

It executes the STEP 7 Micro/WIN SMART user program, reads the 36 onboard binary input signals, and commands 24 field outputs for high-density relay control from one expandable standard CPU. Its relay channels switch approved AC or DC loads within the published contact limits. The standard CPU exchanges engineering, process, and diagnostic data over Industrial Ethernet/PROFINET and RS485, and can use compatible S7-200 SMART expansion components. It is suited to large standalone machines and distributed line sections.

Manufacturer	Siemens
Prepared by	Apter Power
Document ID	AP-SIE-04-6ES7288-1SR60-0AA1-PM-R1
Revision	R1
Issue date	2026-08-18

APTER POWER SALES TEAM

INDUSTRIAL AUTOMATION PRODUCT SUPPORT

24 relay outputs coordinated by an expandable SMART CPU.

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



SCAN FOR PRODUCT & QUOTE
6ES7288-1SR60-0AA1

1. Product Overview and Identity

The Siemens 6ES7288-1SR60-0AA1 is a SIMATIC S7-200 SMART SR60 standard CPU with 36 integrated 24 V DC digital inputs, 24 relay outputs, and 50 KB of program/data memory.

It executes the STEP 7 Micro/WIN SMART user program, reads the 36 onboard binary input signals, and commands 24 field outputs for high-density relay control from one expandable standard CPU. Its relay channels switch approved AC or DC loads within the published contact limits. The standard CPU exchanges engineering, process, and diagnostic data over Industrial Ethernet/PROFINET and RS485, and can use compatible S7-200 SMART expansion components. It is suited to large standalone machines and distributed line sections.

Model Configuration

Field	Verified information
Complete model	6ES7288-1SR60-0AA1
Manufacturer	Siemens
Product description	SIMATIC S7-200 SMART CPU SR60

Key Features

- Exact Siemens MLFB 6ES7288-1SR60-0AA1
- SIMATIC S7-200 SMART CPU SR60
- 36 DI 24 V DC; 24 relay DQ
- 50 KB program/data memory
- 1 x Industrial Ethernet/PROFINET and 1 x RS485

2. Technical Specifications

Only manufacturer-confirmed information is stated. Values absent from the named Siemens source are marked for nameplate or document verification.

Parameter	Verified value
Product type	SIMATIC S7-200 SMART CPU SR60
CPU design	Standard expandable CPU
Onboard digital inputs	36 inputs, 24 V DC
Onboard digital outputs	24; Relay, 2 A
Power supply	85 to 264 V AC at 47 to 63 Hz
Program/data memory	50 KB
Engineering software	STEP 7 Micro/WIN SMART
Communication	1 x Industrial Ethernet/PROFINET and 1 x RS485
Mounting	Standard DIN rail
Degree of protection	IP20
Ambient operation	-20 to 60 deg C for horizontal installation; follow orientation-specific limits in Siemens data
Device dimensions	175 x 100 x 81 mm (W x H x D)
Approximate device weight	0.6115 kg
Country of origin	China
Lifecycle	Current 0AA1 standard CPU article documented by Siemens; confirm regional ordering status at quotation.

Verification Note

Use the complete 6ES7288-1SR60-0AA1 identifier. Current 0AA1 standard CPU article documented by Siemens; confirm regional ordering status at quotation. Values not published in the cited Siemens sources are intentionally not inferred.

3. Functions, Applications and Components

Core Functions

- It executes the STEP 7 Micro/WIN SMART user program, reads the 36 onboard binary input signals, and commands 24 field outputs for high-density relay control from one expandable standard CPU. Its relay channels switch approved AC or DC loads within the published contact limits. The standard CPU exchanges engineering, process, and diagnostic data over Industrial Ethernet/PROFINET and RS485, and can use compatible S7-200 SMART expansion components. It is suited to large standalone machines and distributed line sections.
- Maintains the documented CPU SR60 role for the complete 6ES7288-1SR60-0AA1 article number.
- Provides a verified basis for wiring, programming, commissioning, diagnostics, and replacement planning.

Application Areas

Application	System role
Machine sequence control	Processes 36 digital inputs and drives 24 relay-controlled field circuits
Mixed AC/DC load panels	Uses isolated relay contacts for approved AC or DC loads
Networked automation	Shares process data and diagnostics through Ethernet/PROFINET or RS485
Expandable equipment	Adds compatible S7-200 SMART I/O when the 60 onboard points are not sufficient

Compatible Components

- S7-200 SMART project configured for CPU SR60 and complete MLFB 6ES7288-1SR60-0AA1
- 24 V DC sensors and field loads matched to the documented input and output circuits
- Industrial Ethernet/PROFINET and RS485 devices defined in the STEP 7 Micro/WIN SMART project
- S7-200 SMART expansion modules, signal boards, memory card, and cabling approved for the exact CPU

Lifecycle Status

Current 0AA1 standard CPU article documented by Siemens; confirm regional ordering status at quotation.

4. Installation Precautions

- Identity: Match the complete 6ES7288-1SR60-0AA1 MLFB, CPU SR60 marking, hardware, and firmware
- Power: Verify 85 to 264 V AC at 47 to 63 Hz and isolate all sources before wiring or removal
- I/O: Observe every channel voltage, current, group common, polarity, and protective-device limit
- Project: Back up and match the STEP 7 Micro/WIN SMART configuration, addresses, communications, and retentive data
- Panel: Use DIN-rail mounting, protective earth, segregation, ventilation, and orientation limits from Siemens

STOP - Verify before installation

Use the complete 6ES7288-1SR60-0AA1 identifier. Current 0AA1 standard CPU article documented by Siemens; confirm regional ordering status at quotation. Values not published in the cited Siemens sources are intentionally not inferred.

Use the physical nameplate and current Siemens documents as the controlling records.

5. Official Source and Use Notice

Official source

Siemens official technical data sheet for 6ES7288-1SR60-0AA1: <https://support.industry.siemens.com/teddatasheet/?caller=SIO&format=pdf&language=en&mlfbs=6ES7288-1SR60-0AA1>; Siemens S7-200 SMART System Manual: https://support.industry.siemens.com/cs/attachments/109745610/s7-200_SMART_system_manual_en-US.pdf

Apter Power product page

<https://www.apterpower.com/Siemens/6es7288-1sr60-0aa1>

Use Notice

This is an original Apter Power product-specific reference prepared from the Siemens source named above. It is not a Siemens publication and does not replace the original data sheet, nameplate, certificate, installation drawing, safety instructions, or machine-builder documentation.

ASK FOR QUOTE

For availability and quotation details, visit www.apterpower.com or contact sales13@apterpower.com.