

APTER POWER PRODUCT MANUAL

6ES7288-2DR16-0AA0

SIMATIC S7-200 SMART SM DR16 Digital I/O Module

The Siemens 6ES7288-2DR16-0AA0 is a SIMATIC S7-200 SMART SM DR16 Digital I/O Module that provides balanced eight-input and eight-relay-output expansion.

In an S7-200 SMART automation station, it acquires eight 24 V DC field states and returns eight isolated relay commands through one mixed digital I/O module. It works with the verified CPU or expansion-bus configuration, terminal blocks, field power, sensors, and actuators defined for the exact article number. The module is used in compact actuator stations, valve manifolds, indexed conveyors, and local machine cells.


Manufacturer	Siemens
Prepared by	Apter Power
Document ID	AP-SIE-06-6ES7288-2DR16-0AA0-PM-R1
Revision	R1
Issue date	2026-08-19

APTER POWER SALES TEAM

INDUSTRIAL AUTOMATION PRODUCT SUPPORT

**Eight inputs in. Eight relay decisions out.
Balanced field expansion.**

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



SCAN FOR PRODUCT & QUOTE
6ES7288-2DR16-0AA0

1. Product Overview and Identity

The Siemens 6ES7288-2DR16-0AA0 is a SIMATIC S7-200 SMART SM DR16 Digital I/O Module that provides balanced eight-input and eight-relay-output expansion.

In an S7-200 SMART automation station, it acquires eight 24 V DC field states and returns eight isolated relay commands through one mixed digital I/O module. It works with the verified CPU or expansion-bus configuration, terminal blocks, field power, sensors, and actuators defined for the exact article number. The module is used in compact actuator stations, valve manifolds, indexed conveyors, and local machine cells.

Model Configuration

Field	Verified information
Complete model	6ES7288-2DR16-0AA0
Manufacturer	Siemens
Product description	SIMATIC S7-200 SMART SM DR16 Digital I/O Module

Key Features

- Exact Siemens MLFB 6ES7288-2DR16-0AA0
- SIMATIC S7-200 SMART SM DR16 Digital I/O Module
- 8 DI 24 V DC; 8 relay DQ
- 24 V DC nominal; 20.4 to 28.8 V DC permissible
- 45 x 100 x 81 mm
- 0.2019 kg approximate device weight

2. Technical Specifications

Only manufacturer-confirmed information is stated. Values absent from the named Siemens source are marked for nameplate or document verification.

Parameter	Verified value
Product type	SIMATIC S7-200 SMART SM DR16 Digital I/O Module
Complete article number	6ES7288-2DR16-0AA0
System	SIMATIC S7-200 SMART
Primary function	balanced eight-input and eight-relay-output expansion
Power supply	24 V DC nominal; 20.4 to 28.8 V DC permissible
Digital inputs	8; 24 V DC; sink/source
Digital outputs	8; 8 relay outputs, 2 A
Digital inputs	8, sink/source
Relay outputs	8
Rated output current	2 A
Input delay	200 microseconds maximum
Output delay	10 ms maximum
Power consumption	5.5 W
Mounting	Standard DIN rail
Degree of protection	IP20
Device dimensions	45 x 100 x 81 mm (W x H x D)
Approximate device weight	0.2019 kg
Country of origin	Germany
Lifecycle	The exact article number is documented in Siemens official S7-200 SMART ordering information and technical documentation; confirm current regional availability at quotation.

Verification Note

Use the complete 6ES7288-2DR16-0AA0 identifier. The exact article number is documented in Siemens official S7-200 SMART ordering information and technical documentation; confirm current regional availability at quotation. Values not published in the cited Siemens sources are intentionally not inferred.

3. Functions, Applications and Components

Core Functions

- Acquires eight 24 V DC field states and returns eight isolated relay commands through one mixed digital I/O module.
- Maintains the documented SM DR16 function for the complete 6ES7288-2DR16-0AA0 article number.
- Provides a model-specific basis for wiring, configuration, commissioning, diagnostics, and replacement verification.

Application Areas

Application	System role
Isolated load switching	Commands 8 approved relay-controlled AC or DC circuits
Contactor and valve control	Interfaces controller logic with contactors, solenoids, lamps, and interposing relays
Mixed-voltage auxiliaries	Uses dry relay contacts where the published contact and group limits are respected
Machine and process panels	Supports compact actuator stations, valve manifolds, indexed conveyors, and local machine cells

Compatible Components

- S7-200 SMART configuration that explicitly supports the complete 6ES7288-2DR16-0AA0 article number
- Siemens-approved DIN rail, removable terminal blocks, expansion-bus arrangement, and panel wiring for the exact module
- 24 V DC field devices and power supplies matched to every published channel, group, polarity, and current limit
- 8 compatible input devices and 8 field loads matched to 8 relay outputs, 2 A

Lifecycle Status

The exact article number is documented in Siemens official S7-200 SMART ordering information and technical documentation; confirm current regional availability at quotation.

4. Installation Precautions

- Identity: Match every character of 6ES7288-2DR16-0AA0 and the SM DR16 marking to the physical nameplate and project
- Power: Verify 24 V DC nominal; 20.4 to 28.8 V DC permissible; isolate all energy sources before wiring, insertion, or removal
- Signals: Observe every input/output voltage, current, common, group, polarity, isolation, and protective-device limit
- Panel: Use documented DIN-rail mounting, clearances, protective earth, cable segregation, ventilation, and IP20 enclosure protection
- Commissioning: Back up the project, verify addresses and terminals, test one circuit group at a time, and record the results

STOP - Verify before installation

Use the complete 6ES7288-2DR16-0AA0 identifier. The exact article number is documented in Siemens official S7-200 SMART ordering information and technical documentation; confirm current regional availability at quotation. Values not published in the cited Siemens sources are intentionally not inferred.

Use the physical nameplate and current Siemens documents as the controlling records.

5. Official Source and Use Notice

Official source

Siemens official technical data sheet for 6ES7288-2DR16-0AA0: <https://support.industry.siemens.com/teddatasheet/?caller=SIO&format=pdf&language=en&mlfbs=6ES7288-2DR16-0AA0>; Siemens official S7-200 SMART ordering information: https://www.ad.siemens.com.cn/download/documentdetail_17711.html; Siemens official system manual with model-specific I/O tables: https://support.industry.siemens.com/cs/attachments/109963390/SIMATIC_ET_200_SMART_IM60_System_Manual_en-US.pdf

Apter Power product page

<https://www.apterpower.com/Siemens/6es7288-2dr16-0aa0>

Use Notice

This is an original Apter Power product-specific reference prepared from the Siemens source named above. It is not a Siemens publication and does not replace the original data sheet, nameplate, certificate, installation drawing, safety instructions, or machine-builder documentation.

ASK FOR QUOTE

For availability and quotation details, visit www.apterpower.com or contact sales13@apterpower.com.