

APTER POWER PRODUCT MANUAL

6ES7288-3AM06-0AA0

SIMATIC S7-200 SMART EM AM06 Analog I/O Module

The Siemens 6ES7288-3AM06-0AA0 is a SIMATIC S7-200 SMART EM AM06 Analog I/O Module that provides four analog inputs plus two analog outputs with separate input and output conversion.

In an S7-200 SMART automation station, it digitizes four analog process inputs and generates two voltage or current output commands. It works with the exact CPU, expansion-bus or signal-board interface, wiring, field devices, and project configuration specified for the complete article number. It is applied in multi-variable process skids, dual-loop control, coordinated drives, and compact utility systems.


Manufacturer	Siemens
Prepared by	Apter Power
Document ID	AP-SIE-04-6ES7288-3AM06-0AA0-PM-R1
Revision	R1
Issue date	2026-08-19

APTER POWER SALES TEAM

INDUSTRIAL AUTOMATION PRODUCT SUPPORT

**Four measurements. Two analog commands.
Balanced closed-loop expansion.**

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



SCAN FOR PRODUCT & QUOTE
6ES7288-3AM06-0AA0

1. Product Overview and Identity

The Siemens 6ES7288-3AM06-0AA0 is a SIMATIC S7-200 SMART EM AM06 Analog I/O Module that provides four analog inputs plus two analog outputs with separate input and output conversion.

In an S7-200 SMART automation station, it digitizes four analog process inputs and generates two voltage or current output commands. It works with the exact CPU, expansion-bus or signal-board interface, wiring, field devices, and project configuration specified for the complete article number. It is applied in multi-variable process skids, dual-loop control, coordinated drives, and compact utility systems.

Model Configuration

Field	Verified information
Complete model	6ES7288-3AM06-0AA0
Manufacturer	Siemens
Product description	SIMATIC S7-200 SMART EM AM06 Analog I/O Module

Key Features

- Exact Siemens MLFB 6ES7288-3AM06-0AA0
- SIMATIC S7-200 SMART EM AM06 Analog I/O Module
- 4 analog inputs and 2 analog outputs
- 24 V DC; 20.4 to 28.8 V DC
- 45 x 100 x 81 mm
- 0.1734 kg approximate device weight

2. Technical Specifications

Only manufacturer-confirmed information is stated. Values absent from the named Siemens source are marked for nameplate or document verification.

Parameter	Verified value
Product type	SIMATIC S7-200 SMART EM AM06 Analog I/O Module
Complete article number	6ES7288-3AM06-0AA0
System	SIMATIC S7-200 SMART
Primary function	four analog inputs plus two analog outputs with separate input and output conversion
Signal configuration	4 analog inputs and 2 analog outputs
Supply / host interface	24 V DC; 20.4 to 28.8 V DC
Product type designation	EM AM06, AI 4x12 bit, AQ 2x11 bit
Analog inputs	4
Analog outputs	2; voltage or current
Input ranges	+/-10 V, +/-5 V, +/-2.5 V, 0 to 20 mA
Output ranges	-10 V to +10 V, 0 to 20 mA
Input resolution	12 bit maximum
Output resolution	11 bit maximum
Power loss	2.0 W
Degree of protection	IP20
Device dimensions	45 x 100 x 81 mm (W x H x D)
Approximate device weight	0.1734 kg
Country of origin	Germany
Lifecycle	The exact article number is documented in current Siemens technical data and product records; confirm regional ordering availability at quotation.

Verification Note

Use the complete 6ES7288-3AM06-0AA0 identifier. The exact article number is documented in current Siemens technical data and product records; confirm regional ordering availability at quotation. Values not published in the cited Siemens sources are intentionally not inferred.

3. Functions, Applications and Components

Core Functions

- Digitizes four analog process inputs and generates two voltage or current output commands.
- Maintains the documented EM AM06 function for the complete 6ES7288-3AM06-0AA0 article number.
- Provides a model-specific basis for wiring, configuration, commissioning, diagnostics, and replacement verification.

Application Areas

Application	System role
Closed-loop control	Acquires process feedback and returns analog commands through one module
Skid instrumentation	Combines transmitter inputs with valve or drive references
Multi-variable coordination	Supports multi-variable process skids, dual-loop control, coordinated drives, and compact utility systems
Panel-density improvement	Reduces separate analog input/output module count where the channel total fits

Compatible Components

- S7-200 SMART or ET 200 SMART configuration that explicitly supports 6ES7288-3AM06-0AA0
- Expansion-bus connection, removable terminal blocks, DIN rail, and panel clearances specified by Siemens
- Shielded analog sensor or actuator cabling with documented grounding and reference conductors
- Field transmitters, sensors, loads, and power supplies matched to every published signal range and channel limit

Lifecycle Status

The exact article number is documented in current Siemens technical data and product records; confirm regional ordering availability at quotation.

4. Installation Precautions

- Identity: Match every character of 6ES7288-3AM06-0AA0 and the EM AM06 marking to the physical nameplate and project
- Host and power: Verify 24 V DC; 20.4 to 28.8 V DC; isolate all energy sources before insertion, removal, or wiring
- Signals: Configure every channel for the documented signal type and range; observe polarity, reference, load, and diagnostic limits
- Cabling: Follow Siemens terminal, shielding, grounding, separation, and maximum cable-length instructions
- Commissioning: Verify addresses and scaling, energize one circuit group at a time, test fail-safe behavior, and record results

STOP - Verify before installation

Use the complete 6ES7288-3AM06-0AA0 identifier. The exact article number is documented in current Siemens technical data and product records; confirm regional ordering availability at quotation. Values not published in the cited Siemens sources are intentionally not inferred.

Use the physical nameplate and current Siemens documents as the controlling records.

5. Official Source and Use Notice

Official source

Siemens official technical data sheet or product record for 6ES7288-3AM06-0AA0: <https://support.industry.siemens.com/teddatasheet/?caller=SIOS&format=pdf&language=en&mlfbs=6ES7288-3AM06-0AA0>; Siemens official system manual used for model-specific installation and compatibility context: https://support.industry.siemens.com/cs/attachments/109963390/SIMATIC_ET_200_SMART_IM60_System_Manual_en-US.pdf

Apter Power product page

<https://www.apterpower.com/Siemens/6es7288-3am06-0aa0>

Use Notice

This is an original Apter Power product-specific reference prepared from the Siemens source named above. It is not a Siemens publication and does not replace the original data sheet, nameplate, certificate, installation drawing, safety instructions, or machine-builder documentation.

ASK FOR QUOTE

For availability and quotation details, visit www.apterpower.com or contact sales13@apterpower.com.