

APTER POWER INSTALLATION & VERIFICATION REFERENCE

330171-00-30-10-02-BR

A separate product-specific field checklist

Use this model-specific reference to verify the complete Bently Nevada ordering code, matched components, mounting geometry, signal path, and approval evidence before installation or substitution.


Manufacturer	Bently Nevada
Prepared by	Apter Power
Document ID	AP-BN-B10-05-330171-00-30-10-02-BR-IV-R1
Revision	R1
Issue date	2026-08-20

APTER POWER SALES TEAM

INDUSTRIAL AUTOMATION PRODUCT SUPPORT

Compact five-millimetre sensing. Brazil approval traceability.

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



SCAN FOR PRODUCT & QUOTE
330171-00-30-10-02-BR

1. Pre-Installation Verification

Step	Check	Required evidence
1	Identity	Match every character of 330171-00-30-10-02-BR to the physical nameplate and quotation.
2	Mechanical	Overall case: 3.0 in; integral lead: 1.0 m (3.3 ft); family probe weight reference: 323 g. Exact packed-carton dimensions are not published.
3	System matching	Match the 1.0 m probe with a 4.0 m 330130 extension cable and 5.0 m 330180 Proximator Sensor, or with an 8.0 m extension cable and 9.0 m sensor.
4	Signal path	Used with a correctly matched 3300 XL extension cable and 3300 XL Proximator Sensor, it converts distance from the compact 5.2 mm probe tip to a conductive shaft or target into a proportional voltage. The complete system measures dynamic radial vibration, static or axial position, Keyphasor phase reference, and rotational speed on fluid-film-bearing machinery.
5	Approval	Use only the approvals and installation drawing confirmed by the exact physical marking.
6	Commissioning	Record gap, loop or monitor scaling, functional test result, technician, and date.

Product-Specific Precautions

- Match the 1.0 m probe with a 4.0 m 330130 extension cable and 5.0 m 330180 Proximator Sensor, or with an 8.0 m extension cable and 9.0 m sensor.
- Limit 1/4-28 engagement to 0.375 in and follow the 5.1 N m recommended case torque.
- Maintain the 25.4 mm minimum bend radius and protect the ClickLoc connection from oil, moisture, crushing, and sharp edges.
- Set the final gap against the actual target and verify target size, shaft diameter, probe spacing, and monitoring scale.
- Confirm the BR nameplate, INMETRO applicability, current certificate, barriers, and installation drawing before hazardous-area service.

2. Commissioning Record

Record item	Site entry
Physical model / suffix	
Serial / revision	
Machine and measurement point	
Matched cable / sensor / transmitter	
Mounting and gap evidence	
Signal or loop scaling	
Approval drawing / barrier	
Functional test result	
Technician / date	

Source Basis

Baker Hughes / Bently Nevada 3300 5 mm Transducer System Datasheet 172036 Rev. T - <https://dam.bakerhughes.com/m/3048672186f80f8/original/3300-5-mm-Transducer-System-Datasheet-172036-pdf.pdf>; Baker Hughes / Bently Nevada Approvals Quick Reference Guide 108M1756 Rev. AV - <https://dam.bakerhughes.com/asset/39aafea9-7f77-4a1e-aae3-04783ae5aca9/Approvals-Quick-Reference-Guide-Country-Specific-Ordering-Options-108M1756-pdf.pdf>

Important Notice

This Apter Power checklist is not a Bently Nevada installation instruction. The current manufacturer documentation, the physical nameplate, the machine drawing, and applicable safety rules control all work.

APTER POWER SALES TEAM

INDUSTRIAL AUTOMATION PRODUCT SUPPORT

Compact five-millimetre sensing. Brazil approval traceability.

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



SCAN FOR PRODUCT & QUOTE

330171-00-30-10-02-BR