

APTER POWER INSTALLATION & VERIFICATION REFERENCE

74712-01-11-02-00

A separate product-specific field checklist

Use this model-specific reference to verify the complete Bently Nevada ordering code, matched components, mounting geometry, signal path, and approval evidence before installation or substitution.


Manufacturer	Bently Nevada
Prepared by	Apter Power
Document ID	AP-BN-B10-07-74712-01-11-02-00-IV-R1
Revision	R1
Issue date	2026-08-20

APTER POWER SALES TEAM

INDUSTRIAL AUTOMATION PRODUCT SUPPORT

Vertical calibration. High-temperature velocity insight.

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



SCAN FOR PRODUCT & QUOTE

74712-01-11-02-00

1. Pre-Installation Verification

Step	Check	Required evidence
1	Identity	Match every character of 74712-01-11-02-00 to the physical nameplate and quotation.
2	Mechanical	Typical sensor dimensions: 102 mm high x 41 mm diameter; typical mass: 480 g. Packed-carton dimensions are not published.
3	System matching	An 84508, 84509, 84660, 84510, or 87143 high-temperature cable selected for the required termination and environment.
4	Signal path	Mounted on a bearing housing or machine casing, its internal seismic mechanism produces a voltage proportional to casing vibration velocity. The two-wire signal is routed through a compatible high-temperature cable to a Bently Nevada monitor or vibration data-collection input for continuous condition monitoring of rotating equipment.
5	Approval	Use only the approvals and installation drawing confirmed by the exact physical marking.
6	Commissioning	Record gap, loop or monitor scaling, functional test result, technician, and date.

Product-Specific Precautions

- Install the transducer at 0 +/-2.5 degrees from vertical as viewed from the driver end of the machine.
- Prepare a rigid flat mounting surface and tighten the M10 x 1 base to the published 5.6 N m torque.
- Route the separate high-temperature cable in protected conduit and keep connections dry and mechanically supported.
- Use a 10 kohm compatible input and verify polarity, shielding, frequency response, and channel scaling.
- Do not infer hazardous-area certification: final option 00 orders no agency approval.

2. Commissioning Record

Record item	Site entry
Physical model / suffix	
Serial / revision	
Machine and measurement point	
Matched cable / sensor / transmitter	
Mounting and gap evidence	
Signal or loop scaling	
Approval drawing / barrier	
Functional test result	
Technician / date	

Source Basis

Baker Hughes / Bently Nevada 9200 and 74712 Seismoprobe Velocity Transducers Datasheet 141626 Rev. V - <https://dam.bakerhughes.com/m/7b3b66d04b57d922/original/9200-and-74712-Seismoprobe-Velocity-Transducers-Datasheet-141626-pdf.pdf>

Important Notice

This Apter Power checklist is not a Bently Nevada installation instruction. The current manufacturer documentation, the physical nameplate, the machine drawing, and applicable safety rules control all work.

APTER POWER SALES TEAM

INDUSTRIAL AUTOMATION PRODUCT SUPPORT

Vertical calibration. High-temperature velocity insight.

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



SCAN FOR PRODUCT & QUOTE

74712-01-11-02-00