

INDUSTRIAL AUTOMATION PRODUCT

X20AI2632

Two-Channel Analog Input Module

B&R X20AI2632 is a two-channel analog input module for the documented X20 System installation.

CONTROLLED ENGINEERING COPY

IDENTITY	VERIFIED VALUE
Manufacturer	B&R
System family	X20 System
Part number	X20AI2632
Origin / HS	Austria / 8537101190
Shipping origin	Xiamen,Fujian,China

DOCUMENT SCOPE

Exact article identity, official technical data, host matching, installation checks, applications, precautions and controlled acceptance evidence.

MODEL-SPECIFIC ENGINEERING NOTE

Confirm B&R X20AI2632, X20 I/O station, two voltage or current input channels and X20TB06/X20TB12, wiring, grounding, configuration, companion accessories and controlled commissioning results before service release.

System Role and Architecture

B&R X20AI2632 is a two-channel analog input module for the documented X20 System installation.

FUNCTION 1
Provides two-channel analog signal acquisition

FUNCTION 2
Uses exact B&R article identity X20AI2632

FUNCTION 3
Matches analog inputs: 2

FUNCTION 4
Matches signal ranges: +/-10 V or 0 to 20 mA

MATCHED SYSTEM COMPONENTS

NO.	DOCUMENTED COMPONENT / ROLE
01	X20 System
02	X20 I/O station
03	two voltage or current input channels and X20TB06/X20TB12
04	Approved wiring, shielding and grounding arrangement

SYSTEM INTEGRATION RECORD

INTEGRATION ITEM	DOCUMENTED ROLE
Host identity	X20 System
Interface role	two-channel analog signal acquisition
Field / power context	X20 I/O station
Commissioning evidence	Identity, gap, polarity, response and alarm diagnostics recorded

INSTALLATION AND CONNECTION CHECKS

- 1

Confirm the complete B&R X20AI2632 marking and installed X20 System position before work.
- 2

Place the machine or process in the approved maintenance state and isolate every applicable energy source.
- 3

Record two voltage or current input channels and X20TB06/X20TB12, terminal assignments, shielding and protective-ground connections before
- 4

Use ESD controls and protect keyed connectors, terminals and exposed electronics from contamination.

Technical Specifications

Technical values below are limited to the named product record and directly applicable manufacturer documentation.

PARAMETER	VALUE
Analog inputs	2
Signal ranges	+/-10 V or 0 to 20 mA
Converter resolution	16 bit
Isolation	Channels isolated from bus
Channel isolation	Channels not isolated from each other

PARAMETER	VALUE
Bus module	X20BM11
Terminal block	X20TB06 or X20TB12
Protection	IP20
Pitch	12.5 mm

ENGINEERING BOUNDARY

Confirm B&R X20AI2632, X20 I/O station, two voltage or current input channels and X20TB06/X20TB12, wiring, grounding, configuration, companion accessories and controlled commissioning results before service release.

PRE-INSTALLATION CHECKS

- 1

Confirm the complete B&R X20AI2632 marking and installed X20 System position before work.
- 2

Place the machine or process in the approved maintenance state and isolate every applicable energy source.
- 3

Record two voltage or current input channels and X20TB06/X20TB12, terminal assignments, shielding and protective-ground connections
- 4

Use ESD controls and protect keyed connectors, terminals and exposed electronics from contamination.

Applications and Engineering Context

X20 System system maintenance

Restores two-channel analog signal acquisition in the documented installation.

Controlled hardware replacement

Preserves the exact X20AI2632 identity and approved configuration.

Interface verification

Confirms two voltage or current input channels and X20TB06/X20TB12 before energization.

Functional recommissioning

Reviews diagnostics and records the controlled system response.

TECHNICAL NOTE

Confirm B&R X20AI2632, X20 I/O station, two voltage or current input channels and X20TB06/X20TB12, wiring, grounding, configuration, companion accessories and controlled commissioning results before service release.

MODEL-SPECIFIC ACCEPTANCE EVIDENCE

CHECK	ACCEPTANCE CONDITION
Identity	X20AI2632 recorded
Host / carrier	X20 System
Physical interface	two voltage or current input channels and X20TB06/X20TB12 matched
Configuration	Exact installed configuration and assignments restored
Functional proof	Controlled two-channel analog signal acquisition response recorded

IMPORTANT NOTICE

Confirm B&R X20AI2632, X20 I/O station, two voltage or current input channels and X20TB06/X20TB12, wiring, grounding, configuration, companion accessories and controlled commissioning results before service release.

Related Products and Source Record

Brand-qualified Apter Power navigation links are provided for system planning only; manufacturer evidence remains the named source record.

RELATED PRODUCTS ON APTER POWER	
01	Bently Nevada 330102-00-40-05-01-05
02	Bently Nevada 330850-50-00
03	Bently Nevada 330130-080-02-05
04	Bently Nevada 330104-00-08-10-02-05
05	Bently Nevada 330101-00-66-10-02-CN
06	Bently Nevada 330101-00-58-10-02-CN
07	Bently Nevada 330104-00-06-05-02-CN
08	Bently Nevada 330930-065-01-05

Navigation links only - not manufacturer evidence for technical parameters.

MANUFACTURER SOURCE RECORD

B&R X20AI2632 product data | Data sheet X20AI2632

APTER POWER SALES TEAM

- WHATSAPP / PHONE

+86 180 3023 5313
- EMAIL

sales13@apterpower.com
- WEBSITE

www.apterpower.com

