

Example: 0 4 = 0.4 in

- B:** Overall Case Length Option
Order in increments of 0.1 in
- Threaded length configurations:**
- Maximum case length:** 9.6 in
- Minimum case length:** 0.8 in
- Example:** 2 4 = 2.4 in

- C:** Total Length Option
- | | |
|------------|-------------------------------------|
| 0 5 | 0.5 metre (1.6 feet) |
| 1 0 | 1.0 metre (3.3 feet) |
| 1 5 | 1.5 metre (4.9 feet) |
| 2 0 | 2.0 metres (6.6 feet) |
| 5 0 | 5.0 metres (16.4 feet) ¹ |
| 9 0 | 9.0 metres (29.5 feet) |

- D:** Connector and Cable-Type Option
- | | |
|------------|---|
| 0 1 | Miniature coaxial ClickLoc™ connector with connector protector, standard cable |
| 0 2 | Miniature coaxial ClickLoc™ connector, standard cable |
| 1 1 | Miniature coaxial ClickLoc™ connector with connector protector, FluidLoc® cable |
| 1 2 | Miniature coaxial ClickLoc™ connector, FluidLoc® cable |

- E:** Agency Approval Option
- | | |
|------------|--------------------|
| 0 0 | Not required |
| 0 5 | Multiple Approvals |

3300 XL 8 mm Proximity Probes, Metric:

330103 3300 XL 8 mm Probe, M10 x 1 thread, without armor³

330104 3300 XL 8 mm Probe, M10 x 1 thread, with armor³

Part Number-AXX-BXX-CXX-DXX-EXX

Option Descriptions

A: Unthreaded Length Option

Note: Unthreaded length must be at least 20 mm less than the case length.

Order in increments of 10 mm.

Length configuration:

Maximum unthreaded length: 230 mm

Minimum unthreaded length: 0 mm

Example: 0 6 = 60 mm

- B:** Overall Case Length Option
Order in increments of 10 mm.
- Metric thread configurations:**
- Maximum length:** 250 mm
- Minimum length:** 20 mm
- Example:** 0 6 = 60 mm

- C:** Total Length Option
- | | |
|------------|-------------------------------------|
| 0 5 | 0.5 metre (1.6 feet) |
| 1 0 | 1.0 metre (3.3 feet) |
| 1 5 | 1.5 metres (4.9 feet) |
| 2 0 | 2.0 metres (6.6 feet) |
| 5 0 | 5.0 metres (16.4 feet) ¹ |
| 9 0 | 9.0 metres (29.5 feet) |

- D:** Connector and Cable-Type Option
- | | |
|------------|---|
| 0 1 | Miniature coaxial ClickLoc™ connector with connector protector, standard cable |
| 0 2 | Miniature coaxial ClickLoc™ connector, standard cable |
| 1 1 | Miniature coaxial ClickLoc™ connector with connector protector, FluidLoc® cable |
| 1 2 | Miniature coaxial ClickLoc™ connector, FluidLoc® cable |

- E:** Agency Approval Option
- | | |
|------------|--------------------|
| 0 0 | Not required |
| 0 5 | Multiple Approvals |

3300 XL 8 mm Reverse Mount Probes

330105-02-12-CXX-DXX-EXX, 3/8-24 UNF threads³

330106-05-30-CXX-DXX-EXX, M10 x 1 threads³

Option Descriptions

- C:** Total Length Option
- | | |
|------------|-------------------------------------|
| 0 5 | 0.5 metre (1.6 feet) |
| 1 0 | 1.0 metre (3.3 feet) |
| 1 5 | 1.5 metre (4.9 feet) |
| 2 0 | 2.0 metres (6.6 feet) |
| 5 0 | 5.0 metres (16.4 feet) ¹ |
| 9 0 | 9.0 metres (29.5 feet) |

- D:** Connector Option
- | | |
|------------|---------------------------------------|
| 0 2 | Miniature ClickLoc™ coaxial connector |
|------------|---------------------------------------|