

330910 3300 NSv Probe, M10X1 thread, with armor

Part Number-AA-BB-CC-DD-EE

A: Unthreaded Length Option



Unthreaded length must be at least 20 mm less than the case length.

Order in increments of 10 mm.

Length configuration:

Maximum unthreaded length:

230 mm

Minimum unthreaded length:

0 mm

Example:

06 = 60 mm

B: Overall Case Length Option

Order in increments of 10 mm.

Metric thread configurations:

Maximum length: 250 mm

Minimum length: 20 mm

Example: **06** = 60 mm

C: Total Length Option

05 0.5 meter (20 in)

10 1.0 meter (39 in)

50 5.0 meters (16.4 feet)

70 7.0 meters (23.0 feet)

D: Connector and Cable-Type Option

01 Miniature coaxial ClickLoc connector with connector protector, standard cable

02 Miniature coaxial ClickLoc connector, standard cable

11 Miniature coaxial ClickLoc connector with connector protector, FluidLoc cable

12 Miniature coaxial ClickLoc connector, FluidLoc cable

E: Agency Approval Option

00 Not required

05 Multiple Approvals

3300 NSv Reverse Mount Probe

330906-02-12-CC-DD-EE 3/8-24 UNF threads

330907-05-30- CC-DD-EE M10X1 threads

C: Total Length Option

05 0.5 meter (20 in)

10 1.0 meter (39 in)

50 5.0 meters (16.4 feet)

70 7.0 meters (23.0 feet)


D: Connector Option

02 Miniature coaxial ClickLoc connector, standard cable

12 Miniature coaxial ClickLoc connector, FluidLoc cable

E: Agency Approval Option

00 Not required

| | |
|-----------|---|
| 05 | <p>Multiple Approvals</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;">  For a shorter delivery time, order commonly stocked probes. Currently, stocked probes consist of the following part numbers: 330901-00-24-05-02-00, 330901-00-90-05-02-00, 330902-00-50-05-02-00, 330902-00-95-05-02-00, 330903-00-02-10-02-00, 330903-00-03-10-02-00, 330906-02-12-05-02-00. </div> |
|-----------|---|

3300 XL NSv Proximitor Sensor

330980-AA-BB

A: Total Length and Mounting Option


| | |
|-----------|---|
| 50 | 5.0 meters (16.4 feet) system length, panel mount |
| 51 | 5.0 meters (16.4 feet) system length, DIN mount |
| 52 | 5.0 meters (16.4 feet) system length, no mounting hardware ¹ |
| 70 | 7.0 meters (23.0 feet) system length, panel mount |
| 71 | 7.0 meters (23.0 feet) system length, DIN mount |
| 72 | 7.0 meters (23.0 feet) system length, no mounting hardware ¹ |

B: Agency Approval Option

| | |
|-----------|--------------------|
| 00 | Not required |
| 05 | Multiple approvals |

3300 NSv Extension Cable

330930-AAA-BB-CC

 Make sure that the extension cable length and the probe length, when added together, equal the Proximitor Sensor total length.

A: Cable Length Option

| | |
|------------|------------------------|
| 040 | 4.0 meters (13.1 feet) |
| 045 | 4.5 meters (14.8 feet) |
| 060 | 6.0 meters (19.7 feet) |
| 065 | 6.5 meters (21.3 feet) |

B: Connector and Cable Option

| | |
|-----------|--|
| 00 | Without stainless steel armor |
| 01 | With stainless steel armor, with FEP jacket |
| 02 | With stainless steel armor, without FEP jacket |
| 03 | Without stainless steel armor, with connector protector |
| 04 | With stainless steel armor, with FEP jacket, with connector protector |
| 05 | With stainless steel armor, without FEP jacket, with connector protector |
| 06 | FluidLoc cable without stainless steel armor |
| 07 | FluidLoc cable with stainless steel armor, with FEP jacket |
| 08 | FluidLoc cable with stainless steel armor, without FEP jacket |
| 09 | FluidLoc without stainless steel armor, with connector protector |