

## Ordering Information



For the detailed listing of country and product-specific approvals, refer to the [Approvals Quick Reference Guide \(108M1756\)](#).

For additional technical documentation, please log in to [bntechsupport.com](http://bntechsupport.com) and access the Bently Nevada Media Library.

**Table 1: Maximum "C" Option plus "D" Option for different "B" Options (probe cable length)**

Probe Cable Length	Maximum C plus D
0.5 meter	394 mm (15.5 in)
1.0 meter	760 mm (30.0 in)

**Table 2: Maximum "C" Option plus "D" Option for different "B" Options (probe cable length) where P/N and S/N Label on Probe Cable is visible outside of probe sleeve**

Probe Cable Length	Maximum C plus D with Visible P/N and S/N Label
0.5 meter	64 mm (2.5 in)
1.0 meter	483 mm (19.0 in)



Conduit fittings are necessary when hardline conduit or metal tubing is brought into the housing. Flexible conduit should be ordered with integral 3/4-14 NPT fittings and do not require additional conduit fittings with the housing. If using flexible conduit, order the "E" = 00 option.

## English Proximity Probe Housing Assemblies

### 31000 - AA-BB-CC-DDD-EE-FF

#### A: Probe with Connector

00	Probe not required
16	3300 XL 8 mm probe
26	3300 XL NSv probe
27	3300 XL NSv probe, multiple approvals
28	3300 XL 8 mm probe, multiple approvals
29	3300 XL 8 mm probe, with connector protector
30	3300 XL 8 mm probe, with connector protector, multiple approvals
31	3300 XL NSv probe with connector protector
32	3300 XL NSv probe with connector protector, multiple approvals
33	3300 XL 11 mm probe
34	3300 XL 11 mm probe, multiple approvals
35	3300 XL 11 mm probe with connector protector
36	3300 XL 11 mm probe with connector protector, multiple approvals

#### B: Probe Cable Length

00	Probe cable not required (Option A must also be 00)
05	0.5 m (20 in)
10	1.0 m (39 in)

#### C: Standoff Adapter Length (Option C Dimension)



Must be ordered if Standoff Adapter Length option is not 00.

<b>15</b>	Minimum length 1.5 in (38 mm)
<b>75</b>	Maximum length 7.5 in (191 mm)
	<b>Recommendation</b> Order in increments of 0.5 in (13 mm)
	<b>Examples</b> 1.5 in (38 mm) = <b>15</b> No standoff adapter = <b>00</b>

**D: Probe Penetration Option (Option D Dimension)**

<b>10</b>	Minimum length 1.0 in (25.4 mm)
	<b>Recommendation</b> Order in increments of 0.1 in (3 mm)
	<b>Examples</b> No probe sleeve = <b>000</b> 3.7 in (94 mm) = <b>037</b> 22.4 in (569 mm) = <b>224</b>



"C" plus "D" dimensions greater than 12 in (305 mm) require additional sleeve support near the probe to prevent resonance from occurring. Sleeve adjustment range of Probe Penetration Option "D" is ±0.5 in (13 mm).

For probe penetration lengths between 1.0 and 2.0 inches, it may be necessary to counter bore the machine case to reduce probe side view or rear view effects.

**E: Fittings**

<b>00</b>	Without fittings
<b>01</b>	One 3/4-14 NPT fitting, two plugs.
<b>02</b>	Two 3/4-14 NPT fittings, one plug.

<b>03</b>	Two plugs, one 3/4-14 NPT fitting One 3/4-14 to 1/2-14 NPT SST reducer One cable seal grip with grommets for the following cable sizes: • 1/8 to 3/16 inches • 1/4 to 5/16 inches • 5/16 to 3/8 inches
<b>06</b>	One 3/4-14 NPT fitting One 3/4-14 NPT to 1/2-14 NPR SST reducer Two plugs
<b>F: Mounting Thread Option</b>	
<b>00</b>	No outer sleeve, retainer, or retaining nut
<b>02</b>	3/4-14 NPT (Required if ordering Standoff Adapter Option).
<b>05</b>	7/8-14 UNF 2A