

D: Agency Approval Option

| | |
|-----------|----------------------------|
| 00 | Not required |
| 05 | CSA, ATEX, IECEx Approvals |


3300 XL 8 mm Extended Temperature Range (ETR) Proximity Probes, Metric:

330193 3300 XL 8 mm Probe, M10 x 1 thread, without armor

330194 3300 XL 8 mm Probe, M10 x 1 thread, with armor

Part Number-AA-BB-CC-DD

A: Unthreaded Length Option

 Unthreaded length must be at least 20 mm less than the case length.

Order in increments of 10 mm

Length configurations:

Maximum unthreaded length: 230 mm

Minimum unthreaded length: 0 mm

Example: **0 6** = 60 mm

B: Overall Case Length Option

Order in increments of 10 mm

Metric thread configurations:

Maximum case length: 250 mm

Minimum case length: 20 mm

Example: **0 6** = 60 mm

C: Total Length Option

| | |
|-----------|------------------------|
| 05 | 0.5 meter (1.6 feet) |
| 10 | 1.0 meter (3.3 feet) |
| 15 | 1.5 meter (4.9 feet) |
| 20 | 2.0 meters (6.6 feet) |
| 50 | 5.0 meters (16.4 feet) |
| 90 | 9.0 meters (29.5 feet) |



5-meter probes are designed for use with the 5 meter Proximitor sensor only.

D: Agency Approval Option

| | |
|-----------|----------------------------|
| 00 | Not required |
| 05 | CSA, ATEX, IECEx Approvals |

3300 XL 8 mm Extended Temperature Range (ETR) Reverse Mount Probes

330195-02-12-CC-DD 3/8-24 UNF threads

330196-05-30-CC-DD M10 x 1 threads

C: Total Length Option

| | |
|-----------|------------------------|
| 05 | 0.5 meter (1.6 feet) |
| 10 | 1.0 meter (3.3 feet) |
| 15 | 1.5 meter (4.9 feet) |
| 20 | 2.0 meters (6.6 feet) |
| 50 | 5.0 meters (16.4 feet) |
| 90 | 9.0 meters (29.5 feet) |



5-meter probes are designed for use with the 5 meter Proximitor sensor only.

D: Agency Approval Option

| | |
|-----------|----------------------------|
| 00 | Not required |
| 05 | CSA, ATEX, IECEx approvals |

3300 XL 8 mm Extended Temperature Range (ETR) Proximity Probes, Smooth Case:

330197 3300 XL 8 mm Probe without armor 1

330198 3300 XL 8 mm Probe with armor 1

Part Number-AA-BB-CC