

| | |
|-----------|---|
| 03 | Armored cable with connector protector |
| 10 | FluidLoc cable |
| 11 | Armored FluidLoc cable |
| 12 | FluidLoc cable with connector protector |
| 13 | Armored FluidLoc cable with connector protector |

C: Agency Approval Option

| | |
|-----------|----------------------------|
| 00 | Not required |
| 05 | CSA, ATEX, IECEx Approvals |

3300 XL Extended Temperature Range (ETR) Extension Cable

330190-AAA-BB-CC



Make sure that the extension cable length and the probe length, when added together, equal the Proximity Sensor total length.

A: Cable Length Option

| | |
|------------|------------------------|
| 030 | 3.0 meters (9.8 feet) |
| 035 | 3.5 meters (13.1 feet) |
| 040 | 4.0 meters (11.5 feet) |
| 045 | 4.5 meters (14.8 feet) |
| 070 | 7.0 meters (22.9 feet) |
| 075 | 7.5 meters (24.6 feet) |
| 080 | 8.0 meters (26.2 feet) |
| 085 | 8.5 meters (27.9 feet) |

B: Cable Option

| | |
|-----------|----------------|
| 00 | Standard cable |
| 01 | Armored cable |

C: Agency Approval Option

| | |
|-----------|----------------------------|
| 00 | Not required |
| 05 | CSA, ATEX, IECEx Approvals |

Accessories

| | |
|-----------|---|
| 141078 | 3300 XL 8 mm and 3300 5 mm Proximity Transducer System Manual. |
| 175751 | 3300 XL Multi-Purpose Stainless Steel Housing. 12"x12"x6". Can hold up to 8 Proximity Sensors in a DIN-mount configuration or 6 Proximity Sensors in a panel-mount configuration. (Available with ATEX Zone 0 and Zone 1 certifications.) |
| 176467 | 3300 XL Multi-Purpose Stainless Steel Housing. 12"x8"x6". Can hold up to 4 3300XL Proximity Sensors in both DIN-mount and panel-mount configurations. (Available with ATEX Zone 0 and Zone 1 certifications.) |
| 330181 | 3300 XL Multi-Purpose Stainless Steel Housing. 13"x9.5"x7". Can hold up to 8 Proximity sensors in a DIN-mount configuration or 6 Proximity Sensors in a panel-mount configuration. Primarily used by customers requiring hazardous area approvals for their installations. Available with ATEX Zone 0 and Zone 1 and North American Division 1 and Division 2 certifications. |
| 02120015 | Bulk field wire. 1.0 mm ² (18 AWG), 3 conductor, twisted, shielded cable with drain wire. Specify length in feet. |
| 138492-01 | Replacement panel-mount mounting pad. |
| 138493-01 | Replacement DIN-mount mounting pad. |