

Ordering Information



For the detailed listing of country and product-specific approvals, refer to the [Approvals Quick Reference Guide \(108M1756\)](#).

For additional technical documentation, please log in to bntechsupport.com and access the Bently Nevada Media Library.

3300 Ceramic Capped Proximity Probes

146054 3300 Ceramic Capped Probe, 3/8-24 UNF thread, without armor

146054 with Modification 164523 3300 Ceramic Capped Probe, 3/8-24 UNF thread, with armor

Part Number-AA-BB-CC-DD

A:	Overall Case Length Option
	Order in increments of 0.1 in Threaded length configurations: Maximum case length: 4.0 in Minimum case length: 0.8 in
Example	2 4 = 2.4 in

B: Total Length Option

0 5	0.5 meter (1.6 feet)
1 0	1.0 meter (3.3 feet)
2 0	2.0 meters (6.6 feet)
5 0	5.0 meters (16.4 feet) ¹
9 0	9.0 meters (29.5 feet)

C: Connector and Cable-Type Option

0 1	Miniature coaxial ClickLoc connector with connector protector, standard cable
------------	---

0 2	Miniature coaxial ClickLoc connector, standard cable
------------	--

D: Agency Approval Option

0 0	Not required
0 5	CSA, ATEX, IECEx

3300 Ceramic Capped Proximity Probes, Metric

164517, 3300 Ceramic Capped Probe, M10 x 1 thread, without armor

164517 with Modification 172330, 3300 Ceramic Capped Probe, M10 x 1 thread, with armor

Part Number-AA-BB-CC-DD

A:	Overall Case Length Option
	Order in increments of 1 mm. Metric thread configurations: Maximum length: 100 mm Minimum length: 20 mm
Example	0 6 0 = 60 mm

B: Total Length Option

0 5	0.5 meter (1.6 feet)
1 0	1.0 meter (3.3 feet)
2 0	2.0 meters (6.6 feet)
5 0	5.0 meters (16.4 feet) ¹
9 0	9.0 meters (29.5 feet)

C: Connector and Cable-Type Option

0 1	Miniature coaxial ClickLoc connector with connector protector, standard cable
0 2	Miniature coaxial ClickLoc connector, standard cable
D:	Agency Approval Option
0 0	Not required
0 5	Multiple Approvals