

SCALANCE XC106-2, Unmanaged IE switch, 6x 10/100 Mbit/s RJ45 ports, 2x 100 Mbit/s Multimode SC, LED diagnostics, error-signaling contact with set button, redundant Power supply Manual available as a download



<b>Product type designation</b>	<b>SCALANCE XC106-2</b>
<b>Transmission rate</b>	
Transfer rate	10 Mbit/s, 100 Mbit/s
<b>Interfaces / for communication / integrated</b>	
Number of electrical connections	
• for network components or terminal equipment	6; RJ45
Number of 100 Mbit/s SC ports	
• for multimode	2
<b>Interfaces / others</b>	
Number of electrical connections	
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for signaling contact	2-pole terminal block
• for power supply	3-pole terminal block, permanently installed
<b>Signal-Inputs/outputs</b>	

Operating voltage / of the signaling contacts	
<ul style="list-style-type: none"> <li>• at DC / Rated value</li> </ul>	24 V
Operating current / of the signaling contacts	
<ul style="list-style-type: none"> <li>• at DC / maximum</li> </ul>	0.1 A

#### Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
<ul style="list-style-type: none"> <li>• external</li> </ul>	24 V
<ul style="list-style-type: none"> <li>• external / minimum</li> </ul>	9.6 V
<ul style="list-style-type: none"> <li>• external / maximum</li> </ul>	31.2 V
<b>Supply voltage / 1 / Rated value</b>	12 V
<ul style="list-style-type: none"> <li>• Supply voltage / 1 / rated value</li> </ul>	9.6 ... 31.2 V
<ul style="list-style-type: none"> <li>• Type of voltage / 1 / of the supply voltage</li> </ul>	DC
<ul style="list-style-type: none"> <li>• Consumed current / 1 / at rated supply voltage / maximum</li> </ul>	0.4 A
<b>Supply voltage / 2 / Rated value</b>	24 V
<ul style="list-style-type: none"> <li>• Supply voltage / 2 / rated value</li> </ul>	9.6 ... 31.2 V
<ul style="list-style-type: none"> <li>• Type of voltage / 2 / of the supply voltage</li> </ul>	DC
<ul style="list-style-type: none"> <li>• Consumed current / 2 / at rated supply voltage / maximum</li> </ul>	0.2 A
<ul style="list-style-type: none"> <li>• Power loss [W] / 2 / Rated value</li> </ul>	4.8 W
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	2.5 A / 125 V
Power loss [W]	
<ul style="list-style-type: none"> <li>• at DC / at 24 V</li> </ul>	4.8 W

#### Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +85 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +85 °C
Relative humidity	
<ul style="list-style-type: none"> <li>• at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
Protection class IP	IP20

#### Design, dimensions and weight

Design	compact
Width	60 mm
Height	147 mm
Depth	125 mm
Net weight	0.85 kg
Material / of the enclosure	Polycarbonate (PC-GF10)
Mounting type	

• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-300 rail mounting	Yes
• S7-1500 rail mounting	Yes

#### Product properties, functions, components / general

Number of automatically learnable MAC addresses	2048
---	------

#### Product functions / management, configuration

Product function	
• multiport mirroring	No
• CoS	Yes
Product function / switch-managed	No

#### Product functions / Redundancy

Product function	
• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No

#### Standards, specifications, approvals

Standard	
• for hazardous zone	EN 60079-0:2012 + A11:2013, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X, IEC 6079-0:2011, IEC 6079-0-15:2010
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for hazardous zone / from CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T.., Class 1 / Zone 2 / Group IIC / T..
• for emitted interference	EN 61000-6-4 (Class A)

#### Standards, specifications, approvals / CE

Certificate of suitability / CE marking	Yes
---	-----

#### Standards, specifications, approvals / miscellaneous

Laser protection class	LED Class 1
Certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
• E1 approval	No
• EC declaration of conformity EN 61010, IEC 61010-1, UL 61010A-1	Yes
• KC approval	Yes

#### Standards, specifications, approvals / ship classification

Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes