

SIMATIC DP, RS485 REPEATER FOR THE CONNECTION OF PROFIBUS/MPI BUS SYSTEMS WITH MAX. 31 NODES; MAX. 12 MBIT/S, DEGREE OF PROTECTION IP20

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Input current

Current consumption, max.	200 mA; 200 mA without loads at PG/OP socket; 230 mA load at PG/OP socket (5 V/90 mA); 300 mA load at PG/OP socket (24 V/90 mA)
---------------------------	---

Interfaces

PROFIBUS DP	
• Transmission rate, max.	12 Mbit/s; 9.6 kbit/s to 12 Mbit/s

Degree and class of protection

Degree of protection acc. to EN 60529	
• IP20	Yes

Ambient conditions

Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Relative humidity	
• Operation, max.	95 %; at 25 °C

Connection method

Power supply	Terminal block
Bus cables	2 terminal blocks

Dimensions

Width	45 mm
Height	128 mm
Depth	67 mm

Weights

Weight, approx.	350 g
-----------------	-------

last modified:

12.11.2015