

## 3300 XL 8 mm Proximity Probes, Smooth Case:

**330140** 3300 XL 8 mm Probe without armor<sup>(1)</sup>

**330141** 3300 XL 8 mm Probe with armor<sup>(1)</sup>

### Part Number-AA-BB-CC-DD

#### A: Overall Case Length Option

Order in increments of 0.1 in.

##### Length configurations:

Maximum unthreaded length: 9.6 in.

Minimum unthreaded length: 0.8 in.

Example: **24** = 2.4 in.

#### B: Total Length Option

|           |                        |
|-----------|------------------------|
| <b>05</b> | 0.5 meter (1.6 feet)   |
| <b>10</b> | 1.0 meter (3.3 feet)   |
| <b>15</b> | 1.5 meter (4.9 feet)   |
| <b>20</b> | 2.0 meters (6.6 feet)  |
| <b>50</b> | 5.0 meters (16.4 feet) |
| <b>90</b> | 9.0 meters (29.5 feet) |



5-meter probes are designed for use with the 5 meter Proximitor sensor only.

#### C: Connector and Cable-Type Option

|           |                                                                               |
|-----------|-------------------------------------------------------------------------------|
| <b>01</b> | Miniature coaxial ClickLoc connector with connector protector, standard cable |
| <b>02</b> | Miniature coaxial ClickLoc connector, standard cable                          |
| <b>11</b> | Miniature coaxial ClickLoc connector with connector protector, FluidLoc cable |
| <b>12</b> | Miniature coaxial ClickLoc connector, FluidLoc cable                          |

#### D: Agency Approval Option

|           |                            |
|-----------|----------------------------|
| <b>00</b> | Not required               |
| <b>05</b> | CSA, ATEX, IECEx Approvals |

## 3300 XL 8 mm Extended Temperature Range (ETR) Proximity Probes:

**330191** 3300 XL 8 mm ETR Probe, 3/8-24 UNF thread, without armor

**330192** 3300 XL 8 mm ETR Probe, 3/8-24 UNF thread, with armor

### Part Number-AA-BB-CC-DD

#### A: Unthreaded Length Option



Unthreaded length must be at least 0.8 in. less than the case length.

Order in increments of 0.1 in.

##### Length configurations:

Maximum unthreaded length: 8.8 in.

Minimum unthreaded length: 0.0 in.

Example: **15** = 1.5 in.

#### B: Overall Case Length Option

Order in increments of 0.5 in.

##### Standard thread configurations:

Maximum case length: 9.6 in.

Minimum case length: 0.8 in.

Example: **25** = 2.5 in.

#### C: Total Length Option

|           |                        |
|-----------|------------------------|
| <b>05</b> | 0.5 meter (1.6 feet)   |
| <b>10</b> | 1.0 meter (3.3 feet)   |
| <b>15</b> | 1.5 meter (4.9 feet)   |
| <b>20</b> | 2.0 meters (6.6 feet)  |
| <b>50</b> | 5.0 meters (16.4 feet) |
| <b>90</b> | 9.0 meters (29.5 feet) |



5-meter probes are designed for use with the 5 meter Proximitor sensor only.

### D: Agency Approval Option

|           |                            |
|-----------|----------------------------|
| <b>00</b> | Not required               |
| <b>05</b> | CSA, ATEX, IECEx Approvals |

### 3300 XL 8 mm Extended Temperature Range (ETR) Proximity Probes, Metric:

**330193** 3300 XL 8 mm Probe, M10 x 1 thread, without armor

**330194** 3300 XL 8 mm Probe, M10 x 1 thread, with armor

### Part Number-AA-BB-CC-DD

#### A: Unthreaded Length Option



Unthreaded length must be at least 20 mm less than the case length.

Order in increments of 10 mm

#### Length configurations:

Maximum unthreaded length: 230 mm

Minimum unthreaded length: 0 mm

Example: **0 6** = 60 mm

#### B: Overall Case Length Option

Order in increments of 10 mm

#### Metric thread configurations:

Maximum case length: 250 mm

Minimum case length: 20 mm

Example: **0 6** = 60 mm

#### C: Total Length Option

|           |                        |
|-----------|------------------------|
| <b>05</b> | 0.5 meter (1.6 feet)   |
| <b>10</b> | 1.0 meter (3.3 feet)   |
| <b>15</b> | 1.5 meter (4.9 feet)   |
| <b>20</b> | 2.0 meters (6.6 feet)  |
| <b>50</b> | 5.0 meters (16.4 feet) |
| <b>90</b> | 9.0 meters (29.5 feet) |



5-meter probes are designed for use with the 5 meter Proximitor sensor only.

### D: Agency Approval Option

|           |                            |
|-----------|----------------------------|
| <b>00</b> | Not required               |
| <b>05</b> | CSA, ATEX, IECEx Approvals |

### 3300 XL 8 mm Extended Temperature Range (ETR) Reverse Mount Probes

**330195-02-12-CC-DD3**/8-24 UNF threads

**330196-05-30-CC-DD** M10 x 1 threads

#### C: Total Length Option

|           |                        |
|-----------|------------------------|
| <b>05</b> | 0.5 meter (1.6 feet)   |
| <b>10</b> | 1.0 meter (3.3 feet)   |
| <b>15</b> | 1.5 meter (4.9 feet)   |
| <b>20</b> | 2.0 meters (6.6 feet)  |
| <b>50</b> | 5.0 meters (16.4 feet) |
| <b>90</b> | 9.0 meters (29.5 feet) |



5-meter probes are designed for use with the 5 meter Proximitor sensor only.

### D: Agency Approval Option

|           |                            |
|-----------|----------------------------|
| <b>00</b> | Not required               |
| <b>05</b> | CSA, ATEX, IECEx approvals |

### 3300 XL 8 mm Extended Temperature Range (ETR) Proximity Probes, Smooth Case:

**330197** 3300 XL 8 mm Probe without armor 1

**330198** 3300 XL 8 mm Probe with armor 1

### Part Number-AA-BB-CC