

C: Overall Case Length Option

Note: Standard case lengths are 26, 40, 60, 80, 100 and 250 mm for metric cases and 1.0, 2.0, 3.0, 4.0 and 9.9 in. for English cases. There is an additional charge for non-standard case lengths.

Metric Case

Types:

Order in increments of 2 mm

Maximum case length:

250 mm

Minimum case length:

26 mm

Example:

0 5 0 = 50 mm

English and Smooth Case

Types:

Order in increments of 0.1 in

Maximum case length:

9.9 in

Minimum case length:

1.0 in (1.5 in for side exit case types)

Example:

0 2 0 = 2.0 in

D: Total Length Option

1 0 1.0 metre (3.3 feet)

5 0 5.0 metres (16.4 feet)

9 0 9.0 metres (29.5 feet)

Note: Five metre probes are designed for use with the five metre Proximity Sensor only.

E: Armor Option

0 0 No Armor

0 1 with SST Armor

Note: When ordering SST Armor, the minimum probe length is 28 mm or 1.1 inch.

F: Agency Approval Option

0 0 No Approvals

0 5 Multiple Approvals

Note: For a shorter delivery time, order commonly stocked **multi-approvals** probes. Currently, stocked probes consist of the following part numbers:
330851-01-000-020-10-00-05
330851-01-000-030-10-00-05
330851-02-000-040-10-00-05
330851-02-000-080-10-00-05
330851-04-000-015-10-00-05
330851-04-000-020-10-00-05

3300 XL 25 mm Proximity Sensor

330850-AXX-BXX

A: Total Length and Mounting Option

5 0 5.0 metres (16.4 feet) system length, panel mount

5 1 5.0 metres (16.4 feet) system length, DIN mount

9 0 9.0 metres (29.5 feet) system length, panel mount

9 1 9.0 metres (29.5 feet) system length, DIN mount

B: Agency Approval Option

0 0 No Approvals

0 5 Multiple Approvals

3300 XL 25 mm Extension Cable

330854-AXXX-BXX-CXX

Note: Make sure that the extension cable length and the probe length, when added together, equal the Proximity Sensor total length.

A: Cable Length Option

0 4 0 4.0 metres (13.1 feet)

0 8 0 8.0 metres (26.2 feet)

B: Armor and Cable Option

2 4 High Temperature FluidLoc cable

2 5 Armored High Temperature FluidLoc cable

C: Agency Approval Option

0 0 No Approvals

0 5 Multiple Approvals

3300 XL Sliding Bracket

330853-AXX-BXX

A: Bracket Length Option

0 1 Short - Single Differential Expansion Application

	0 2	Long - Complementary Input Differential Expansion Application
B:	Probe Adapter Option	
	0 0	Adapter not supplied
	0 1	1¼-12 Thread
	0 2	M30x2 Thread
	0 3	1.06 in diameter Smooth
	Note: When probe adapters are selected, one is supplied with the short bracket length and two are supplied with the long bracket length.	

Dial Indicator Verification Kit

The dial indicator verification kit contains all of the parts needed to verify accuracy of a differential expansion installation. The kit contains a dial indicator, magnetic base, flex mounting arm, and indicator holding rod all housed in a protective carry case

163854-AXX

A: Measurement Units Option

- 0 1** English Units (0-2 Inch)
- 0 2** Metric Units (0-50 mm)

Accessories

163235

Manual

161984

Performance Specification

148722-01

3300 XL Test Plug. The 3300 XL Test Plug has three self-contained test pins attached to three color-coded wires 1 metre in length, each terminated in a banana plug. The three-pin adapter plugs into the test pin holes on 3300 XL-style Proximity sensors. It is used to check the performance of the Proximity sensor from the test pin holes in the terminal strip without requiring the removal of the field wiring.

330187

Extended Range Micrometer Kit. The extended range micrometer kit contains a precision micrometer and AISI 4140 target and is intended for acceptance testing of

our Bently Nevada extended range transducers. Bracket options are available to hold 8mm - 35mm probes and also the 50 mm DE transducer.

02120015

Bulk field wire. 1.0 mm² (18 AWG), 3 conductor, twisted, shielded cable with drain wire. Specify length in feet.

02173009

Bulk field wire. 1.0 mm² (18 AWG), 3 conductor, twisted, shielded cable. Specify length in feet.

138492-01

Replacement panel-mount mounting pad

138493-01

Replacement DIN-mount mounting pad

04310310

3300 XL Proximity Sensor Panel-mount Screws. Package includes four 6-32 UNC thread forming mounting screws (Supplied standard with 3300 XL Proximity Housings [3300 XL option]).

03200006

Silicone self-fusing tape. A 9.1 metre (10 yard) roll of silicone tape to protect connectors. It is easy to install and provides excellent electrical isolation and protection from the environment. It is not recommended for use inside the casing of the machine.

40113-02

Connector Protector Kit. Connector Protector Kit for 3300 XL probes and extension cables, including connector protectors and installation tools.

29660-01