



Table 1: Interconnection Cables and Accessories

APPLICATION	PART NUMBER	DESCRIPTION
†Note: AA - Specifies the length (in feet) of cable required		
Standard Interconnect Cable	6925-AA†	3-conductor shielded 22 AWG (0.5 mm ²) cable with 3-socket plug at one end, terminal lugs at the other end. Minimum length of 2.0 ft (0.6 m), maximum length of 99 ft (30 m). See Figure 4
Standard Armored Interconnect Cable	16710-AA†	3-conductor shielded 22 AWG (0.5 mm ²) armored cable with 3-socket plug at one end, terminal lugs at the other end. Minimum length of 3.0 ft (0.9 m), maximum length of 99 ft (30 m). See Figure 5
Interconnect Cable with Boot	130539-AA†	3-conductor shielded 18 AWG (1.0 mm ²) cable with 3-socket plug and fluorosilicone elastomer boot at one end, terminal lugs at the other end. Minimum length of 2.0 ft (0.6 m), maximum length of 99 ft (30 m). A manual is available to assist with installation of this cable (part number 133080-01). See Figure 6
Spare Mating Connector	00531080	Mating connector for 330450 HTAS.
Electronics Housing Strap	03818073	1 inch rigid conduit strap for securing the electronics housing. 
Electronics Mounting Hub	03818071	1 inch weather tight hub used to mount the electronics housing in a weatherproof enclosure. 
Seal Ring	03818072	1 inch sealing lock ring used to mount the electronics housing. Two rings are required to mount the electronics. 