

## Ordering Information



For the detailed listing of country and product-specific approvals, refer to the [Approvals Quick Reference Guide \(108M1756\)](#).

For additional technical documentation, please log in to [bntechsupport.com](http://bntechsupport.com) and access the Bently Nevada Media Library.

## Velomitor Piezo-velocity Sensor 330500-AA-BB

### A: Mounting Thread Adaptor Option

|           |                         |
|-----------|-------------------------|
| <b>00</b> | No adapter              |
| <b>01</b> | 1/2 – 20 UNF            |
| <b>02</b> | M8 x 1                  |
| <b>03</b> | 1/4 – 28 UNF            |
| <b>04</b> | 1/4 – 20 UNC            |
| <b>05</b> | Unavailable for 330500. |

Note: For 1/4–18 NPT mounting, order 330525.

|           |              |
|-----------|--------------|
| <b>06</b> | 5/8 – 18 UNF |
| <b>07</b> | 3/8 – 16 UNC |
| <b>08</b> | 1/2 – 13 UNC |

### B: Agency Approval Option

|           |                                |
|-----------|--------------------------------|
| <b>00</b> | Not required                   |
| <b>01</b> | CSA/US/C                       |
| <b>02</b> | ATEX (European)                |
| <b>04</b> | Multiple approvals (CSA, ATEX) |

## Interconnection Cables

### Standard Cable Lengths

| Feet  | Meters (approximate) |
|-------|----------------------|
| 6 ft  | 1.8 m                |
| 8 ft  | 2.4 m                |
| 10 ft | 3.0 m                |
| 12 ft | 3.6 m                |
| 15 ft | 4.5 m                |
| 17 ft | 5.0 m                |
| 20 ft | 6.0 m                |
| 25 ft | 7.6 m                |
| 30 ft | 9.0 m                |
| 33 ft | 10.0 m               |
| 50 ft | 15.2 m               |
| 99 ft | 30.0 m               |

### Custom Cable Part Numbers

You can order custom cable lengths in increments of 1.0 ft (305 mm) at additional cost. Some cables have a minimum and maximum length.



Use 'NN' in these part numbers to specify the length (in feet) of the cable you want to order.