

0 3	75/95 Ω , with armor
0 4	50 Ω , with armor

Adapter

4190-AXX

XX	See Specifications section for dimension details.
----	---

Additional sizes and configurations are available in both standard product and special modifications. Contact your local sales representative for details.

Low Pressure Cable Seal

43501 – AXX – BXX-CXX

A: High Pressure Side Thread Size

0 1	1/2-14 NPT
0 2	3/4-14 NPT

B:Cable Grommet and Washer

0 0	Solid grommet (no holes). Holes must be punched in grommet.
0 2	Grommet will accommodate up to two 25mm and 50mm DE cables. One hole is punched and one is partially pre-drilled.
0 4	Grommet will accommodate up to 4 cables. One hole is punched and three are partially pre-drilled.

C:Low Pressure Side Thread Size

0 1	1/2-14 NPT
0 2	3/4-14 NPT

Junction Boxes

03818016	Cylindrical Junction Box.
----------	---------------------------

03818022	Optional Extension for Cylindrical Junction Box.
03818065	Rectangular Junction Box. Dimensions (W x L x D) 38.1mm x 95.3mm x 29.7mm (1.10in x 1.50in x 3.75in x 1.10in).
03818066	Rectangular Junction Box. Dimensions (W x L x D) 44.5mm x 102mm x 61.0mm (1.75in x 4.00in x 61.0in).

Explosion-Proof Fittings

03818055	1/2-14 NPT Fitting
03818056	3/4-14 NPT Fitting
03818057	1 to 1½ NPT Fitting
03818058	1¼ to 1½ NPT Fitting

Probe Lock Nuts

04301007	3/8-24 UNF-2B.
04301008	M10 x 1-6H.

Accessories for Low Pressure Cable Seal

04490104	Punch tool kit for solid grommet option.
43574-04	Replacement grommet. For up to 4 cables.
43575-04	Replacement washer

Field Wiring

02173006	2-conductor, twisted, shielded 18 AWG (1.0 mm ²).
02173008	3-conductor, twisted, shielded 22 AWG (0.5 mm ²).
02173009	3-conductor, twisted, shielded 18 AWG (1.0 mm ²).