

APTER POWER PRODUCT TECHNICAL REFERENCE

200155-00-CN

Low-Frequency Trendmaster Pro Accelerometer

This is a 200155 low-frequency Trendmaster Pro accelerometer supplied without a mounting stud.

Its piezoelectric sensing element converts case vibration along the sensitive axis into a differential voltage proportional to acceleration for low-frequency machine monitoring.

Document field	Value
Manufacturer	Bently Nevada
Prepared by	Apter Power
Document ID	AP-BN-11-200155-00-CN-TR-R2
Revision	R2
Issue date	2026-08-31

APTER POWER SALES TEAM

INDUSTRIAL AUTOMATION PRODUCT SUPPORT

Three interface paths, one controlled configuration.

WHATSAPP / PHONE

EMAIL

WEBSITE

+86 180 3023 5313

sales13@apterpower.com

www.apterpower.com



SCAN FOR PRODUCT & QUOTE

200155-00-CN

1. Product Overview and Identity

This is a 200155 low-frequency Trendmaster Pro accelerometer supplied without a mounting stud.

Its piezoelectric sensing element converts case vibration along the sensitive axis into a differential voltage proportional to acceleration for low-frequency machine monitoring.

Model Configuration

Field	Verified value
Complete model	200155-00-CN
Manufacturer	Bently Nevada
Product description	Low-Frequency Trendmaster Pro Accelerometer

Key Features

- Exact product identifier: 200155-00-CN
- The accelerometer connects through its top-mounted 5-pin connector and is used with the applicable acceleration-to-velocity channel type in the Trendmaster Pro monitoring architecture.
- It is intended for low-frequency acceleration applications such as fin-fan and slow rotating shafts.
- Select the machine-side mounting hardware separately because the -00 option does not provide a mounting stud.

2. Technical Specifications

Technical data for 200155-00-CN is organized below for engineering review and configuration control.

Parameter	Technical value
Measurement range	+/-196 m/s2 (+/-20 g)
Frequency range	1.5 to 10000 Hz
Sensitivity	10.2 mV/(m/s2)
Mounting stud	None
Housing material	316L stainless steel

Configuration Control

Select the machine-side mounting hardware separately because the -00 option does not provide a mounting stud.

3. Functions, Applications and Components

Core Function

200155-00-CN converts machine-case acceleration along its sensitive axis into an electrical signal. The monitoring channel uses this signal to trend casing vibration and machine structural response.

Application Areas

Application	System role
Bearing housings	200155-00-CN measures casing acceleration at a rigid mounting point.
Pumps and motors	The sensor supports routine machine vibration trending.
Fans and compressors	Case response can be monitored across operating conditions.
Condition monitoring	The electrical output is routed to a compatible acceleration channel.

Compatible Components

- Specified mounting stud or adhesive interface
- Compatible accelerometer signal cable
- Acceleration or acceleration-to-velocity monitor input
- Clean, flat machine measurement surface

4. Installation Precautions

- Select a rigid measurement surface for 200155-00-CN.
- Prepare the surface for the supplied mounting option.
- Orient the sensitive axis toward the vibration direction of interest.
- Route and secure the signal cable to avoid connector loading.

Engineering FAQ - Questions 1 to 4

What engineering function does 200155-00-CN perform in its monitoring loop?

200155-00-CN converts machine-case acceleration along its sensitive axis into an electrical signal. The monitoring channel uses this signal to trend casing vibration and machine structural response.

Which measurement range applies to 200155-00-CN?

The configured measurement range for 200155-00-CN is +/-196 m/s² (+/-20 g).

What frequency range must be checked when specifying 200155-00-CN?

Use 1.5 to 10000 Hz for the frequency range when reviewing this complete model.

How does the sensitivity selection affect 200155-00-CN?

This configuration identifies sensitivity as 10.2 mV/(m/s²); include that value in the installation record.

Manufacturer Technical Source

200150, 200155 and 200157 Accelerometers Datasheet 164986