

MANUFACTURER-SOURCE TECHNICAL REFERENCE

Honeywell MC-TDIY22 51204160-175

MC-TDIY22 Product Information Manual

24 VDC digital input field termination assembly

DOCUMENT SCOPE

Apter Power product reference prepared from product-specific Honeywell technical information. Confirm the complete product identity and installed-system requirements before use. No product photograph is included.

Product / lookup identity	Honeywell MC-TDIY22 51204160-175
Reference number	51204160-175
Document basis	Product-specific Honeywell technical information



Product page

<https://www.apterpower.com/Honeywell/mc-tdiy22-51204160-175>

Apter Power contact

sales13@apterpower.com | +86 180 3023 5313

Workflow and system context

Honeywell MC-TDIY22 51204160-175 is a legacy 24 VDC digital input field termination assembly with compression terminals. Its primary hardware function is 24 VDC digital input field termination assembly.

- | | |
|----|--|
| 01 | System Inputs: 24 VDC digital input field termination assembly |
| 02 | Processing: Honeywell MC-TDIY22 51204160-175 is a legacy 24 VDC digital input field termination assembly with compression terminals. |

Published context and boundaries

- | | |
|----|---|
| 01 | Use MC-TDIY22 with the exact Honeywell host, companion hardware, terminal assembly and field wiring specified for the installed system. |
| 02 | Verify model MC-TDIY22 and part number 51204160-175 on the physical label before use. |
| 03 | Match every MC-TDIY22 connector, terminal, cable and companion assembly before moving field wiring. |

Verification and release checks

01	Verify model MC-TDIY22 and part number 51204160-175 on the physical label before use.
02	Use MC-TDIY22 with the exact Honeywell host, companion hardware, terminal assembly and field wiring specified for the installed system.
03	Match every MC-TDIY22 connector, terminal, cable and companion assembly before moving field wiring.
04	Back up the applicable controller, node, I/O or communication configuration before replacing MC-TDIY22.
05	Isolate energy before handling MC-TDIY22 unless the applicable hardware procedure explicitly permits energized service.
06	Follow ESD controls and protect MC-TDIY22 connectors and printed-circuit assemblies during handling.

Identity and release controls

Verification Status	Product Reference
---------------------	-------------------