

Bently Nevada

330101-02-60-05-01-05

Installation Guide

3300 XL 8 mm 3/8-24 UNF unarmored proximity probe

DOCUMENT SCOPE

Apter Power product reference prepared from product-specific Baker Hughes / Bently Nevada technical information. Confirm the complete product identity and installed-system requirements before use. No product photograph is included.

Product / lookup identity	Bently Nevada 330101-02-60-05-01-05
Reference number	330101-02-60-05-01-05
Document basis	Baker Hughes / Bently Nevada technical documents listed on page 3



Product page

<https://www.apterpower.com/Bently-Nevada/330101-02-60-05-01-05>

Apter Power contact

sales13@apterpower.com | +86 180 3023 5313

Workflow and system context

Bently Nevada 330101-02-60-05-01-05 is a 3300 XL 8 mm unarmored 3/8-24 UNF proximity probe with a 0.5 m system cable and multiple approvals. It is used as a 3300 XL 8 mm 3/8-24 UNF unarmored proximity probe within the matched Bently Nevada machinery-monitoring installation.

- | | |
|----|--|
| 01 | System Inputs: 3300 XL 8 mm 3/8-24 UNF unarmored proximity probe |
| 02 | Processing: Bently Nevada 330101-02-60-05-01-05 is a 3300 XL 8 mm unarmored 3/8-24 UNF proximity probe with a 0.5 m system cable and multiple approvals. |

Published context and boundaries

- | | |
|----|---|
| 01 | Use only with the matching 3300 XL system length and verify the complete order code, target material, installation gap and approved hazardous-area arrangement. |
| 02 | Verify model 330101-02-60-05-01-05 and the complete order code on the physical label before use. |
| 03 | Match every 330101-02-60-05-01-05 connector, terminal, cable and companion assembly before moving field wiring. |

Verification and release checks

01	Verify model 330101-02-60-05-01-05 and the complete order code on the physical label before use.
02	Use only with the matching 3300 XL system length and verify the complete order code, target material, installation gap and approved hazardous-area arrangement.
03	Match every 330101-02-60-05-01-05 connector, terminal, cable and companion assembly before moving field wiring.
04	Back up the applicable controller, monitor, HMI or I/O configuration before replacing 330101-02-60-05-01-05.
05	Isolate energy and follow the approved site safety procedure before handling 330101-02-60-05-01-05.
06	Follow ESD controls and protect 330101-02-60-05-01-05 connectors and printed-circuit assemblies during handling.

Identity and release controls

Verification Status	Verified Product Reference
---------------------	----------------------------

Official Baker Hughes / Bently Nevada sources

3300 XL 8 mm Proximity Transducer System Datasheet	https://dam.bakerhughes.com/m/23d2a1de24360b13/original/3300-XL-8mm-Proximity-Transducer-System-Datasheet-141194-pdf.pdf
--	---