

MANUFACTURER-SOURCE TECHNICAL REFERENCE

Honeywell MC-TAMR03 51309218-175

MC-TAMR03 Product Information Manual

LLMux RTD field termination assembly

DOCUMENT SCOPE

Apter Power product reference prepared from product-specific Honeywell technical information. Confirm the complete product identity and installed-system requirements before use. No product photograph is included.

Product / lookup identity	Honeywell MC-TAMR03 51309218-175
Reference number	51309218-175
Document basis	Product-specific Honeywell technical information



Product page

<https://www.apterpower.com/Honeywell/mc-tamr03-51309218-175>

Apter Power contact

sales13@apterpower.com | +86 180 3023 5313

Workflow and system context

Honeywell MC-TAMR03 is a conformally coated 16-channel LLMux RTD field termination assembly with compression terminals. Its primary hardware function is LLMux RTD field termination assembly.

01	System Inputs: LLMux RTD field termination assembly
02	Processing: Honeywell MC-TAMR03 is a conformally coated 16-channel LLMux RTD field termination assembly with compression terminals. Its part number is 51309218-175.

Published context and boundaries

01	Use MC-TAMR03 with the exact Honeywell host, companion hardware, terminal assembly and field wiring specified for the installed system.
02	Verify model MC-TAMR03 and part number 51309218-175 on the physical label before use.
03	Match every MC-TAMR03 connector, terminal, cable and companion assembly before moving field wiring.

Verification and release checks

01	Verify model MC-TAMR03 and part number 51309218-175 on the physical label before use.
02	Use MC-TAMR03 with the exact Honeywell host, companion hardware, terminal assembly and field wiring specified for the installed system.
03	Match every MC-TAMR03 connector, terminal, cable and companion assembly before moving field wiring.
04	Back up the applicable controller, node, I/O or communication configuration before replacing MC-TAMR03.
05	Isolate energy before handling MC-TAMR03 unless the applicable hardware procedure explicitly permits energized service.
06	Follow ESD controls and protect MC-TAMR03 connectors and printed-circuit assemblies during handling.

Identity and release controls

Verification Status	Product Reference
---------------------	-------------------