

APTER POWER PRODUCT GUIDE

LL02

H&B Contronic Module

The ABB H&B Contronic LL02 is a legacy control-system module identified by the LL02 hardware code. It is retained as a model-specific unit for the installed Contronic assembly.

Manufacturer	ABB
Model	LL02
Product type	H&B Contronic Module
Product family	H&B Contronic
Country	Sweden
HS code	8537101190
Shipping origin	Xiamen, Fujian, China

APTER POWER SALES TEAM

INDUSTRIAL AUTOMATION PRODUCT SUPPORT

Three interface paths, one controlled configuration.

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com



SCAN FOR PRODUCT & QUOTE

1. Product overview and identity

- Maintains the documented LL 02 position in the installed cabinet
- Preserves the original controller-to-module assignment
- Supports model-specific service work without changing the slot identity
- Keeps wiring and configuration aligned with the plant drawing set

Model configuration

Complete model	LL02
Product type	H&B Contronic Module
System family	H&B Contronic

2. Technical specifications

Model-controlled field verification

Use the complete model identity, installed carrier position, wiring schedule and controller configuration as the controlling technical records.

3. Functions, applications and components

LL02 cabinet-position retention

Maintains the documented LL 02 position in the installed cabinet

LL02 control-loop service

Preserves the original controller-to-module assignment

LL02 shutdown maintenance

Supports model-specific service work without changing the slot identity

LL02 engineered replacement planning

Keeps wiring and configuration aligned with the plant drawing set

Associated system components

- H&B Contronic carrier or rack
- installed terminal wiring
- controller configuration
- plant loop drawings

4. Engineering FAQ and source record

How should LL02 be identified before cabinet work?

Read the LL 02 front label, board revision and installed slot, then record all three in the job package.

What compatibility check is required for LL02?

Match LL02 to the original carrier position, connector keying and controller configuration.

How should wiring be handled when removing LL02?

Label every conductor and terminal position before disturbing the LL02 circuit.

What configuration should be retained for LL02?

Retain the slot assignment, loop references and controller database entry associated with LL02.

ASK FOR QUOTE

Contact sales13@apterpower.com or +86 180 3023 5313.