

MANUFACTURER-SOURCE TECHNICAL REFERENCE

Bently Nevada

330101-00-44-15-02-CN

Installation Guide

3300 XL 8 mm 3/8-24 UNF unarmored proximity probe

DOCUMENT SCOPE

Apter Power product reference prepared from product-specific Bently Nevada technical information. Confirm the complete product identity and installed-system requirements before use. No product photograph is included.

Product / lookup identity	Bently Nevada 330101-00-44-15-02-CN
Reference number	330101-00-44-15-02-CN
Document basis	Bently Nevada technical documents listed on page 3



Product page

<https://www.apterpower.com/Bently-Nevada/330101-00-44-15-02-cn>
Apter Power contact

sales13@apterpower.com | +86 180 3023 5313

Workflow and system context

Bently Nevada 330101-00-44-15-02-CN is a 3300 XL 8 mm unarmored proximity probe with a 3/8-24 UNF thread, 4.4 in case length, 1.5 m total length and standard ClickLoc connector. Use it only in the matched Bently Nevada machinery-monitoring installation and verify the complete product code, associated hardware, mounting and wiring before service.

- | | |
|----|---|
| 01 | System Inputs: 3300 XL 8 mm 3/8-24 UNF unarmored proximity probe |
| 02 | Processing: Bently Nevada 330101-00-44-15-02-CN is a 3300 XL 8 mm unarmored proximity probe with a 3/8-24 UNF thread, 4.4 in case length, 1.5 m total length and standard ClickLoc connector. |

Published context and boundaries

- | | |
|----|--|
| 01 | Use only with a matched 3300 XL system length; confirm the complete label, target material, gap setting and site approval requirements before service. |
| 02 | Verify model 330101-00-44-15-02-CN and the complete order code on the physical label before use. |
| 03 | Match every 330101-00-44-15-02-CN connector, terminal, cable and companion assembly before moving field wiring. |

Verification and release checks

01	Verify model 330101-00-44-15-02-CN and the complete order code on the physical label before use.
02	Use only with a matched 3300 XL system length; confirm the complete label, target material, gap setting and site approval requirements before service.
03	Match every 330101-00-44-15-02-CN connector, terminal, cable and companion assembly before moving field wiring.
04	Back up the applicable controller, monitor, HMI or I/O configuration before replacing 330101-00-44-15-02-CN.
05	Isolate energy and follow the approved site safety procedure before handling 330101-00-44-15-02-CN.
06	Follow ESD controls and protect 330101-00-44-15-02-CN connectors and printed-circuit assemblies during handling.

Identity and release controls

Verification Status	Verified Product Reference
---------------------	----------------------------

Official Bently Nevada sources

3300 XL 8 mm Proximity Transducer System Datasheet	https://dam.bakerhughes.com/m/23d2a1de24360b13/original/3300-XL-8mm-Proximity-Transducer-System-Datasheet-141194-pdf.pdf
--	---