

PRODUCT
DASHBOARD

330153-01

3300 XL ClickLoc Connector Kit

Bently Nevada 330153-01 is the standard 3300 XL ClickLoc connector kit for 8 mm probes and extension cables. It supplies the matched connector, sleeve, FEP-tube and sealing materials required to assemble or repair the documented connection.

BRAND

Bently Nevada

ORIGIN

USA

HS CODE

8537101190

SHIPS FROM

Xiamen, Fujian, China

Technical data dashboard

3300 XL ClickLoc Connector Kit

KIT TYPE 3300 XL connector kit	SYSTEM COMPATIBILITY 3300 XL 8 mm probes and extension cables	MALE CLICKLOC CONNECTOR 1
FEMALE CLICKLOC CONNECTOR 1	COLOR-CODED SLEEVES 2	SLIT FEP TUBES 2
SILICONE TAPE STRIPS 1	COMPATIBLE CRIMP TOOL KIT 163356	

Application and support view

Four engineering use cases plus customer-oriented verification questions.

Probe connector field repair

Replaces damaged ClickLoc hardware on a compatible 3300 XL 8 mm probe lead.

Extension-cable connector restoration

Rebuilds the mating end of a documented 3300 XL extension cable.

Turnaround continuity recovery

Supplies and performs connector replacement when a transducer loop fails continuity or insulation checks.

FAQ SNAPSHOT

1 Which transducer cables are compatible with 330153-01?

Spare connector preparation

Provides the complete material set used with the approved crimp tooling and assembly procedure.

2 What ClickLoc parts are included in 330153-01?

3 What insulation materials are supplied in 330153-01?

4 Which tool is listed for installing 330153-01?

Related-series navigator

Eight unique and verified Apter Power destinations for this dashboard.

01 3500/25 enhanced Keyphasor module

02 3500/15 133292-01 power supply

03 3500/05 system rack

04 3500/72M 176449-08 rod position monitor

05 3500/65 145988-02 temperature monitor

06 330500-00-02 Velomitor sensor

07 16925-30 seismic interconnect cable

08 330130-080-02-05 extension cable

Related pages are navigation aids and are not used as manufacturer parameter sources.

Traceability and commissioning closeout

Confirm 330153-01, compatible 3300 XL 8 mm probe and cable, male/female connector positions, sleeve colors, FEP tubing, silicone tape, 163356 tool, cleanliness, ClickLoc lock, continuity, insulation and gap voltage.

OFFICIAL MANUFACTURER SOURCE

3300 XL 8 mm Proximity Transducer System Datasheet

141194 Rev. AM

ENGINEERING RELEASE NOTE

Install 330153-01 only on compatible 3300 XL 8 mm probe and extension-cable assemblies using the approved crimp tool and connector instructions. Keep the conductor, dielectric and shield clean, then verify ClickLoc engagement, continuity, insulation and system gap voltage.

APTER POWER SALES TEAM

WHATSAPP / PHONE

+86 180 3023 5313

EMAIL

sales13@apterpower.com

WEBSITE

www.apterpower.com



330153-01