

INDUSTRIAL AUTOMATION PRODUCT

330104-00-05-10-11-00

3300 XL 8 mm Metric Armored Proximity Probe

330104-00-05-10-11-00 senses shaft-to-bearing relative displacement without mechanical contact and passes the probe signal to a matched Proximitor Sensor for machinery-monitoring measurement.

| IDENTITY      | VERIFIED VALUE                                         |
|---------------|--------------------------------------------------------|
| Manufacturer  | Bently Nevada                                          |
| System family | Bently Nevada 3300 XL 8 mm Proximity Transducer System |
| Part number   | 330104-00-05-10-11-00                                  |
| Country       | USA                                                    |
| HS code       | 8537101190                                             |

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313  
EMAIL sales13@apterpower.com  
WEBSITE www.apterpower.com



## 2

## Technical Specifications

Technical values below are limited to the named Bently Nevada product record.

| PARAMETER                       | VALUE                                     |
|---------------------------------|-------------------------------------------|
| Complete order number           | 330104-00-05-10-11-00                     |
| Probe construction              | With armor                                |
| Thread                          | M10 x 1                                   |
| Unthreaded length               | 0 mm                                      |
| Case length                     | 50 mm                                     |
| Total probe length              | 1.0 m                                     |
| Connector option                | Miniature coaxial ClickLoc with protector |
| Probe-cable type                | FluidLoc cable                            |
| Approval option                 | Not required                              |
| Probe-tip diameter              | 8.0 mm                                    |
| System linear range             | 2.0 mm (80 mils)                          |
| Approximate linear-range limits | 0.25 to 2.3 mm                            |
| Approximate output span         | -1 to -17 V DC                            |
| Recommended gap                 | 1.27 mm (50 mils)                         |

| PARAMETER                          | VALUE                                     |
|------------------------------------|-------------------------------------------|
| Nominal output at recommended gap  | -9 V DC                                   |
| Incremental scale factor           | 7.87 V/mm (200 mV/mil)                    |
| Frequency response                 | 0 to 10 kHz, +0/-3 dB                     |
| Minimum flat-target diameter       | 15.2 mm                                   |
| Minimum shaft diameter             | 50.8 mm                                   |
| Recommended shaft diameter         | 76.2 mm                                   |
| Probe-cable impedance              | 75 ohm                                    |
| Standard probe-cable temperature   | -52 to +177 degC                          |
| Proximito Sensor supply            | -17.5 to -26 V DC                         |
| Proximito Sensor current           | 12 mA maximum                             |
| Proximito Sensor output resistance | 50 ohm                                    |
| Field-wiring conductor range       | 0.2 to 1.5 mm <sup>2</sup> (16 to 24 AWG) |
| Maximum field-wiring length        | 305 m                                     |

### VERIFIED PRODUCT RECORD

| DATA GROUP                 | VERIFIED VALUE                                                           |
|----------------------------|--------------------------------------------------------------------------|
| Installed host / carrier   | 3300 XL 8 mm Proximito Sensor                                            |
| Companion hardware         | Matched 3300 XL extension cable when required                            |
| Field connection           | AISI 4140 steel target or validated equivalent                           |
| Primary system function    | Uses the with armor probe construction selected by 330104-00-05-10-11-00 |
| Controlled acceptance duty | Radial shaft-vibration measurement                                       |

3

## System Role and Architecture

330104-00-05-10-11-00 senses shaft-to-bearing relative displacement without mechanical contact and passes the probe signal to a matched Proximitor Sensor for machinery-monitoring measurement.

**FUNCTION 1**

Uses the with armor probe construction selected by 330104-00-05-10-11-00

**FUNCTION 2**

Fits the documented M10 x 1 mounting thread

**FUNCTION 3**

Carries the eddy-current signal through the selected fluidloc cable lead

**FUNCTION 4**

Forms the sensing element of a matched 3300 XL 8 mm transducer system

### Matched system components

- 3300 XL 8 mm Proximitor Sensor
- Matched 3300 XL extension cable when required
- AISI 4140 steel target or validated equivalent
- Compatible Bently Nevada monitor channel

### SYSTEM INTEGRATION RECORD

| INTEGRATION ITEM           | DOCUMENTED ROLE                                                          |
|----------------------------|--------------------------------------------------------------------------|
| Installed host / carrier   | 3300 XL 8 mm Proximitor Sensor                                           |
| Companion hardware         | Matched 3300 XL extension cable when required                            |
| Field connection           | AISI 4140 steel target or validated equivalent                           |
| Primary system function    | Uses the with armor probe construction selected by 330104-00-05-10-11-00 |
| Controlled acceptance duty | Radial shaft-vibration measurement                                       |

4

Applications and Engineering Context

Radial shaft-vibration measurement

Uses the with armor probe construction selected by 330104-00-05-10-11-00

Axial position and thrust monitoring

Fits the documented M10 x 1 mounting thread

Machine shaft centerline observation

Carries the eddy-current signal through the selected fluidloc cable lead

Probe replacement in a matched 3300 XL 8 mm loop

Forms the sensing element of a matched 3300 XL 8 mm transducer system

TECHNICAL NOTE

Match 330104-00-05-10-11-00 to a 3300 XL 8 mm Proximitor Sensor and the approved total system length. Set the static gap in the linear region, route the probe lead without tensile loading, and verify polarity and response before enabling protection logic.

MODEL-SPECIFIC ACCEPTANCE EVIDENCE

| CHECK              | ACCEPTANCE CONDITION                                                     |
|--------------------|--------------------------------------------------------------------------|
| Identity           | 330104-00-05-10-11-00 / 330104-00-05-10-11-00 recorded                   |
| Physical interface | 3300 XL 8 mm Proximitor Sensor                                           |
| Companion check    | Matched 3300 XL extension cable when required                            |
| Functional proof   | Uses the with armor probe construction selected by 330104-00-05-10-11-00 |
| Application test   | Radial shaft-vibration measurement                                       |

5

## Engineering Precautions

1

Verify the full 330104-00-05-10-11-00 marking and the 50 mm case length before disturbing the bracket.

2

Place the monitored machine and associated protection channel in the approved maintenance state.

3

Protect the 8 mm PPS probe tip and keep the M10 x 1 thread free from burrs and contamination.

4

Route the 1.0 m fluidloc cable probe lead without sharp bends, crushing or tensile loading.

5

Secure the miniature coaxial clickloc with protector connection and keep exposed coaxial interfaces clean and dry.

### RELATED PRODUCTS ON APTER POWER

| MODEL                 | SYSTEM ROLE                         | APTER POWER PAGE                                |
|-----------------------|-------------------------------------|-------------------------------------------------|
| 330103-00-12-10-02-00 | 3300 XL 8 mm metric proximity probe | <a href="#">View 330103-00-12-10-02-00 page</a> |
| 330103-00-16-10-02-05 | 3300 XL 8 mm metric proximity probe | <a href="#">View 330103-00-16-10-02-05 page</a> |
| 330106-05-30-05-02-00 | 3300 XL 8 mm reverse-mount probe    | <a href="#">View 330106-05-30-05-02-00 page</a> |
| 330130-045-00-00      | 3300 XL standard extension cable    | <a href="#">View 330130-045-00-00 page</a>      |
| 330130-080-02-05      | 3300 XL extension cable             | <a href="#">View 330130-080-02-05 page</a>      |
| 330850-50-00          | 3300 XL NSv extension cable         | <a href="#">View 330850-50-00 page</a>          |
| 330171-00-12-50-01-05 | 3300 XL 5/8 mm proximity probe      | <a href="#">View 330171-00-12-50-01-05 page</a> |
| 330171-00-12-05-01-05 | 3300 XL 5/8 mm proximity probe      | <a href="#">View 330171-00-12-05-01-05 page</a> |

### MANUFACTURER SOURCE RECORD

Bently Nevada 3300 XL 8 mm Proximity Transducer System Datasheet

141194 Rev. AM

### APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL [sales13@apterpower.com](mailto:sales13@apterpower.com)

WEBSITE [www.apterpower.com](http://www.apterpower.com)

