

INDUSTRIAL AUTOMATION PRODUCT

330103-00-06-50-02-00

3300 XL 8 mm Metric Proximity Probe

330103-00-06-50-02-00 senses shaft-to-bearing relative displacement without mechanical contact and passes the probe signal to a matched Proximitor Sensor for machinery-monitoring measurement.

IDENTITY	VERIFIED VALUE
Manufacturer	Bently Nevada
System family	Bently Nevada 3300 XL 8 mm Proximity Transducer System
Part number	330103-00-06-50-02-00
Country	USA
HS code	8537101190

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



2

Technical Specifications

Technical values below are limited to the named Bently Nevada product record.

PARAMETER	VALUE
Complete order number	330103-00-06-50-02-00
Probe construction	Without armor
Thread	M10 x 1
Unthreaded length	0 mm
Case length	60 mm
Total probe length	5.0 m
Connector option	Miniature coaxial ClickLoc
Probe-cable type	Standard cable
Approval option	Not required
Probe-tip diameter	8.0 mm
System linear range	2.0 mm (80 mils)
Approximate linear-range limits	0.25 to 2.3 mm
Approximate output span	-1 to -17 V DC
Recommended gap	1.27 mm (50 mils)

PARAMETER	VALUE
Nominal output at recommended gap	-9 V DC
Incremental scale factor	7.87 V/mm (200 mV/mil)
Frequency response	0 to 10 kHz, +0/-3 dB
Minimum flat-target diameter	15.2 mm
Minimum shaft diameter	50.8 mm
Recommended shaft diameter	76.2 mm
Probe-cable impedance	75 ohm
Standard probe-cable temperature	-52 to +177 degC
Proximito Sensor supply	-17.5 to -26 V DC
Proximito Sensor current	12 mA maximum
Proximito Sensor output resistance	50 ohm
Field-wiring conductor range	0.2 to 1.5 mm ² (16 to 24 AWG)
Maximum field-wiring length	305 m

PUBLISHED REFERENCE CONDITIONS

CONDITION	VALUE
-----------	-------

3

System Role and Architecture

330103-00-06-50-02-00 senses shaft-to-bearing relative displacement without mechanical contact and passes the probe signal to a matched Proximitor Sensor for machinery-monitoring measurement.

FUNCTION 1

Uses the without armor probe construction selected by 330103-00-06-50-02-00

FUNCTION 2

Fits the documented M10 x 1 mounting thread

FUNCTION 3

Carries the eddy-current signal through the selected standard cable lead

FUNCTION 4

Forms the sensing element of a matched 3300 XL 8 mm transducer system

Matched system components

- 3300 XL 8 mm Proximitor Sensor
- Matched 3300 XL extension cable when required
- AISI 4140 steel target or validated equivalent
- Compatible Bently Nevada monitor channel

SYSTEM INTEGRATION RECORD

INTEGRATION ITEM	DOCUMENTED ROLE
Installed host / carrier	3300 XL 8 mm Proximitor Sensor
Companion hardware	Matched 3300 XL extension cable when required
Field connection	AISI 4140 steel target or validated equivalent
Primary system function	Uses the without armor probe construction selected by 330103-00-06-50-02-00
Controlled acceptance duty	Radial shaft-vibration measurement

4

Applications and Engineering Context

Radial shaft-vibration measurement

Uses the without armor probe construction selected by 330103-00-06-50-02-00

Axial position and thrust monitoring

Fits the documented M10 x 1 mounting thread

Machine shaft centerline observation

Carries the eddy-current signal through the selected standard cable lead

Probe replacement in a matched 3300 XL 8 mm loop

Forms the sensing element of a matched 3300 XL 8 mm transducer system

TECHNICAL NOTE

Match 330103-00-06-50-02-00 to a 3300 XL 8 mm Proximitior Sensor and the approved total system length. Set the static gap in the linear region, route the probe lead without tensile loading, and verify polarity and response before enabling protection logic.

MODEL-SPECIFIC ACCEPTANCE EVIDENCE

CHECK	ACCEPTANCE CONDITION
Identity	330103-00-06-50-02-00 / 330103-00-06-50-02-00 recorded
Physical interface	3300 XL 8 mm Proximitior Sensor
Companion check	Matched 3300 XL extension cable when required
Functional proof	Uses the without armor probe construction selected by 330103-00-06-50-02-00
Application test	Radial shaft-vibration measurement

5

Engineering Precautions

1

Verify the full 330103-00-06-50-02-00 marking and the 60 mm case length before disturbing the bracket.

2

Place the monitored machine and associated protection channel in the approved maintenance state.

3

Protect the 8 mm PPS probe tip and keep the M10 x 1 thread free from burrs and contamination.

4

Route the 5.0 m standard cable probe lead without sharp bends, crushing or tensile loading.

5

Secure the miniature coaxial clickloc connection and keep exposed coaxial interfaces clean and dry.

RELATED PRODUCTS ON APTER POWER

MODEL	SYSTEM ROLE	APTER POWER PAGE
330171-00-12-50-01-05	3300 XL 5/8 mm proximity probe	View 330171-00-12-50-01-05 page
330171-00-12-05-01-05	3300 XL 5/8 mm proximity probe	View 330171-00-12-05-01-05 page
330171-00-33-50-01-05	3300 XL 5/8 mm proximity probe	View 330171-00-33-50-01-05 page
330171-00-08-10-01-05	3300 XL 5/8 mm proximity probe	View 330171-00-08-10-01-05 page
330172-00-08-10-01-05	3300 XL 5/8 mm armored proximity probe	View 330172-00-08-10-01-05 page
330103-00-04-10-02-00	3300 XL 8 mm metric proximity probe	View 330103-00-04-10-02-00 page
330103-00-12-10-02-00	3300 XL 8 mm metric proximity probe	View 330103-00-12-10-02-00 page
330103-00-16-10-02-05	3300 XL 8 mm metric proximity probe	View 330103-00-16-10-02-05 page

MANUFACTURER SOURCE RECORD

Bently Nevada 3300 XL 8 mm Proximity Transducer System Datasheet

141194 Rev. AM

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

