

INDUSTRIAL AUTOMATION PRODUCT

330851-02-000-080-10-00-00

3300 XL 25 mm m30 x 2 threaded proximity probe

Large-range non-contact eddy-current displacement signal

IDENTITY	VERIFIED VALUE
Manufacturer	Bently Nevada
System family	3300 XL 25 mm Proximity Transducer System
Part number	330851-02-000-080-10-00-00
Country	USA
HS code	8537101190

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



2

Technical Specifications

Technical values below are limited to the named Bently Nevada product record.

PARAMETER	VALUE
Probe model	330851
Probe case	M30 x 2 threaded
Unthreaded length	0
Overall case length	80 mm
Total probe length	1.0 m (3.3 ft)
Aarmor	No
Agency approval option	Not required
Probe tip material	PEEK
Probe case material	AISI 304 stainless steel
Probe cable	75 Ohm PFA FluidLoc
Probe operating temperature	-35 to +200 degC
Short-term probe temperature	+250 degC maximum for less than 24 h
Power without barriers	-17.5 to -26 V DC; 12 mA maximum

PARAMETER	VALUE
Power with barriers	-23 to -26 V DC
Supply sensitivity	<2 mV/V
Output resistance	50 Ohm
Field-wire conductor range	0.2 to 1.5 mm ² (16 to 24 AWG)
Maximum field-wire length	305 m (1000 ft)
Linear range	12.7 mm (500 mils)
Linear-range limits	0.63 to 13.33 mm (25 to 525 mils)
Average scale factor	0.787 V/mm (20 mV/mil)
Frequency response	0 to 2.7 kHz; +0/-3 dB
Minimum target diameter	61 mm (2.4 in)
Extension-cable capacitance	69.9 pF/m typical
Minimum bend radius	25.4 mm (1.0 in)

VERIFIED PRODUCT RECORD

DATA GROUP	VERIFIED VALUE
Installed host / carrier	3300 XL 25 mm Proximitor Sensor
Companion hardware	matched 25 mm extension cable
Field connection	61 mm or larger steel target
Primary system function	Uses the documented m30 x 2 threaded case
Controlled acceptance duty	Steam-turbine differential expansion

3

System Role and Architecture

Large-range non-contact eddy-current displacement signal

FUNCTION 1

Uses the documented m30 x 2 threaded case

FUNCTION 2

Provides a 80 mm case with a one-metre lead

FUNCTION 3

Uses a PEEK sensing tip for the large target range

FUNCTION 4

Forms the probe element of a matched 25 mm measurement system

Matched system components

- 3300 XL 25 mm Proximator Sensor
- matched 25 mm extension cable
- 61 mm or larger steel target
- compatible displacement monitor

SYSTEM INTEGRATION RECORD

INTEGRATION ITEM	DOCUMENTED ROLE
Installed host / carrier	3300 XL 25 mm Proximator Sensor
Companion hardware	matched 25 mm extension cable
Field connection	61 mm or larger steel target
Primary system function	Uses the documented m30 x 2 threaded case
Controlled acceptance duty	Steam-turbine differential expansion

4

Applications and Engineering Context

Steam-turbine differential expansion

Uses the documented m30 x 2 threaded case

Large-shaft axial position

Provides a 80 mm case with a one-metre lead

Rotor travel observation

Uses a PEEK sensing tip for the large target range

25 mm probe-loop replacement

Forms the probe element of a matched 25 mm measurement system

TECHNICAL NOTE

Confirm the m30 x 2 threaded case, 80 mm length, one-metre FluidLoc lead and complete five- or nine-metre matched system before setting the operating gap.

MODEL-SPECIFIC ACCEPTANCE EVIDENCE

CHECK	ACCEPTANCE CONDITION
Identity	330851-02-000-080-10-00-00 / 330851-02-000-080-10-00-00 recorded
Physical interface	3300 XL 25 mm Proximitior Sensor
Companion check	matched 25 mm extension cable
Functional proof	Uses the documented m30 x 2 threaded case
Application test	Steam-turbine differential expansion

5

Engineering Precautions

- 1 Verify the complete 330851-02-000-080-10-00-00 marking and M30 x 2 threaded execution before work.
- 2 Place the monitored machine and protection channel in the approved maintenance state.
- 3 Protect the sensing tip, threads and mounting surface from impact, burrs and contamination.
- 4 Route and support the 1.0 m lead without sharp bends, crushing, tensile load or contact with moving parts.
- 5 Keep coaxial connector faces clean, dry and mechanically unloaded during handling.

RELATED PRODUCTS ON APTER POWER

MODEL	SYSTEM ROLE	APTER POWER PAGE
3500-15-129486-01	Related Bently Nevada product	View 3500-15-129486-01 page
330103-00-06-10-02-CN	Related Bently Nevada product	View 330103-00-06-10-02-CN page
330101-30-63-15-02-CN	Related Bently Nevada product	View 330101-30-63-15-02-CN page
26363-30	Related Bently Nevada product	View 26363-30 page
3300-12-02-20-00	Related Bently Nevada product	View 3300-12-02-20-00 page
130768-01	Related Bently Nevada product	View 130768-01 page
4300111	Related Bently Nevada product	View 4300111 page
125565-01	Related Bently Nevada product	View 125565-01 page

MANUFACTURER SOURCE RECORD

Bently Nevada 3300 XL 25 mm Proximity Transducer System Datasheet

163236 Rev. M

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com

