

IC670MDL740

12/24 VDC Positive Logic Output Module

GE IC670MDL740 is the documented 12/24 VDC Positive Logic Output Module for the Field Control distributed I/O.

| IDENTITY      | VERIFIED VALUE                                                          |
|---------------|-------------------------------------------------------------------------|
| Manufacturer  | General Electric                                                        |
| System family | Field Control distributed I/O                                           |
| Part number   | IC670MDL740                                                             |
| Product role  | Provides the documented 12/24 vdc positive logic output module function |
| Lifecycle     | Installed product record                                                |

DOCUMENT SCOPE

Exact-article identity, technical data, host role, installation checks, applications, precautions and engineering verification.

MODEL-SPECIFIC ENGINEERING NOTE

Install IC670MDL740 only in the documented Field Control distributed I/O position. Preserve the as-found terminal mapping and configuration, then verify diagnostics and the affected field function under controlled conditions.

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



IC670MDL740

# Technical Specifications

Technical values below are limited to the named General Electric product record and directly applicable manufacturer documentation.

| PARAMETER          | VALUE                          | PARAMETER        | VALUE                 |
|--------------------|--------------------------------|------------------|-----------------------|
| Output points      | 16                             | Module current   | 4 A maximum           |
| Output grouping    | One group                      | Minimum load     | 1 mA per point        |
| User input         | 10 to 30 V DC; 24 V DC nominal | Response time    | 200 us maximum on/off |
| Output voltage     | 9.2 to 29.5 V DC               | BIU current draw | 111 mA maximum        |
| Continuous current | 0.5 A per point                |                  |                       |

## Verified Product Record

| DATA GROUP                 | VERIFIED VALUE                                                                                                                                                                                                                    |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Installed host / carrier   | Field Control distributed I/O                                                                                                                                                                                                     |
| Primary system role        | Provides the documented 12/24 vdc positive logic output module function                                                                                                                                                           |
| Connection boundary        | Install IC670MDL740 only in the documented Field Control distributed I/O position. Preserve the as-found terminal mapping and configuration, then verify diagnostics and the affected field function under controlled conditions. |
| Controlled acceptance duty | Field Control distributed I/O station maintenance                                                                                                                                                                                 |

ENGINEERING BOUNDARY

Confirm IC670MDL740, host, terminals, power grouping, point map and controlled test results before release.

## Pre-Installation Checks

|   |                                                                                                                |   |                                                                                             |
|---|----------------------------------------------------------------------------------------------------------------|---|---------------------------------------------------------------------------------------------|
| 1 | Confirm the full IC670MDL740 catalog marking and installed Field Control distributed I/O position before work. | 2 | Isolate the station supply and connected field energy using the approved procedure.         |
| 3 | Record every terminal, common, shield, connector and configured point before removal.                          | 4 | Use ESD controls and protect backplane, terminal and connector contacts from contamination. |

## Documented Service Record

| RECORD ITEM        | REQUIRED ENTRY                   |
|--------------------|----------------------------------|
| As-found article   | IC670MDL740                      |
| Installed host     | Field Control distributed I/O    |
| Connection record  | Capture before removal           |
| Controlled release | Diagnostics and functional proof |

# System Role and Architecture

GE IC670MDL740 is the documented 12/24 VDC Positive Logic Output Module for the Field Control distributed I/O.

**FUNCTION 1**  
  
Provides the documented 12/24 vdc positive logic output module function

**FUNCTION 2**  
  
Uses exact catalog identity IC670MDL740 for replacement control

**FUNCTION 3**  
  
Integrates with the matched Field Control distributed I/O hardware

**FUNCTION 4**  
  
Supports controlled connection checks and functional verification

## Matched System Components

| NO. | DOCUMENTED COMPONENT / ROLE                                                                                                                                                                                                       |
|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | Field Control distributed I/O                                                                                                                                                                                                     |
| 2   | One group                                                                                                                                                                                                                         |
| 3   | Field Control distributed I/O station maintenance                                                                                                                                                                                 |
| 4   | Install IC670MDL740 only in the documented Field Control distributed I/O position. Preserve the as-found terminal mapping and configuration, then verify diagnostics and the affected field function under controlled conditions. |

## System Integration Record

| INTEGRATION ITEM       | DOCUMENTED ROLE                                                                                                                                                                                                           |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Host identity          | Field Control distributed I/O                                                                                                                                                                                             |
| Interface role         | Provides the documented 12/24 vdc positive logic output module function                                                                                                                                                   |
| Field / power context  | The component is used with the exact terminal assembly, carrier, power grouping and bus configuration identified for IC670MDL740. Commissioning preserves the installed point map and verifies controlled field response. |
| Commissioning evidence | Complete a controlled signal or load test before returning the station to service.                                                                                                                                        |

## Installation and Connection Checks

1

Verify each documented value for IC670MDL740 against the installed host and field circuit.

2

Restore the approved terminal assembly, power grouping and configuration record.

3

Energize in the prescribed sequence and review module, bus and point diagnostics.

4

Complete a controlled signal or load test before returning the station to service.

### MANUFACTURER SOURCE RECORD

Field Control Distributed I/O and Control System I/O Modules User's Manual  
GFK-0826J, June 2002

# Applications and Engineering Context

## Field Control distributed I/O station maintenance

Restores the documented 12/24 vdc positive logic output module function in an engineered station.

## Distributed I/O refurbishment

Uses exact IC670MDL740 identity when rebuilding the recorded field interface.

## Control-panel modernization

Preserves the approved terminal, power and communications arrangement during migration work.

## Controlled recommissioning

Verifies point mapping, diagnostics and field response before process release.

### TECHNICAL NOTE

Install IC670MDL740 only in the documented Field Control distributed I/O position. Preserve the as-found terminal mapping and configuration, then verify diagnostics and the affected field function under controlled conditions.

## Model-Specific Acceptance Evidence

| CHECK              | ACCEPTANCE CONDITION                                                               |
|--------------------|------------------------------------------------------------------------------------|
| Identity           | IC670MDL740 recorded                                                               |
| Host / carrier     | Field Control distributed I/O                                                      |
| Physical interface | Provides the documented 12/24 vdc positive logic output module function            |
| Configuration      | Energize in the prescribed sequence and review module, bus and point diagnostics.  |
| Functional proof   | Complete a controlled signal or load test before returning the station to service. |

## IMPORTANT NOTICE

Confirm IC670MDL740, host, terminals, power grouping, point map and controlled test results before release.

## Controlled Release Summary

| RELEASE ITEM     | MODEL-SPECIFIC CONDITION                                                           |
|------------------|------------------------------------------------------------------------------------|
| Article identity | IC670MDL740                                                                        |
| Approved role    | Field Control distributed I/O station maintenance                                  |
| Final validation | Complete a controlled signal or load test before returning the station to service. |

# Engineering Precautions

- 1

Confirm the full IC670MDL740 catalog marking and installed Field Control distributed I/O position before work.
- 2

Isolate the station supply and connected field energy using the approved procedure.
- 3

Record every terminal, common, shield, connector and configured point before removal.
- 4

Use ESD controls and protect backplane, terminal and connector contacts from contamination.
- 5

Verify each documented value for IC670MDL740 against the installed host and field circuit.
- 6

Restore the approved terminal assembly, power grouping and configuration record.
- 7

Energize in the prescribed sequence and review module, bus and point diagnostics.
- 8

Complete a controlled signal or load test before returning the station to service.

## Related Products on Apter Power

| MODEL                        | SYSTEM ROLE  | APTER POWER PAGE                                       |
|------------------------------|--------------|--------------------------------------------------------|
| MIVII3000E00HI00             | product page | <a href="#">View MIVII3000E00HI00 page</a>             |
| IS215VPROH1BD                | product page | <a href="#">View IS215VPROH1BD page</a>                |
| IS200VCMIH2CAA-IS215VCMIH2CA | product page | <a href="#">View IS200VCMIH2CAA-IS215VCMIH2CA page</a> |
| IC200UDR005-DJ               | product page | <a href="#">View IC200UDR005-DJ page</a>               |
| A06B-6117-H209               | product page | <a href="#">View A06B-6117-H209 page</a>               |
| PCIE-5565PIORC-100A00        | product page | <a href="#">View PCIE-5565PIORC-100A00 page</a>        |
| A06B-6096-H106               | product page | <a href="#">View A06B-6096-H106 page</a>               |
| A06B-6096-H104               | product page | <a href="#">View A06B-6096-H104 page</a>               |

## MANUFACTURER SOURCE RECORD

Field Control Distributed I/O and Control System I/O Modules User's Manual  
GFK-0826J, June 2002

### APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313  
EMAIL sales13@apterpower.com  
WEBSITE www.apterpower.com



IC670MDL740