

IC698CPE010

PACSystems RX7i 300 MHz CPU

GE IC698CPE010 is a 300 MHz PACSystems RX7i CPU with 10 MB of battery-backed user memory, 10 MB of nonvolatile flash memory and integrated Ethernet and serial communications. It executes RX7i control logic and coordinates supported Series 90-70 I/O and VME modules.

BRAND	GE	ORIGIN	USA
MODEL	IC698CPE010	HS CODE	8537101190
FAMILY	PACSystems RX7i	SHIP FROM	Xiamen, Fujian, China

MANUFACTURER SOURCE RECORD

PACSystems RX7i CPE010/CPE020 Important Product Information
GE Intelligent Platforms publication GFK-2244AG, February 2012; CPU Reference Manual GFK-2222

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 531

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



IC698CPE010

Product Overview

SYSTEM FUNCTION

GE IC698CPE010 is a 300 MHz PACSystems RX7i CPU with 10 MB of battery-backed user memory, 10 MB of nonvolatile flash memory and integrated Ethernet and serial communications. It executes RX7i control logic and coordinates supported Series 90-70 I/O and VME modules.

FUNCTION 1

300 MHz RX7i controller execution platform

FUNCTION 2

10 MB battery-backed RAM plus 10 MB flash memory

FUNCTION 3

Two integrated switched 10/100 Ethernet ports

FUNCTION 4

Supports Series 90-70 I/O and VME modules

TECHNICAL NOTE

Record the IC698CPE010 firmware, rack slot, Ethernet settings, serial-port assignments and application checksum before replacement. Restore the approved hardware configuration and prove I/O, communications and control logic before releasing the RX7i system.

Technical Data and Acceptance

PARAMETER	VERIFIED VALUE
Processor	300 MHz Celeron
Battery-backed user memory	10 MB
Nonvolatile flash user memory	10 MB
Configurable %W memory	Up to 4 MB
Discrete references	32 Kbits each for %I and %Q
Analog references	Up to 32 Kwords each for %AI and %AQ
Program blocks	Up to 512; 128 KB maximum per block
Ethernet	Two switched 10/100BASE-T ports
Serial interfaces	Isolated RS-485, RS-232 and station manager
Operating temperature	0 to 50 °C without fan; 0 to 60 °C with fan tray

ENGINEERING BOUNDARY

Record the IC698CPE010 firmware, rack slot, Ethernet settings, serial-port assignments and application checksum before replacement. Restore the approved hardware configuration and prove I/O, communications and control logic before releasing the RX7i system.

Acceptance Path

1 IDENTITY

IC698CPE010, firmware and rack position are recorded.

2 CONFIGURATION

Hardware configuration and application checksum match the approved record.

3 COMMUNICATIONS

Ethernet and serial services operate without unexplained faults.

4 FUNCTIONAL PROOF

I/O scan and controlled logic test pass before process release.

Applications and Engineering FAQ

APPLICATION	ENGINEERING CONTEXT
RX7i machine control	Executes deterministic logic and coordinates local or networked I/O in an RX7i rack.
Legacy Series 90-70 migration	Retains support for documented Series 90-70 I/O and VME modules in a PACSystems controller.
Industrial Ethernet integration	Uses SRTP, EGD and Modbus TCP services through the integrated switched ports.
Supervisory and serial connectivity	Supports isolated serial communication, station management and time synchronization.

Model-Specific FAQ — Part 1

QUESTION	ANSWER
What processor is used by GE IC698CPE010?	IC698CPE010 uses a 300 MHz Celeron processor.
How much user memory does GE IC698CPE010 provide?	It provides 10 MB of battery-backed user RAM and 10 MB of nonvolatile flash user memory.
How many Ethernet ports are built into GE IC698CPE010?	The CPU provides two switched RJ45 ports supporting 10BASE-T and 100BASE-TX.
Which Ethernet services are documented for GE IC698CPE010?	The official information lists SRTP, Ethernet Global Data and Modbus TCP server/client services.

FAQ, Related Products and Source

Related Products on Apter Power

QUESTION	ANSWER	MODEL	APTER POWER PAGE
Which programming languages are supported by GE IC698CPE010?	The RX7i CPU documentation lists ladder diagram, structured text, function block diagram and C blocks.	ic693pwr330	View ic693pwr330
Can GE IC698CPE010 operate at 60 °C?	Yes, but the published 0 to 60 °C range requires the documented fan tray; without it the upper limit is 50 °C.	ic693pwr331	View ic693pwr331
Does GE IC698CPE010 support Series 90-70 I/O?	Yes. The RX7i CPU supports documented Series 90-70 I/O and VME modules subject to configuration and firmware requirements.	ic693pwr331d	View ic693pwr331d
What should be verified after replacing GE IC698CPE010?	Verify firmware, application checksum, reference memory, Ethernet and serial settings, I/O health and the controlled process test.	is200egdmh1afg	View is200egdmh1afg
		ic697alg320	View ic697alg320
		ic697bem711	View ic697bem711
		ic697bem731	View ic697bem731
		ic660bba100	View ic660bba100

MANUFACTURER SOURCE RECORD

PACSystems RX7i CPE010/CPE020 Important Product Information
GE Intelligent Platforms publication GFK-2244AG, February 2012; CPU Reference Manual GFK-2222

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



IC698CPE010