

IC670MDL644

12/24 VDC Fast Positive/Negative Input Module

GE IC670MDL644 is a 12/24 VDC Fast Positive/Negative Input Module for the Field Control distributed I/O. It provides the documented field interface or control function in the configured system.

BRAND	General Electric	FAMILY	Field Control distributed I/O
PART	IC670MDL644	SYSTEM ROLE	Provides the documented 12/24 vdc fast positive/negative input module function

APTER POWER SALES
TEAM

WHATSAPP / PHONE
+86 180 3023 5313
EMAIL sales13@apterp
ower.com
WEBSITE
www.apterpower.com



IC670MDL644

MANUFACTURER SOURCE RECORD

Field Control Distributed I/O and Control System I/O Modules User's Manual
GFK-0826J, June 2002

Product Overview

SYSTEM FUNCTION

GE IC670MDL644 is a 12/24 VDC Fast Positive/Negative Input Module for the Field Control distributed I/O. It provides the documented field interface or control function in the configured system.

FUNCTION 1

Provides the documented 12/24 vdc fast positive/negative input module function

FUNCTION 2

Uses exact catalog identity IC670MDL644 for replacement control

FUNCTION 3

Integrates with the matched Field Control distributed I/O hardware

FUNCTION 4

Supports controlled connection checks and functional verification

System Components

COMPONENT	DOCUMENTED ROLE
Host / carrier	Field Control distributed I/O
Primary interface	Provides the documented 12/24 vdc fast positive/negative input module function
Engineering context	The component is used with the exact terminal assembly, carrier, power grouping and bus configuration identified for IC670MDL644. Commissioning preserves the installed point map and verifies controlled field response.
Commissioning duty	Complete a controlled signal or load test before returning the station to service.

TECHNICAL NOTE

Install IC670MDL644 only in the documented Field Control distributed I/O position. Preserve the as-found terminal mapping and configuration, then verify diagnostics and the affected field function under controlled conditions.

Technical Data

PARAMETER	VALUE	PARAMETER	VALUE
Input points	16	Input impedance	3 kohm
Input grouping	One group	On response	25 us typical; 60 us maximum
Rated voltage	12/24 V DC	Off response	100 us typical; 150 us maximum
Input voltage range	0 to 30 V DC	BIU current draw	80 mA maximum
Input current	8 mA per point at 24 V DC		

Related Products on Apter Power

MODEL	SYSTEM ROLE	APTER POWER PAGE
F31X134EPRBEG1-FR00-0	product page	View F31X134EPRBEG1-FR00-0 page
IC200MDL740	product page	View IC200MDL740 page
DS200ADGIH1AAA	product page	View DS200ADGIH1AAA page
A06B-0104-B111-7000	product page	View A06B-0104-B111-7000 page
750-P5-G5-HI-A1-R-E	product page	View 750-P5-G5-HI-A1-R-E page
IC693MDL741G	product page	View IC693MDL741G page
IC670MDL640	product page	View IC670MDL640 page
DS200SLCCG3AFG	product page	View DS200SLCCG3AFG page

ENGINEERING BOUNDARY

Confirm IC670MDL644, Field Control distributed I/O host, hardware revision, terminal or connector type, power and signal ranges, wiring, grounding, bus configuration, companion accessories and controlled commissioning results before service release.

Applications and Precautions

Common Applications

Field Control distributed I/O station maintenance

Restores the documented 12/24 vdc fast positive/negative input module function in an engineered station.

Distributed I/O refurbishment

Uses exact IC670MDL644 identity when rebuilding the recorded field interface.

Control-panel modernization

Preserves the approved terminal, power and communications arrangement during migration work.

Controlled recommissioning

Verifies point mapping, diagnostics and field response before process release.

Product Precautions

- 1

Confirm the full IC670MDL644 catalog marking and installed Field Control distributed I/O position before work.
- 2

Isolate the station supply and connected field energy using the approved procedure.
- 3

Record every terminal, common, shield, connector and configured point before removal.
- 4

Use ESD controls and protect backplane, terminal and connector contacts from contamination.
- 5

Verify each documented value for IC670MDL644 against the installed host and field circuit.
- 6

Restore the approved terminal assembly, power grouping and configuration record.
- 7

Energize in the prescribed sequence and review module, bus and point diagnostics.
- 8

Complete a controlled signal or load test before returning the station to service.

IMPORTANT NOTICE

Confirm IC670MDL644, Field Control distributed I/O host, hardware revision, terminal or connector type, power and signal ranges, wiring, grounding, bus configuration, companion accessories and controlled commissioning results before service release.

ACCEPTANCE CHECK	REQUIRED EVIDENCE
Identity	IC670MDL644
Configuration	Energize in the prescribed sequence and review module, bus and point diagnostics.
Functional release	Complete a controlled signal or load test before returning the station to service.

Engineer FAQ

Q1 How is IC670MDL644 identified?

Match the complete catalog number and the 12/24 VDC Fast Positive/Negative Input Module designation.

Q3 What records are retained before removing IC670MDL644?

Record terminals, commons, shields, connectors, point mapping and diagnostics.

Q5 Which official values govern IC670MDL644?

Input points: 16; Input grouping: One group; Rated voltage: 12/24 V DC; Input voltage range: 0 to 30 V DC.

Q7 Which diagnostics follow IC670MDL644 energization?

Review module, bus and channel status in the prescribed startup sequence.

Q2 Which system accepts IC670MDL644?

Use the documented Field Control distributed I/O carrier, terminal and bus arrangement.

Q4 How is IC670MDL644 isolated safely?

Isolate station and field supplies, prove the safe state and apply ESD controls.

Q6 How is IC670MDL644 configuration restored?

Restore the approved hardware execution, power grouping and point map.

Q8 What releases IC670MDL644 to service?

A controlled signal or load test with the expected field response and no active diagnostic.

MANUFACTURER SOURCE RECORD

Field Control Distributed I/O and Control System I/O Modules User's Manual
GFK-0826J, June 2002

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



IC670MDL644