

330103-00-04-10-01-05

3300 XL 8 mm Proximity Probe

Bently Nevada 330103-00-04-10-01-05 is the documented 3300 XL 8 mm Proximity Probe for the matched Bently Nevada 3300 XL 8 mm Proximity Transducer System.

BRAND	Bently Nevada	FAMILY	Bently Nevada 3300 XL 8 mm Proximity Transducer System
PART	330103-00-04-10-01-05	SYSTEM ROLE	Exact article identity: Bently Nevada 330103-00-04-10-01-05

APTER POWER SALES
TEAM

WHATSAPP / PHONE
+86 180 3023 5313
EMAIL sales13@apterp
ower.com
WEBSITE
www.apterpower.com



330103-00-04-10-01-05

MANUFACTURER SOURCE RECORD

3300 XL 8 mm Proximity Transducer System Datasheet
141194 Rev. AM

Product Overview

SYSTEM FUNCTION

Bently Nevada 330103-00-04-10-01-05 is the documented 3300 XL 8 mm Proximity Probe for the matched Bently Nevada 3300 XL 8 mm Proximity Transducer System.

FUNCTION 1

Exact article identity: Bently Nevada 330103-00-04-10-01-05

FUNCTION 2

Documented component: 3300 XL 8 mm Proximity Probe

FUNCTION 3

Installed family: Bently Nevada 3300 XL 8 mm Proximity Transducer System

FUNCTION 4

Controlled replacement and verification workflow

System Components

COMPONENT	DOCUMENTED ROLE
Host / carrier	Bently Nevada 3300 XL 8 mm Proximity Transducer System
Primary interface	Exact article identity: Bently Nevada 330103-00-04-10-01-05
Engineering context	Use 330103-00-04-10-01-05 only with the documented Bently Nevada host system and matched interfaces. Preserve the as-found configuration during replacement and commissioning.
Commissioning duty	Complete a controlled response and alarm test before service release.

TECHNICAL NOTE

Match 330103-00-04-10-01-05 to the documented host, physical interface and connection arrangement. Restore the recorded configuration and verify diagnostics and controlled channel response before release.

Technical Data

PARAMETER	VALUE	PARAMETER	VALUE
Complete order number	330103-00-04-10-01-05	Connector and cable option	Miniature coaxial ClickLoc with connector protector, standard cable
Probe construction	Without armor	Approval option	Multiple approvals
Mounting thread	M10 x 1	Probe-tip diameter	8.0 mm
Unthreaded length	0 mm	System linear range	2.0 mm (80 mils)
Overall case length	40 mm	Recommended gap	1.27 mm (50 mils)
Total lead length	1.0 m	Incremental scale factor	7.87 V/mm (200 mV/mil)

Related Products on Apter Power

MODEL	SYSTEM ROLE	APTER POWER PAGE
Bently Nevada 330103-00-06-10-02-CN	Bently Nevada product	View Bently Nevada 330103-00-06-10-02-CN page
Bently Nevada 330101-30-63-15-02-CN	Bently Nevada product	View Bently Nevada 330101-30-63-15-02-CN page
Bently Nevada 330104-00-15-10-02-00	Bently Nevada product	View Bently Nevada 330104-00-15-10-02-00 page
Bently Nevada 330104-00-12-10-02-00	Bently Nevada product	View Bently Nevada 330104-00-12-10-02-00 page
Bently Nevada 330910-00-05-50-02-00	Bently Nevada product	View Bently Nevada 330910-00-05-50-02-00 page
Bently Nevada 330909-00-60-10-01-05	Bently Nevada product	View Bently Nevada 330909-00-60-10-01-05 page
Bently Nevada 330103-00-06-50-02-00	Bently Nevada product	View Bently Nevada 330103-00-06-50-02-00 page
Bently Nevada 330101-37-57-10-02-05	Bently Nevada product	View Bently Nevada 330101-37-57-10-02-05 page

ENGINEERING BOUNDARY

Confirm 330103-00-04-10-01-05, host identity, hardware execution, interfaces, wiring, shielding, grounding, configuration, accessories and controlled functional-test results before commissioning.

Applications and Precautions

Common Applications

Radial shaft-vibration measurement

Measures shaft motion relative to the bearing housing in the matched proximity loop.

Machine shaft centerline observation

Supplies slow-roll and static-position information to the installed monitor.

Axial position and thrust monitoring

Provides a documented noncontact sensing point for the configured position channel.

Matched transducer-loop replacement

Restores the exact mechanical, lead and approval execution without changing loop identity.

Product Precautions

- 1

Confirm the complete Bently Nevada 330103-00-04-10-01-05 marking and installed position.
- 2

Place the machine and protection channel in the approved maintenance state.
- 3

Isolate the circuit and apply ESD-safe handling controls.
- 4

Record connectors, terminals, cable route, shielding and grounding.
- 5

Verify the documented host, hardware execution and technical values.
- 6

Restore the approved interfaces and channel configuration.
- 7

Review bias, channel and monitor diagnostics after energization.
- 8

Complete a controlled response and alarm test before service release.

IMPORTANT NOTICE

Confirm 330103-00-04-10-01-05, host identity, hardware execution, interfaces, wiring, shielding, grounding, configuration, accessories and controlled functional-test results before commissioning.

ACCEPTANCE CHECK	REQUIRED EVIDENCE
Identity	330103-00-04-10-01-05
Configuration	Review bias, channel and monitor diagnostics after energization.
Functional release	Complete a controlled response and alarm test before service release.

Engineer FAQ

Q1 How is Bently Nevada 330103-00-04-10-01-05 identified?

Match the complete order number 330103-00-04-10-01-05 and documented product designation.

Q3 What records precede removal of Bently Nevada 330103-00-04-10-01-05?

Record position, connections, cable route, configuration and diagnostics.

Q5 Which values govern Bently Nevada 330103-00-04-10-01-05?

Complete order number: 330103-00-04-10-01-05; Probe construction: Without armor; Mounting thread: M10 x 1.

Q7 Which diagnostics follow fitting Bently Nevada 330103-00-04-10-01-05?

Review channel, bias and monitor diagnostics after controlled energization.

Q2 Which host accepts Bently Nevada 330103-00-04-10-01-05?

Use only the documented Bently Nevada 3300 XL 8 mm Proximity Transducer System execution.

Q4 How is Bently Nevada 330103-00-04-10-01-05 isolated?

Secure the machine, isolate the loop and apply ESD controls.

Q6 How is Bently Nevada 330103-00-04-10-01-05 compatibility checked?

Match the host, physical interface, cable or terminal execution and system configuration.

Q8 What releases Bently Nevada 330103-00-04-10-01-05 to service?

A documented controlled response and alarm test with no active fault.

MANUFACTURER SOURCE RECORD

3300 XL 8 mm Proximity Transducer System Datasheet
141194 Rev. AM

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



330103-00-04-10-01-05