

3500/77M 143729-01

3500/77M internal-termination I/O module

Four reciprocating-compressor cylinder pressure signals

PRODUCT SNAPSHOT

BRAND

Bently Nevada

FAMILY

3500/77M reciprocating compressor pressure

PART

3500/77M 143729-01

ORIGIN / HS

USA / 8537101190

APTER POWER SALES TEAM

WHATSAPP / PHONE

+86 180 3023 5313

EMAIL

sales13@apterpower.com

WEBSITE

www.apterpower.com



PRODUCT OVERVIEW

Four reciprocating-compressor cylinder pressure signals

1

Handles four dynamic pressure channels

2

Covers signals from DC to 5.5 kHz

3

Supplies compatible pressure transducers

4

Provides buffered channel outputs for diagnostics

SYSTEM COMPONENTS

3500 rack

compatible cylinder-pressure transducers

matched I/O module and field wiring

3500 Rack Configuration Software

TECHNICAL NOTE

Verify 3500/77M 143729-01, front/rear assembly pairing, transducer supply, channel scale and phase reference, firmware compatibility and rack slot before work; prove all four pressure waveforms and alarms after restart.

TECHNICAL DATA

PARAMETER	VALUE
Complete model	3500/77M 143729-01
Assembly	143729-01
Termination	Internal
Input channels	4
Frequency response	0 to 5.5 kHz
Pressure accuracy at 25 degC	+/-0.5%
Pressure accuracy over temperature	+/-1%
Power consumption	7.8 W full load

PARAMETER	VALUE
Buffered output impedance	550 ohm
Transducer supply	+23 +/-0.8 V DC
Current limit	24.5 mA per channel
Operating temperature	-30 to +65 degC
Storage temperature	-40 to +85 degC
Humidity	95%, noncondensing
Rack occupancy	One full-height front slot and one rear slot

ENGINEERING NOTE

Verify 3500/77M 143729-01, front/rear assembly pairing, transducer supply, channel scale and phase reference, firmware compatibility and rack slot before work; prove all four pressure waveforms and alarms after restart.

RELATED PRODUCTS ON APTER POWER

MODEL	SYSTEM ROLE	APTER POWER PAGE
Bently Nevada 330902 00 90 05 02 00	Related Bently Nevada machinery-monitoring product	View Bently Nevada 330902 00 90 05 02 00 page
Bently Nevada 990 05 50 03 05	Related Bently Nevada machinery-monitoring product	View Bently Nevada 990 05 50 03 05 page
Bently Nevada 21000 28 05 20 035 03 02	Related Bently Nevada machinery-monitoring product	View Bently Nevada 21000 28 05 20 035 03 02 page
Bently Nevada 32000 28 05 00 070 03 02	Related Bently Nevada machinery-monitoring product	View Bently Nevada 32000 28 05 00 070 03 02 page
Bently Nevada 31000 28 05 15 032 03 02	Related Bently Nevada machinery-monitoring product	View Bently Nevada 31000 28 05 15 032 03 02 page
Bently Nevada 31000 16 05 00 065 03 02	Related Bently Nevada machinery-monitoring product	View Bently Nevada 31000 16 05 00 065 03 02 page
Bently Nevada 31000 16 05 00 071 03 02	Related Bently Nevada machinery-monitoring product	View Bently Nevada 31000 16 05 00 071 03 02 page
Bently Nevada 330171 00 47 10 01 05	Related Bently Nevada machinery-monitoring product	View Bently Nevada 330171 00 47 10 01 05 page

APPLICATIONS & PRECAUTIONS

COMMON APPLICATIONS

Recip compressor cylinder-pressure monitoring

Handles four dynamic pressure channels

Compressor performance analysis

Covers signals from DC to 5.5 kHz

Rod-load and valve diagnostic support

Supplies compatible pressure transducers

3500/77M system renewal

Provides buffered channel outputs for diagnostics

PRODUCT PRECAUTIONS

- 1 Verify the complete 3500/77M 143729-01 marking and its assigned 3500/77M reciprocating compressor pressure system position before work.
- 2 Place the connected recip compressor cylinder-pressure monitoring process in the approved maintenance state.
- 3 Isolate applicable power and four reciprocating-compressor cylinder pressure signals field energy before disconnecting conductors.
- 4 Record connector, conductor, address, firmware and software identities before removal.
- 5 Use ESD controls and protect keyed interfaces, exposed contacts and electronic assemblies.
- 6 Confirm the installed 3500 rack and compatible cylinder-pressure transducers against the approved project.
- 7 Restore power in a controlled sequence and review device, network and host diagnostics.
- 8 Prove the intended compressor performance analysis function and retain the final test result.

ENGINEER FAQ

Q1 Does 3500/77M 143729-01 match 3500 rack in a Recip compressor cylinder-pressure monitoring installation?

Verify the complete 3500/77M 143729-01 marking, the documented 3500/77M reciprocating compressor pressure system position and the installed 3500 rack before fitting the assembly.

Q3 Which 3500/77M reciprocating compressor pressure system records should be captured before removing 3500/77M 143729-01?

Record the as-found wiring, installed position, active configuration and diagnostic state associated with 3500/77M 143729-01 before disconnection.

Q5 Which compatible cylinder-pressure transducers condition should be checked when 3500/77M 143729-01 reports an abnormal state?

Check the compatible cylinder-pressure transducers supply, seating and connection first, then compare channel diagnostics with the recorded 3500/77M 143729-01 baseline.

Q7 What maintenance evidence is required after 3500/77M 143729-01 is used for Rod-load and valve diagnostic support?

Retain the nameplate record, corrective action, final diagnostics and a controlled rod-load and valve diagnostic support functional-test result for 3500/77M 143729-01.

Q2 How should 3500/77M 143729-01 be wired when it must handles four dynamic pressure channels?

Isolate the circuit, identify every terminal and reproduce the approved polarity, shield and channel assignment for 3500/77M 143729-01; then continuity-test the affected path.

Q4 What controlled test confirms that 3500/77M 143729-01 can covers signals from dc to 5.5 khz?

Apply the approved field or simulated stimulus, observe the 3500/77M reciprocating compressor pressure system indication and confirm the intended response without bypassing the normal interlocks.

Q6 Can 3500/77M 143729-01 be moved directly into Compressor performance analysis without validating 3500 Rack Configuration Software?

No. Confirm the 3500 Rack Configuration Software, revision, connection scheme and 3500/77M reciprocating compressor pressure system configuration before transferring 3500/77M 143729-01 to that duty.

Q8 How should 3500/77M 143729-01 be returned to service in 3500/77M system renewal?

Restore power under control, verify supplies compatible pressure transducers, exercise the intended signal path and release 3500/77M 143729-01 only after the 3500/77M reciprocating compressor pressure system remains in its approved operating state.

SOURCE Bently Nevada 3500/77M Recip Cylinder Pressure Monitor Datasheet | 147485 Rev. Y

+86 180 3023 5313 | sales13@apterpower.com | www.apterpower.com