

APTER POWER | BENTLY NEVADA

330102-16-40-50-01-05

3300 XL 8 mm 3/8-24 UNF Armored Proximity Probe

Bently Nevada 330102-16-40-50-01-05 is a 3/8-24 UNF armored probe configuration for the 3300 XL 8 mm proximity transducer system.

DOCUMENT PURPOSE

Complete Product Information prepared from Baker Hughes, 3300 XL 8 mm Proximity Transducer System Datasheet, publication 141194 Rev. AM.

CONTACT APTER POWER
WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



330102-16-40-50-01-05

1 | Exact ordering identity

Preserve the complete ordering code. Each suffix defines a controlled mechanical, cable, connector or approval option.

POSITION	VALUE	DOCUMENTED MEANING
Base	330102	3/8-24 UNF probe with armor
AA	16	1.6 in unthreaded length
BB	40	4.0 in overall case length
CC	50	5.0 m total length
DD	01	ClickLoc connector with protector; standard cable
EE	05	CSA, ATEX and IECEx approvals

System pairing
Use only with the matching extension cable, Proximitor Sensor and monitor configuration identified in the official system documentation.

2 | Electrical and performance data

PARAMETER	DOCUMENTED VALUE
Incremental scale factor	7.87 V/mm (200 mV/mil)
Linear range	2.0 mm (80 mils)
Recommended radial gap	1.27 mm (50 mils)
Frequency response	0 to 10 kHz, +0/-3 dB
Power without barriers	-17.5 Vdc to -26 Vdc, 12 mA maximum
Field wiring	Three-conductor shielded triad; up to 305 m

Commissioning boundary
Verify power, polarity, static gap, smooth output response, monitor scaling and final diagnostics under controlled machinery conditions.

3 | Installation and acceptance

CONTROL	ACCEPTANCE CHECK
Identity	Complete model and suffix string recorded.
Mechanical	Thread, mounting depth and probe clearance verified.
Cable	Cable route, bend radius and connector condition acceptable.
System	Extension cable and Proximito Sensor match the configured system length.
Electrical	Supply and field wiring comply with the documented limits.
Functional	Gap, scale, direction, monitor response and diagnostics recorded.

Important Notice
Confirm the physical nameplate, installed host, matched transducer components, target geometry, wiring, grounding, applicable approval drawing and commissioning record before replacement.

4 | Related product navigation

These verified Apter Power links are navigation aids and are separate from the manufacturer evidence record.

RELATED PRODUCT	LINK
Bently Nevada 330101-00-16-10-02-00	View Bently Nevada 330101-00-16-10-02-00 page
Bently Nevada 330101-00-12-10-02-00	View Bently Nevada 330101-00-12-10-02-00 page
Bently Nevada 330101-00-08-10-02-05	View Bently Nevada 330101-00-08-10-02-05 page
Bently Nevada 330101-00-08-10-02-00	View Bently Nevada 330101-00-08-10-02-00 page
Bently Nevada 330101-00-08-05-02-00	View Bently Nevada 330101-00-08-05-02-00 page
Bently Nevada 3500/05-01-02-01-00-01	View Bently Nevada 3500/05-01-02-01-00-01 page
Bently Nevada 330130-070-00-05	View Bently Nevada 330130-070-00-05 page
Bently Nevada 330130-040-03-00	View Bently Nevada 330130-040-03-00 page

MANUFACTURER SOURCE RECORD
Baker Hughes, 3300 XL 8 mm Proximity Transducer System Datasheet, publication 141194 Rev. AM

CONTACT APTER POWER
WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



330102-16-40-50-01-05