

990-05-70-01-05

Vibration Transmitter

Bently Nevada 990-05-70-01-05 is a two-wire, loop-powered vibration transmitter with an integrated Proximitor interface for a 3300 NSv probe system. It provides a proportional 4-20 mA vibration signal plus dynamic vibration and gap-voltage access.

BRAND	Bently Nevada	ORIGIN	USA
MODEL	990-05-70-01-05	PRODUCT	Vibration Transmitter
FAMILY	990 Vibration Transmitter	SOURCE	Baker Hughes / Bently Nevada publication 141612 Rev. Y

MANUFACTURER SOURCE RECORD

990 Vibration Transmitter Datasheet
Baker Hughes / Bently Nevada publication 141612 Rev. Y

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 531
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



990-05-70-01-05

Product Overview

SYSTEM FUNCTION

Bently Nevada 990-05-70-01-05 is a two-wire, loop-powered vibration transmitter with an integrated Proximitor interface for a 3300 NSv probe system. It provides a proportional 4-20 mA vibration signal plus dynamic vibration and gap-voltage access.

FUNCTION 1

Loop-powered 4-20 mA output

FUNCTION 2

Integrated 3300 NSv interface

FUNCTION 3

Dynamic vibration and gap access

FUNCTION 4

DIN-rail industrial installation

TECHNICAL NOTE

Match the 3300 NSv probe and extension cable to the documented 7.0 m system length. Confirm loop supply, resistance, probe gap, scale option, DIN mounting and hazardous-area approval before commissioning.

Technical Data and Acceptance

PARAMETER	VERIFIED VALUE
Complete model	990-05-70-01-05
Output	Two-wire loop-powered 4-20 mA proportional vibration
Probe system	3300 NSv probe and matching extension cable
Full-scale option	05 = 0 to 5 mil peak-to-peak (0 to 125 um)
System length	70 = 7.0 m
Mounting option	01 = 35 mm DIN-rail clips
Approval option	05 = CSA Division 2, ATEX Zone 0/2 and ABS
Supply	17 to 35 VDC
Maximum loop resistance	1000 ohm at 35 VDC
Frequency response	5 to 6000 Hz, +0/-3 dB
Linear range	1.4 mm
Country of origin	USA

ENGINEERING BOUNDARY

Match the 3300 NSv probe and extension cable to the documented 7.0 m system length. Confirm loop supply, resistance, probe gap, scale option, DIN mounting and hazardous-area approval before commissioning.

Acceptance Path

1 IDENTITY

Bently Nevada 990-05-70-01-05 is recorded.

2 LOOP

Supply, resistance, polarity and shielding are correct.

3 PROBE SYSTEM

The matched 7.0 m NSv chain and gap are valid.

4 MEASUREMENT

4-20 mA, gap and dynamic signals pass.

Applications and Engineering FAQ

APPLICATION	ENGINEERING CONTEXT
PLC and DCS vibration input	Supplies a standard 4-20 mA vibration signal to approved control or monitoring systems.
Shaft vibration monitoring	Uses the matched 3300 NSv probe system to measure shaft-relative vibration.
Condition verification	Provides dynamic vibration and gap voltage through the documented PROX OUT and COM points.
Hazardous-area installation	Supports the documented option-05 approval set when the complete installation follows the approved drawing.

Model-Specific FAQ - Part 1

QUESTION	ANSWER
What is Bently Nevada 990-05-70-01-05?	It is a two-wire loop-powered vibration transmitter with an integrated interface for a matched 3300 NSv proximity probe system.
What output does it provide?	It provides a proportional 4-20 mA vibration output and access to dynamic vibration and gap voltage.
What does option 05 specify for full scale?	The first 05 option identifies a 0 to 5 mil peak-to-peak, or 0 to 125 um, vibration range.
What system length is required?	Option 70 identifies a 7.0 m probe and extension-cable system.

FAQ, Related Products and Source

QUESTION	ANSWER
How is the transmitter mounted?	Option 01 identifies the 35 mm DIN-rail clip mounting configuration.
What approvals are included?	The final 05 option identifies the documented CSA Division 2, ATEX Zone 0/2 and ABS approval selection.
What loop supply is documented?	The transmitter operates from 17 to 35 VDC, with loop resistance limited by the supply and up to 1000 ohm at 35 VDC.
What confirms successful commissioning?	The probe gap is valid, the 4-20 mA output matches the applied vibration and the dynamic and gap signals are credible.

MANUFACTURER SOURCE RECORD

990 Vibration Transmitter Datasheet
Baker Hughes / Bently Nevada publication 141612 Rev. Y

Related Products on Apter Power

MODEL	APTER POWER PAGE
Bently Nevada 139554-01	View Bently Nevada 139554-01
Bently Nevada 140471-02	View Bently Nevada 140471-02
Bently Nevada 140482-01	View Bently Nevada 140482-01
Bently Nevada 143493-00-080-040-50-00	View Bently Nevada 143493-00-080-040-50-00
Bently Nevada 144181-51	View Bently Nevada 144181-51
Bently Nevada 144181-51-05	View Bently Nevada 144181-51-05
Bently Nevada 146054-034-20-02-05	View Bently Nevada 146054-034-20-02-05
Bently Nevada 146054-12-05-01-05	View Bently Nevada 146054-12-05-01-05

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



990-05-70-01-05