

3300/25-XX-15-15-00-00-03-02

3300/25 Dual Accelerometer Monitor

Bently Nevada 3300/25-XX-15-15-00-00-03-02 is a dual accelerometer monitor for absolute machine-housing or structural vibration. Its documented options set both channels to 0-25 mm/s peak, no ordered approval or safety barrier, quad relays and 3X Trip Multiply; the XX input/channel-unit field must be confirmed from the installed unit.

CONTROLLED ENGINEERING COPY

IDENTITY	VERIFIED VALUE
Manufacturer	Bently Nevada
System family	Bently Nevada 3300 Monitoring System
Part number	3300/25-XX-15-15-00-00-03-02
Document status	Controlled product and system reference

DOCUMENT SCOPE

Exact article identity, official technical data, host matching, installation checks, applications, precautions and controlled acceptance evidence.

MODEL-SPECIFIC ENGINEERING NOTE

Install 3300/25-XX-15-15-00-00-03-02 only in the documented Bently Nevada 3300 Monitoring System position. Preserve the exact mating interfaces and option settings, then verify diagnostics and two-channel absolute housing-vibration monitoring with 0-25 mm/s ranges, quad relays and 3X Trip Multiply under controlled conditions.

System Role and Architecture

Bently Nevada 3300/25-XX-15-15-00-00-03-02 is a dual accelerometer monitor for absolute machine-housing or structural vibration. Its documented options set both channels to 0-25 mm/s peak, no ordered approval or safety barrier, quad relays and 3X Trip Multiply; the XX input/channel-unit field must be confirmed from the installed unit.

FUNCTION 1
3300/25 Dual Accelerometer Monitor

FUNCTION 2
Absolute housing or structural vibration relative to free space

FUNCTION 3
2 independent online vibration channels

FUNCTION 4
Two-channel absolute housing-vibration monitoring with 0-25 mm/s ranges, quad relays and 3x trip multiply

RELATED APTER POWER PAGES

1 Bently Nevada 330104-00-12-10-02-00

2 Bently Nevada 330104-03-06-10-02-00

3 Bently Nevada 330104-06-12-10-02-00

4 Bently Nevada 330105-02-12-10-02-05

5 Bently Nevada 330106-05-30-10-02-05

6 Bently Nevada 330130-080-00-00

7 Bently Nevada 330180-50-00

8 Bently Nevada 3500-25-149369-01-135473-01

9 Bently Nevada 3500-40M-176449-01

MATCHED SYSTEM COMPONENTS

NO.	DOCUMENTED COMPONENT / ROLE
01	Bently Nevada 3300 Monitoring System
02	Matched Bently Nevada host monitor, rack or rear module
03	Documented connectors, field wiring, alarm contacts and shielding
04	Approved option settings, configuration and acceptance record

SYSTEM INTEGRATION RECORD

INTEGRATION ITEM	DOCUMENTED ROLE
Host identity	Bently Nevada 3300 Monitoring System
Interface role	two-channel absolute housing-vibration monitoring with 0-25 mm/s ranges, quad relays and 3X Trip
Field / power context	documented Bently Nevada machinery-monitoring rack position
Commissioning evidence	Identity, option settings, diagnostics and controlled functional response recorded

INSTALLATION AND CONNECTION CHECKS

1 Confirm the complete 3300/25-XX-15-15-00-00-03-02 marking and the documented 3300/25 Dual Accelerometer Monitor execution.

2 Place the machinery-protection system and connected process in the approved maintenance state.

3 Isolate rack power and field circuits, prove the safe state and apply ESD controls.

4 Record the rack position, mating hardware, connectors, alarm wiring and as-found configuration.

Technical Specifications

Technical values below are limited to the named product record and directly applicable manufacturer documentation.

PARAMETER	VALUE	PARAMETER	VALUE
Monitor type	3300/25 dual accelerometer monitor	Safety barrier option	00: None
Measurement	Absolute housing or structural vibration relative to free space	Alarm relay option	03: Quad relays, epoxy-sealed
Channels	2 independent online vibration channels	Trip Multiply option	02: 3X
Transducer/channel-units option	XX: Must be confirmed from installed marking	Filter combinations	More than 10,000 high-pass/low-pass
Channel A range option	15: 0-25 mm/s peak	High-pass range	3.7-3008 Hz selectable
Channel B range option	15: 0-25 mm/s peak	Low-pass range	24-22372 Hz selectable
Agency approval option	00: Not required	Power consumption	10.5 W nominal

RELATED PRODUCT PAGES

1 Bently Nevada 330104-00-12-10-02-00

2 Bently Nevada 330104-03-06-10-02-00

3 Bently Nevada 330104-06-12-10-02-00

4 Bently Nevada 330105-02-12-10-02-05

5 Bently Nevada 330106-05-30-10-02-05

6 Bently Nevada 330130-080-00-00

7 Bently Nevada 330180-50-00

8 Bently Nevada 3500-25-149369-01-135473-01

9 Bently Nevada 3500-40M-176449-01

ENGINEERING BOUNDARY

Confirm 3300/25-XX-15-15-00-00-03-02, its exact Bently Nevada 3300 Monitoring System host, installed position, mating hardware, wiring, alarm logic, configuration, diagnostics and controlled acceptance evidence before release.

PRE-INSTALLATION CHECKS

- 1

Confirm the complete 3300/25-XX-15-15-00-00-03-02 marking and the documented 3300/25 Dual Accelerometer Monitor execution.
- 2

Place the machinery-protection system and connected process in the approved maintenance state.
- 3

Isolate rack power and field circuits, prove the safe state and apply ESD controls.
- 4

Record the rack position, mating hardware, connectors, alarm wiring and as-found configuration.

Applications and Engineering Context

Matched 3300/3500 rack service

Restores two-channel absolute housing-vibration monitoring with 0-25 mm/s ranges, quad relays and 3X Trip Multiply in the documented machinery-monitoring architecture.

Exact-execution replacement

Uses the complete 3300/25-XX-15-15-00-00-03-02 identity instead of a neighboring option or revision.

Machinery-protection refurbishment

Preserves the installed host position, connectors, alarm logic and approved configuration.

Controlled recommissioning

Confirms hardware identity, diagnostics and the affected protection function before return to operation.

TECHNICAL NOTE

Install 3300/25-XX-15-15-00-00-03-02 only in the documented Bently Nevada 3300 Monitoring System position. Preserve the exact mating interfaces and option settings, then verify diagnostics and two-channel absolute housing-vibration monitoring with 0-25 mm/s ranges, quad relays and 3X Trip Multiply under controlled conditions.

MODEL-SPECIFIC ACCEPTANCE EVIDENCE

CHECK	ACCEPTANCE CONDITION
Identity	3300/25-XX-15-15-00-00-03-02 recorded
Host / carrier	Bently Nevada 3300 Monitoring System
Physical interface	Installed mating hardware and field interfaces match the as-found record
Configuration	Approved monitor and alarm configuration restored
Functional proof	Controlled test confirms two-channel absolute housing-vibration monitoring with 0-25 mm/s ranges, quad relays and 3X Trip Multiply

IMPORTANT NOTICE

Confirm 3300/25-XX-15-15-00-00-03-02, its exact Bently Nevada 3300 Monitoring System host, installed position, mating hardware, wiring, alarm logic, configuration, diagnostics and controlled acceptance evidence before release.

Related Products and Source Record

Brand-qualified Apter Power navigation links are provided for system planning only; manufacturer evidence remains the named source record.

RELATED PRODUCTS ON APTER POWER

1

Bently Nevada 330104-00-12-10-02-00

View Bently Nevada 330104-00-12-10-02-00 page

2

Bently Nevada 330104-03-06-10-02-00

View Bently Nevada 330104-03-06-10-02-00 page

3

Bently Nevada 330104-06-12-10-02-00

View Bently Nevada 330104-06-12-10-02-00 page

4

Bently Nevada 330105-02-12-10-02-05

View Bently Nevada 330105-02-12-10-02-05 page

5

Bently Nevada 330106-05-30-10-02-05

View Bently Nevada 330106-05-30-10-02-05 page

6

Bently Nevada 330130-080-00-00

View Bently Nevada 330130-080-00-00 page

7

Bently Nevada 330180-50-00

View Bently Nevada 330180-50-00 page

8

Bently Nevada 3500-25-149369-01-135473-01

View Bently Nevada 3500-25-149369-01-135473-01 page

9

Bently Nevada 3500-40M-176449-01

View Bently Nevada 3500-40M-176449-01 page

MANUFACTURER SOURCE RECORD

3300/25 Dual Accelerometer Monitor, Specifications and Ordering Information 141501-01 Rev. K | Bently Nevada manufacturer document supplied by the user and verified 28 September 2026

APTER POWER SALES TEAM

WHATSAPP / PHONE

+86 180 3023 5313

EMAIL

sales13@apterpower.com

WEBSITE

www.apterpower.com



RECOMMENDATION SCOPE

These links support product navigation and comparison. Technical values in this document are sourced only from the manufacturer record above.