

6GT2002-0ED00

RFID Interface Module

COMPLETE PRODUCT INFORMATION

It connects two MOBY read/write devices to a PROFIBUS DP-V1 master through the ASM456 communication interface.

- Connects two read/write devices
- Provides the MOBY ASM456 interface role
- Communicates through PROFIBUS DP-V1
- Uses a separately selected PROFIBUS connection block

VERIFIED IDENTITY

Article number	6GT2002-0ED00	Module designation	ASM456 communications module
System family	MOBY	Host interface	PROFIBUS DP-V1
Reader connections	Two read/write devices	PROFIBUS connection block	Not included

Official source: Siemens Industry Mall exact article record
Publication: 6GT2002-0ED00

APTER POWER | COMPLETE PRODUCT INFORMATION

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com | WEBSITE www.apterpower.com

6GT2002-0ED00 | PAGE 1



TECHNICAL DATA

Article number	6GT2002-0ED00	Module designation	ASM456 communications module
System family	MOBY	Host interface	PROFIBUS DP-V1
Reader connections	Two read/write devices	PROFIBUS connection block	Not included
Lifecycle	Product cancellation	Cancellation effective date	1 October 2022
Successor	6GT2002-0EE20	Successor designation	RF166C communications module
Export classification	ECCN N; AL N	Siemens catalog identifier	ID10-E
Product group	X0AI		

APPLICATIONS & SYSTEM COMPONENTS

Dual-reader RFID integration	Connects two reader channels to the controller network.
Workpiece identification	Identifies tagged workpieces at production stations.
PROFIBUS tracking station	Transfers identification data over PROFIBUS DP-V1.
ASM456 replacement	Restores the original MOBY communication position.

- PROFIBUS DP-V1 master and network
- two documented MOBY read/write devices
- separate PROFIBUS connection block
- approved identification-system project and addressing

APTER POWER | COMPLETE PRODUCT INFORMATION

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com | WEBSITE www.apterpower.com

6GT2002-0ED00 | PAGE 2



PRECAUTIONS & ENGINEER FAQ

PRODUCT PRECAUTIONS

- Verify the complete 6GT2002-0ED00 marking and the assigned Siemens MOBY identification system position before work.
- Isolate all applicable power and profibus dp-v1 identification data from two read/write devices field energy before disconnection.
- Use ESD controls and protect keyed interfaces, exposed contacts and electronic assemblies.
- Restore power in a controlled sequence and review module, rack and host diagnostics.
- Place the connected dual-reader rfid integration process in the approved maintenance state.
- Record every connector, conductor, address, jumper and project identity before removal.
- Confirm the installed PROFIBUS DP-V1 master and network and two documented MOBY read/write devices against the approved system record.
- Prove the intended workpiece identification function and retain the final acceptance result.

ENGINEER FAQ — PART 1

1	What interface role does Siemens 6GT2002-0ED00 provide?	It is the MOBY ASM456 communication module for a PROFIBUS DP-V1 identification station.
2	How many read/write devices can connect to 6GT2002-0ED00?	The exact article supports two documented MOBY read/write devices.
3	Is the PROFIBUS connection block included with 6GT2002-0ED00?	No. Siemens states that the article is supplied without the PROFIBUS connection block, so the installed block must be identified separately.

APTER POWER | COMPLETE PRODUCT INFORMATION

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com | WEBSITE www.apterpower.com

6GT2002-0ED00 | PAGE 3



4	Which project settings must be retained for 6GT2002-0ED00?	Record the PROFIBUS address, master configuration, module parameters and both reader-channel assignments.
---	---	---

APTER POWER | COMPLETE PRODUCT INFORMATION

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com | WEBSITE www.apterpower.com

6GT2002-0ED00 | PAGE 4



ENGINEER FAQ & RELATED PRODUCTS

1	What lifecycle date applies to 6GT2002-0ED00?	Siemens records product cancellation effective 1 October 2022 and treats the article as a spare part.
2	Which successor is listed for 6GT2002-0ED00?	The exact Industry Mall record names 6GT2002-0EE20, RF166C, as successor; compatibility still requires engineering review.
3	Why is 6GT2002-0EE20 not an automatic substitute for 6GT2002-0ED00?	The successor has different communication capabilities and installation details, so network, reader and project compatibility must be verified.
4	How is 6GT2002-0ED00 commissioned after replacement?	Restore the PROFIBUS configuration, confirm both readers are detected, and run controlled tag-read and tag-write tests on each channel.

RELATED PRODUCTS ON APTER POWER

01	Emerson VCCM8551G410MO	Related industrial automation product
02	Emerson VCCM8551G309MO	Related industrial automation product
03	Siemens 6SL3300 1AH32 5BA0	Related industrial automation product
04	Siemens 6SE7041 8GK85 0LA0	Related industrial automation product
05	Siemens 6SE7041 8EK85 1MA0	Related industrial automation product
06	Siemens 6SE7037 0EJ84 1JC2	Related industrial automation product
07	Siemens 6SE7036 1EE85 1HA0	Related industrial automation product
08	Siemens C98043 A1682 L1	Related industrial automation product

APTER POWER | COMPLETE PRODUCT INFORMATION

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com | WEBSITE www.apterpower.com

6GT2002-0ED00 | PAGE 5

