

330905-00-05-10-12-CN

NSv Proximity Probe

Bently Nevada 330905-00-05-10-12-CN is an unarmored M10 x 1 3300 XL NSv proximity probe with 50 mm case identity, 1.0 m probe lead and miniature clickloc coaxial connector with fluidloc cable.

PRODUCT SNAPSHOT

BRAND

Bently Nevada

FAMILY

3300 XL NSv Proximity Transducer System

PART

330905-00-05-10-12-CN

PRODUCT TYPE

NSv Proximity Probe

APTER POWER SALES TEAM

WHATSAPP / PHONE

+86 180 3023 5313

EMAIL

sales13@apterpower.com

WEBSITE

www.apterpower.com



PRODUCT OVERVIEW

Bently Nevada 330905-00-05-10-12-CN is an unarmored M10 x 1 3300 XL NSv proximity probe with 50 mm case identity, 1.0 m probe lead and miniature clickloc coaxial connector with fluidloc cable.

1

Uses the compact 3300 XL NSv transducer architecture

2

Provides the documented M10 x 1 mounting identity

3

Retains the 1.0 m probe-lead option

4

Uses the miniature clickloc coaxial connector with fluidloc cable connection option

SYSTEM COMPONENTS

matched 3300 XL NSv extension cable

compatible 3300 XL NSv Proximitior Sensor

approved target surface

configured monitor channel

TECHNICAL NOTE

The official NSv order table does not decode the supplied CN suffix as a standard approval code; retain CN exactly and verify it against the nameplate and controlled drawing.



TECHNICAL DATA

PARAMETER	VALUE
probe family	3300 XL NSv
mounting thread	M10 x 1
cable protection	Unarmored
unthreaded length code	0 mm
overall case-length code	50 mm
total probe-lead length	1.0 m

PARAMETER	VALUE
connector and cable option	miniature ClickLoc coaxial connector with FluidLoc cable
agency-approval option	CN suffix retained as supplied; verify from nameplate
linear measurement range	1.5 mm (60 mils)
incremental scale factor	7.87 V/mm (200 mV/mil)
frequency response	0 to 10 kHz, +0/-3 dB typical
recommended gap	1.0 mm (40 mils)

ENGINEERING NOTE

The official NSv order table does not decode the supplied CN suffix as a standard approval code; retain CN exactly and verify it against the nameplate and controlled drawing.

RELATED BENTLY NEVADA PRODUCTS ON APTER POWER

BRAND + MODEL	RELATED PRODUCT	APTER POWER LINK
Bently Nevada 330130 080 13 05	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 330130 046 00 06	Bently Nevada monitoring product	Open Bently Nevada page
Siemens 6SL3985 6TM00 0AA0	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 330525 00	Bently Nevada monitoring product	Open Bently Nevada page
GE DS200SBCBG1ADC	Bently Nevada monitoring product	Open Bently Nevada page
GE DS200PCTMG1AAA	Bently Nevada monitoring product	Open Bently Nevada page



APPLICATIONS & PRECAUTIONS

COMMON APPLICATIONS

Small-target shaft vibration

Uses the compact 3300 XL NSv transducer architecture

Axial position monitoring

Provides the documented M10 x 1 mounting identity

Tight-clearance installation

Retains the 1.0 m probe-lead option

Exact NSv probe replacement

Uses the miniature clickloc coaxial connector with fluidloc cable connection option

MORE RELATED BENTLY NEVADA PRODUCTS

GE DS200PCCAG9ACB

Bently Nevada product - open page

GE DS200FCRRG1AKD

Bently Nevada product - open page

GE DS200ADGIH1AAA

Bently Nevada product - open page

GE A06B 0104 B111 7000

Bently Nevada product - open page

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

330905-00-05-10-12-CN



PRODUCT PRECAUTIONS

- 1 Verify the complete 330905-00-05-10-12-CN marking and its assigned 3300 XL NSv Proximity Transducer System position before work.
- 2 Place the connected small-target shaft vibration process in the approved maintenance state.
- 3 Isolate the documented power, signal and stored-energy sources before disconnecting the transducer or module.
- 4 Record every connector, cable route, shield, polarity, channel assignment and host configuration before removal.
- 5 Use ESD-safe handling and protect coaxial, terminal and keyed interfaces from contamination or mechanical damage.
- 6 Confirm the installed matched 3300 XL NSv extension cable and compatible 3300 XL NSv Proximitor Sensor against the approved project record.
- 7 Restore power in a controlled sequence and review transducer, monitor and host diagnostics.
- 8 Prove the intended axial position monitoring function and retain the final controlled acceptance result.

ENGINEER FAQ

Q1 Which probe family identifies Bently Nevada 330905-00-05-10-12-CN?

3300 XL NSv Proximity Transducer System Datasheet documents the probe family as 3300 XL NSv. Confirm the complete 330905-00-05-10-12-CN marking and the installed-system record before service.

Q3 How must the cable protection of Bently Nevada 330905-00-05-10-12-CN be matched?

3300 XL NSv Proximity Transducer System Datasheet documents the cable protection as Unarmored. Confirm the complete 330905-00-05-10-12-CN marking and the installed-system record before service.

Q5 What does the official record state for the overall case-length code of Bently Nevada 330905-00-05-10-12-CN?

3300 XL NSv Proximity Transducer System Datasheet documents the overall case-length code as 50 mm. Confirm the complete 330905-00-05-10-12-CN marking and the installed-system record before service.

Q7 Which exact connector and cable option distinguishes Bently Nevada 330905-00-05-10-12-CN?

3300 XL NSv Proximity Transducer System Datasheet documents the connector and cable option as miniature ClickLoc coaxial connector with FluidLoc cable. Confirm the complete 330905-00-05-10-12-CN marking and the installed-system record before service.

Q2 What mounting thread is published for Bently Nevada 330905-00-05-10-12-CN?

3300 XL NSv Proximity Transducer System Datasheet documents the mounting thread as M10 x 1. Confirm the complete 330905-00-05-10-12-CN marking and the installed-system record before service.

Q4 Which unthreaded length code must technicians retain for Bently Nevada 330905-00-05-10-12-CN?

3300 XL NSv Proximity Transducer System Datasheet documents the unthreaded length code as 0 mm. Confirm the complete 330905-00-05-10-12-CN marking and the installed-system record before service.

Q6 How should the total probe-lead length be verified on Bently Nevada 330905-00-05-10-12-CN?

3300 XL NSv Proximity Transducer System Datasheet documents the total probe-lead length as 1.0 m. Confirm the complete 330905-00-05-10-12-CN marking and the installed-system record before service.

Q8 What agency-approval option is used when commissioning Bently Nevada 330905-00-05-10-12-CN?

3300 XL NSv Proximity Transducer System Datasheet documents the agency-approval option as CN suffix retained as supplied; verify from nameplate. Confirm the complete 330905-00-05-10-12-CN marking and the installed-system record before service.

SOURCE 3300 XL NSv Proximity Transducer System Datasheet | 147385 Rev. R

APTER POWER SALES TEAM

+86 180 3023 5313

sales13@apterpower.com

www.apterpower.com

330905-00-05-10-12-CN

