

APTER POWER

COMPLETE PRODUCT INFORMATION

330103-00-16-10-12-05

Proximity Probe

Bently Nevada 330103-00-16-10-12-05 is an unarmored M10 x 1 3300 XL 8 mm proximity probe with 160 mm case identity, 1.0 m probe lead and miniature clickloc coaxial connector with fluidloc cable.

PRODUCT SNAPSHOT

BRAND

Bently Nevada

FAMILY

3300 XL 8 mm Proximity Transducer System

PART

330103-00-16-10-12-05

PRODUCT TYPE

Proximity Probe

APTER POWER SALES TEAM

WHATSAPP / PHONE

+86 180 3023 5313

EMAIL

sales13@apterpower.com

WEBSITE

www.apterpower.com



PRODUCT OVERVIEW

Bently Nevada 330103-00-16-10-12-05 is an unarmored M10 x 1 3300 XL 8 mm proximity probe with 160 mm case identity, 1.0 m probe lead and miniature clickloc coaxial connector with fluidloc cable.

1

Uses the 3300 XL 8 mm transducer architecture

2

Provides the documented M10 x 1 mounting identity

3

Retains the 1.0 m probe-lead option

4

Uses the miniature clickloc coaxial connector with fluidloc cable connection option

SYSTEM COMPONENTS

matched 3300 XL 8 mm extension cable

compatible 3300 XL Proximitior Sensor

approved target surface

configured monitor channel

TECHNICAL NOTE

Preserve the M10 x 1 mounting, 160 mm case identity, 1.0 m lead, connector option, target material, system length and approved response when replacing 330103-00-16-10-12-05.



TECHNICAL DATA

PARAMETER	VALUE
probe family	3300 XL 8 mm
mounting thread	M10 x 1
cable protection	Unarmored
unthreaded length code	0 mm
overall case-length code	160 mm
total probe-lead length	1.0 m

PARAMETER	VALUE
connector and cable option	miniature ClickLoc coaxial connector with FluidLoc cable
agency-approval option	CSA, ATEX and IECEx
linear measurement range	2.0 mm (80 mils)
incremental scale factor	7.87 V/mm (200 mV/mil)
frequency response	0 to 10 kHz, +0/-3 dB
recommended gap	approximately 1.27 mm (50 mils) at -9 V DC

ENGINEERING NOTE

Preserve the M10 x 1 mounting, 160 mm case identity, 1.0 m lead, connector option, target material, system length and approved response when replacing 330103-00-16-10-12-05.

RELATED BENTLY NEVADA PRODUCTS ON APTER POWER

BRAND + MODEL	RELATED PRODUCT	APTER POWER LINK
Bently Nevada 330881 28 05 050 03 02	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 21504 00 48 10 02	Bently Nevada monitoring product	Open Bently Nevada page
ABB 3HAC043569 004	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 129525 0050 02	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 102044 00 32 10 02	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 21000 11 05 00 085 03 02	Bently Nevada monitoring product	Open Bently Nevada page



APPLICATIONS & PRECAUTIONS

COMMON APPLICATIONS

Radial shaft vibration

Uses the 3300 XL 8 mm transducer architecture

Axial position monitoring

Provides the documented M10 x 1 mounting identity

Phase reference measurement

Retains the 1.0 m probe-lead option

Exact probe replacement

Uses the miniature clickloc coaxial connector with fluidloc cable connection option

MORE RELATED BENTLY NEVADA PRODUCTS

Bently Nevada 21000 15 10 00 166 03 02

Bently Nevada product - open page

Bently Nevada 21000 28 05 00 070 01 02

Bently Nevada product - open page

Bently Nevada 84661 55

Bently Nevada product - open page

Bently Nevada 330880 00 00 000 03 02

Bently Nevada product - open page

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

330103-00-16-10-12-05



PRODUCT PRECAUTIONS

- 1 Verify the complete 330103-00-16-10-12-05 marking and its assigned 3300 XL 8 mm Proximity Transducer System position before work.
- 2 Place the connected radial shaft vibration process in the approved maintenance state.
- 3 Isolate the documented power, signal and stored-energy sources before disconnecting the transducer or module.
- 4 Record every connector, cable route, shield, polarity, channel assignment and host configuration before removal.
- 5 Use ESD-safe handling and protect coaxial, terminal and keyed interfaces from contamination or mechanical damage.
- 6 Confirm the installed matched 3300 XL 8 mm extension cable and compatible 3300 XL Proximitor Sensor against the approved project record.
- 7 Restore power in a controlled sequence and review transducer, monitor and host diagnostics.
- 8 Prove the intended axial position monitoring function and retain the final controlled acceptance result.

ENGINEER FAQ

Q1 Which probe family identifies Bently Nevada 330103-00-16-10-12-05?

3300 XL 8 mm Proximity Transducer System Datasheet documents the probe family as 3300 XL 8 mm. Confirm the complete 330103-00-16-10-12-05 marking and the installed-system record before service.

Q3 How must the cable protection of Bently Nevada 330103-00-16-10-12-05 be matched?

3300 XL 8 mm Proximity Transducer System Datasheet documents the cable protection as Unarmored. Confirm the complete 330103-00-16-10-12-05 marking and the installed-system record before service.

Q5 What does the official record state for the overall case-length code of Bently Nevada 330103-00-16-10-12-05?

3300 XL 8 mm Proximity Transducer System Datasheet documents the overall case-length code as 160 mm. Confirm the complete 330103-00-16-10-12-05 marking and the installed-system record before service.

Q7 Which exact connector and cable option distinguishes Bently Nevada 330103-00-16-10-12-05?

3300 XL 8 mm Proximity Transducer System Datasheet documents the connector and cable option as miniature ClickLoc coaxial connector with FluidLoc cable. Confirm the complete 330103-00-16-10-12-05 marking and the installed-system record before service.

Q2 What mounting thread is published for Bently Nevada 330103-00-16-10-12-05?

3300 XL 8 mm Proximity Transducer System Datasheet documents the mounting thread as M10 x 1. Confirm the complete 330103-00-16-10-12-05 marking and the installed-system record before service.

Q4 Which unthreaded length code must technicians retain for Bently Nevada 330103-00-16-10-12-05?

3300 XL 8 mm Proximity Transducer System Datasheet documents the unthreaded length code as 0 mm. Confirm the complete 330103-00-16-10-12-05 marking and the installed-system record before service.

Q6 How should the total probe-lead length be verified on Bently Nevada 330103-00-16-10-12-05?

3300 XL 8 mm Proximity Transducer System Datasheet documents the total probe-lead length as 1.0 m. Confirm the complete 330103-00-16-10-12-05 marking and the installed-system record before service.

Q8 What agency-approval option is used when commissioning Bently Nevada 330103-00-16-10-12-05?

3300 XL 8 mm Proximity Transducer System Datasheet documents the agency-approval option as CSA, ATEX and IECEx. Confirm the complete 330103-00-16-10-12-05 marking and the installed-system record before service.

SOURCE 3300 XL 8 mm Proximity Transducer System Datasheet | 141194 Rev. AM

APTER POWER SALES TEAM

+86 180 3023 5313

sales13@apterpower.com

www.apterpower.com

330103-00-16-10-12-05

