

INDUSTRIAL AUTOMATION PRODUCT

330101-XX-XX-20-02-05 MOD:147773-00-12

Proximity Probe

Bently Nevada 330101-XX-XX-20-02-05 MOD:147773-00-12 is an unarmored 3/8-24 UNF 3300 XL 8 mm proximity probe with Custom XX option case identity, 2.0 m probe lead and miniature clickloc coaxial connector with standard cable.

IDENTITY	VERIFIED VALUE
Manufacturer	Bently Nevada
System family	3300 XL 8 mm Proximity Transducer System
Part number	330101-XX-XX-20-02-05 MOD:147773-00-12

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



2

Technical Specifications

Technical values below are limited to the named Bently Nevada product record.

PARAMETER	TECHNICAL VALUE
probe family	3300 XL 8 mm
mounting thread	3/8-24 UNF
cable protection	Unarmored
unthreaded length code	Custom XX option
overall case-length code	Custom XX option
total probe-lead length	2.0 m
connector and cable option	miniature ClickLoc coaxial connector with standard cable
agency-approval option	CSA, ATEX and IECEx
linear measurement range	2.0 mm (80 mils)
incremental scale factor	7.87 V/mm (200 mV/mil)
frequency response	0 to 10 kHz, +0/-3 dB
recommended gap	approximately 1.27 mm (50 mils) at -9 V DC

ENGINEERING DATA SUMMARY

DATA GROUP	VERIFIED ASSIGNMENT
Installed host / carrier	matched 3300 XL 8 mm extension cable
Companion hardware	compatible 3300 XL Proximitors Sensor
Field connection	approved target surface
Primary system function	Uses the 3300 XL 8 mm transducer architecture
Controlled acceptance duty	Radial shaft vibration



3

System Role and Architecture

Bently Nevada 330101-XX-XX-20-02-05 MOD:147773-00-12 is an unarmored 3/8-24 UNF 3300 XL 8 mm proximity probe with Custom XX option case identity, 2.0 m probe lead and miniature clickloc coaxial connector with standard cable.

FUNCTION 1

Uses the 3300 XL 8 mm transducer architecture

FUNCTION 2

Provides the documented 3/8-24 UNF mounting identity

FUNCTION 3

Retains the 2.0 m probe-lead option

FUNCTION 4

Uses the miniature clickloc coaxial connector with standard cable connection option

Matched system components

- matched 3300 XL 8 mm extension cable
- compatible 3300 XL Proximito Sensor
- approved target surface
- configured monitor channel

SYSTEM INTEGRATION RECORD

INTEGRATION ITEM	DOCUMENTED ROLE
Installed host / carrier	matched 3300 XL 8 mm extension cable
Companion hardware	compatible 3300 XL Proximito Sensor
Field connection	approved target surface
Primary system function	Uses the 3300 XL 8 mm transducer architecture
Controlled acceptance duty	Radial shaft vibration



4

Applications and Engineering Context

Radial shaft vibration

Uses the 3300 XL 8 mm transducer architecture

Axial position monitoring

Provides the documented 3/8-24 UNF mounting identity

Phase reference measurement

Retains the 2.0 m probe-lead option

Exact probe replacement

Uses the miniature clickloc coaxial connector with standard cable connection option

TECHNICAL NOTE

The XX length fields and MOD:147773-00-12 are custom identities not decoded by the standard table; preserve both exactly and verify the controlled drawing before installation.

MODEL-SPECIFIC ACCEPTANCE EVIDENCE

CHECK	ACCEPTANCE CONDITION
Identity	330101-XX-XX-20-02-05 MOD:147773-00-12 / 330101-XX-XX-20-02-05 MOD:147773-00-12 recorded
Physical interface	matched 3300 XL 8 mm extension cable
Companion check	compatible 3300 XL Proximator Sensor
Functional proof	Uses the 3300 XL 8 mm transducer architecture
Application test	Radial shaft vibration



5

Engineering Precautions

- 1 Verify the complete 330101-XX-XX-20-02-05 MOD:147773-00-12 marking and its assigned 3300 XL 8 mm Proximity Transducer System position before work.
- 2 Place the connected radial shaft vibration process in the approved maintenance state.
- 3 Isolate the documented power, signal and stored-energy sources before disconnecting the transducer or module.
- 4 Record every connector, cable route, shield, polarity, channel assignment and host configuration before removal.
- 5 Use ESD-safe handling and protect coaxial, terminal and keyed interfaces from contamination or mechanical damage.

RELATED BENTLY NEVADA PRODUCTS ON APTER POWER

BRAND + MODEL	RELATED PRODUCT	APTER POWER LINK
Bently Nevada 330103 00 06 10 02 CN	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 330101 30 63 15 02 CN	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 26363 30	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 3300 12 02 20 00	Bently Nevada monitoring product	Open Bently Nevada page
Siemens A5E36717803	Bently Nevada monitoring product	Open Bently Nevada page
Siemens A5E36717808	Bently Nevada monitoring product	Open Bently Nevada page
Siemens A5E00297630	Bently Nevada monitoring product	Open Bently Nevada page
Siemens A5E36717793	Bently Nevada monitoring product	Open Bently Nevada page
Siemens A5E36717811	Bently Nevada monitoring product	Open Bently Nevada page
Siemens 6ED1052 1HB08 0BA1	Bently Nevada monitoring product	Open Bently Nevada page

MANUFACTURER SOURCE RECORD

3300 XL 8 mm Proximity Transducer System Datasheet

141194 Rev. AM

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

