

APTER POWER FIELD WORKBOOK

INSTALLATION | APPLICATION | VERIFICATION

330103-00-16-10-12-05

Proximity Probe

CONTROLLED ENGINEERING COPY

Preserve the M10 x 1 mounting, 160 mm case identity, 1.0 m lead, connector option, target material, system length and approved response when replacing 330103-00-16-10-12-05.

INSTALLATION IDENTITY	REQUIRED VALUE
Complete model	330103-00-16-10-12-05
Manufacturer part	330103-00-16-10-12-05
Hardware type	3300 XL 8 mm
System family	3300 XL 8 mm Proximity Transducer System



APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



01 PRE-INSTALLATION PLAN

- 1

Verify the complete 330103-00-16-10-12-05 marking and its assigned 3300 XL 8 mm Proximity Transducer System position before work.
- 2

Place the connected radial shaft vibration process in the approved maintenance state.
- 3

Isolate the documented power, signal and stored-energy sources before disconnecting the transducer or module.
- 4

Record every connector, cable route, shield, polarity, channel assignment and host configuration before removal.
- 5

Use ESD-safe handling and protect coaxial, terminal and keyed interfaces from contamination or mechanical damage.

MATCHED HARDWARE

- matched 3300 XL 8 mm extension cable
- compatible 3300 XL Proximitior Sensor
- approved target surface
- configured monitor channel

INSTALLATION CONTROL RECORD

CONTROL ITEM	REQUIRED RECORD
Identity	330103-00-16-10-12-05 / 330103-00-16-10-12-05 recorded
Physical interface	matched 3300 XL 8 mm extension cable
Companion check	compatible 3300 XL Proximitior Sensor
Functional proof	Uses the 3300 XL 8 mm transducer architecture
Application test	Radial shaft vibration



02 WIRING & INTERFACE CHECKS

CHECK ITEM	REQUIRED VALUE
probe family	3300 XL 8 mm
mounting thread	M10 x 1
cable protection	Unarmored
unthreaded length code	0 mm
overall case-length code	160 mm
total probe-lead length	1.0 m
connector and cable option	miniature ClickLoc coaxial connector with FluidLoc cable
agency-approval option	CSA, ATEX and IECEx
linear measurement range	2.0 mm (80 mils)
incremental scale factor	7.87 V/mm (200 mV/mil)
frequency response	0 to 10 kHz, +0/-3 dB
recommended gap	approximately 1.27 mm (50 mils) at -9 V DC

FIELD NOTE

Preserve the M10 x 1 mounting, 160 mm case identity, 1.0 m lead, connector option, target material, system length and approved response when replacing 330103-00-16-10-12-05.



03 COMMISSIONING WORKFLOW



COMMISSIONING ACCEPTANCE EVIDENCE

EVIDENCE ITEM	ACCEPTANCE CONDITION
Identity	330103-00-16-10-12-05 / 330103-00-16-10-12-05 recorded
Physical interface	matched 3300 XL 8 mm extension cable
Companion check	compatible 3300 XL Proximity Sensor
Functional proof	Uses the 3300 XL 8 mm transducer architecture
Application test	Radial shaft vibration

04 RETURN-TO-SERVICE RECORD

- ☐ Confirm the installed matched 3300 XL 8 mm extension cable and compatible 3300 XL Proximity Sensor against the approved project record.
- ☐ Restore power in a controlled sequence and review transducer, monitor and host diagnostics.
- ☐ Prove the intended axial position monitoring function and retain the final controlled acceptance result.
- ☐ Confirm the intended process response before normal operation.

VERIFICATION RECORD

PRODUCT IDENTITY	330103-00-16-10-12-05
INSTALLED POSITION	Documented 3300 XL 8 mm Proximity Transducer System position
VERIFICATION METHOD	Controlled inspection and functional test
RELEASE RECORD	Final diagnostic state retained before service

RELATED BENTLY NEVADA PRODUCTS ON APTER POWER

BRAND + MODEL	RELATED PRODUCT	APTER POWER LINK
GE IC670MFP100	Bently Nevada monitoring product	Open Bently Nevada page
GE IC670FBI001	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 330162 03 45 45 05 05 94 01 02	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 86691 00750 0435 15	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 200350 02 00 01	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 21500 00 12 10 02	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 21500 00 32 05 02	Bently Nevada monitoring product	Open Bently Nevada page
GE IC670GBI002	Bently Nevada monitoring product	Open Bently Nevada page
GE IC670GBI001	Bently Nevada monitoring product	Open Bently Nevada page
Bently Nevada 330851 04 000 040 10 01 00	Bently Nevada monitoring product	Open Bently Nevada page

SOURCE IDENTIFIERS

3300 XL 8 mm Proximity Transducer System Datasheet
141194 Rev. AM

APTER POWER SALES TEAM

WHATSAPP / PHONE	+86 180 3023 5313
EMAIL	sales13@apterpower.com
WEBSITE	www.apterpower.com

