

APTER POWER

330851-02-000-060-50-00-05

25 mm Probe

It is an M30 x 2 unarmored 3300 XL 25 mm probe with a 60 mm case, 5.0 m lead and multiple approvals.

COMPLETE PRODUCT SNAPSHOT

MANUFACTURER	Bently Nevada
FAMILY	3300 XL 25 mm proximity transducer system
MODEL	330851-02-000-060-50-00-05
DOCUMENT	163236 Rev. M

RELATED PRODUCTS ON APTER POWER

01	Bently Nevada 330101-00-12-05-01-05	OPEN
02	Bently Nevada 330101-00-32-05-01-05	OPEN
03	Bently Nevada 330881-16-00-385-06-02	OPEN
04	Bently Nevada 21000-28-05-40-025-03-02	OPEN
05	Bently Nevada 330104-00-06-50-02-00	OPEN
06	Bently Nevada 330190-080-00-00	OPEN

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



330851-02-000-060-50-00-05

Exact-model technical record

Complete model	330851-02-000-060-50-00-05
Manufacturer	Bently Nevada
Product family	3300 XL 25 mm proximity transducer system
Probe thread	M30 x 2
Unthreaded length	0 mm
Overall case length	60 mm
Total probe length	5.0 m
Armor option	No armor

Approval option	Multiple approvals
Linear range	12.7 mm (500 mils)
Scale factor	0.787 V/mm (20 mV/mil)
Frequency response	0 to 2.7 kHz
Recommended nominal gap	7.0 mm (275 mils)
Minimum target diameter	61 mm
Cable type	FluidLoc

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



System role and applications

Large-range displacement

Measures non-contacting movement across the published 12.7 mm linear range.

Thrust position

Tracks axial position with the documented target and gap geometry.

Differential expansion

Supports large-range expansion measurement in an engineered installation.

Exact 25 mm probe renewal

Preserves thread, case, lead, armor and approval identity.

ENGINEERING BOUNDARY

Verify 330851-02-000-060-50-00-05, the M30 x 2 mounting, 60 mm case, 5.0 m matched system, target diameter and approval record before replacement.

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



Model-specific engineering questions

Q1. What certification check belongs to Bently Nevada 330851-02-000-060-50-00-05?

The 05 ending carries the multiple-approval identity, which must agree with the hazardous-area documents for the installed machine.

Q2. How do the M30 x 2 thread and 60 mm case affect replacement clearance?

The bracket, locknuts, and withdrawal path must accept the M30 x 2 body, zero unthreaded length, and 60 mm case without moving the target reference.

Q3. Why must the full 5.0 m length remain intact on Bently Nevada 330851-02-000-060-50-00-05?

The unarmored FluidLoc cable is part of the matched 25 mm transducer arrangement; shortening, splicing, or substituting it changes the system.

Q4. Which target-diameter check precedes gapping of Bently Nevada 330851-02-000-060-50-00-05?

Confirm at least 61 mm of suitable conductive target surface and the required alignment before setting the probe position.

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



Acceptance reference and related products

Q5. What nominal position centers the approved 25 mm probe system?

Use approximately 7.0 mm (275 mils) as the nominal gap while ensuring the actual operating travel remains inside the linear region.

Q6. How is the 12.7 mm range verified without disturbing the approval installation?

Move the target under controlled conditions and confirm a continuous response across the required portion of the 12.7 mm (500 mil) range.

RELATED PRODUCTS ON APTER POWER

01	Bently Nevada 330101-00-12-05-01-05	OPEN
02	Bently Nevada 330101-00-32-05-01-05	OPEN
03	Bently Nevada 330881-16-00-385-06-02	OPEN
04	Bently Nevada 21000-28-05-40-025-03-02	OPEN
05	Bently Nevada 330104-00-06-50-02-00	OPEN
06	Bently Nevada 330190-080-00-00	OPEN
07	Bently Nevada 32000-29-10-04-048-03-02	OPEN

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

11	Bently Nevada 3500-61-C2-A0133811-02	OPEN
----	--------------------------------------	------

