

APTER POWER

330101-00-30-50-02-00

Proximity Probe

It is a unarmored 3/8-24 UNF 3300 XL 8 mm probe with a 3.0 in case and 5.0 m integral lead.

COMPLETE PRODUCT SNAPSHOT

MANUFACTURER	Bently Nevada
FAMILY	3300 XL 8 mm proximity transducer system
MODEL	330101-00-30-50-02-00
DOCUMENT	141194 Rev. AN

RELATED PRODUCTS ON APTER POWER

01	Bently Nevada 330101-00-08-10-01-00	OPEN
02	Bently Nevada 330101-00-13-30-02-05	OPEN
03	Bently Nevada 330104-04-10-50-02-05	OPEN
04	Bently Nevada 330101-51-82-10-01-05	OPEN
05	Bently Nevada 330101-35-62-10-01-05	OPEN
06	Bently Nevada 330102-00-83-50-02-05	OPEN

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



330101-00-30-50-02-00

Exact-model technical record

Complete model	330101-00-30-50-02-00
Manufacturer	Bently Nevada
Product family	3300 XL 8 mm proximity transducer system
Probe part family	330101
Mounting thread	3/8-24 UNF
Cable armor	Unarmored
Unthreaded length	0.0 in
Overall case length	3.0 in

Probe lead length	5.0 m
Connector and cable option	ClickLoc standard cable
Approval option	No approvals
System linear range	2.0 mm (80 mils)
Scale factor	7.87 V/mm (200 mV/mil)
Frequency response	0 to 10 kHz
Nominal gap	1.27 mm (50 mils)

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



System role and applications

Radial shaft vibration

Measures non-contacting shaft vibration in a matched 8 mm system.

Axial position

Tracks shaft position where the engineered target and mounting geometry support the measurement.

Phase reference

Supports phase-reference service when the monitor project assigns this probe accordingly.

Exact probe replacement

Preserves the published thread, case, lead and connector identity during maintenance.

ENGINEERING BOUNDARY

Verify 330101-00-30-50-02-00, the installed extension cable and Proximitar Sensor, target material, system length and gap before replacement.

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



Model-specific engineering questions

Q1. Which inch-threaded mounting fits Bently Nevada 330101-00-30-50-02-00?

Use the 3/8-24 UNF mounting specified for the 330101 probe family and preserve the installed axial reference.

Q2. What case profile distinguishes Bently Nevada 330101-00-30-50-02-00?

Its ordering identity combines a 0.0 inch unthreaded section with a 3.0 inch overall case; both must match the available bracket depth.

Q3. How much integral lead must be accommodated for Bently Nevada 330101-00-30-50-02-00?

Plan the route for the full 5.0 m unarmored lead without coils, sharp bends, or tensile load at the ClickLoc connector.

Q4. Which certification boundary applies to Bently Nevada 330101-00-30-50-02-00?

The final 00 option carries no approval selection, so the application must not depend on an approval that is absent from this catalog identity.

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



Acceptance reference and related products

Q5. What linear excursion can the 330101-00-30-50-02-00 transducer system measure?

The matched 3300 XL 8 mm system covers 2.0 mm (80 mils) of linear travel when target material and component lengths are correct.

Q6. How should a 200 mV/mil channel be checked with Bently Nevada 330101-00-30-50-02-00?

Apply a known displacement and compare it with the 7.87 V/mm response before accepting the monitor scaling.

RELATED PRODUCTS ON APTER POWER

01	Bently Nevada 330101-00-08-10-01-00	OPEN
02	Bently Nevada 330101-00-13-30-02-05	OPEN
03	Bently Nevada 330104-04-10-50-02-05	OPEN
04	Bently Nevada 330101-51-82-10-01-05	OPEN
05	Bently Nevada 330101-35-62-10-01-05	OPEN
06	Bently Nevada 330102-00-83-50-02-05	OPEN
07	Bently Nevada 330104-00-09-50-02-00	OPEN

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

11	Bently Nevada 330880-28-00-085-03-02	OPEN
----	--------------------------------------	------



330101-00-30-50-02-00