


MU-TAOX12 51304335-100

MU-TAOX12 Analog Output FTA

CONTROLLED ENGINEERING COPY

Honeywell MU-TAOX12 51304335-100 is the MU-TAOX12 Analog Output FTA used for field termination for eight analog outputs in the uncoated non-CE execution in a documented PM/APM/HPM Process Manager I/O installation. Confirm the complete identity and installed system configuration before replacement.

INSTALLATION IDENTITY	REQUIRED VALUE
Complete model	MU-TAOX12 51304335-100
Manufacturer	Honeywell
System family	PM/APM/HPM Process Manager I/O
Record scope	Installation, application and verification



APTER POWER SALES TEAM

WHATSAPP / PHONE

EMAIL

WEBSITE

+86 180 3023 5313

sales13@apterpower.com

www.apterpower.com

01 PRE-INSTALLATION PLAN

- 1

Confirm the complete MU-TAOX12 51304335-100 identity on the hardware and maintenance record.
- 2

Place the affected PM/APM/HPM Process Manager I/O process in the approved maintenance state.
- 3

Record the installed position, connectors, terminals, wiring and configuration before removal.
- 4

Isolate all documented power and field energy and apply ESD controls where required.
- 5

Inspect the replacement identity, revision, interfaces and mating hardware before installation.

MATCHED HARDWARE

- Honeywell MU-TAOX12 51304335-100 with exact visible identity
- Matched PM/APM/HPM Process Manager I/O host
- Documented power, field and communication interfaces
- Approved configuration and acceptance record

INSTALLATION CONTROL RECORD

CONTROL ITEM	REQUIRED RECORD
Identity	MU-TAOX12 51304335-100 recorded
Physical interface	Installed terminals, ports and signals matched to the as-found record
Configuration	Approved Honeywell hardware and system configuration restored
Functional proof	Controlled test confirms field termination for eight analog outputs in the uncoated non-CE execution

02 WIRING & INTERFACE CHECKS

CHECK ITEM	REQUIRED VALUE
Product type	Analog Output Field Termination Assembly
FTA model	MU-TAOX12
Manufacturer item number	51304335-100
Channels	8 analog outputs
Signal class	4-20 mA
Terminal type	Compression
Coating	Uncoated
Compliance execution	Non-CE part
Redundancy	Supported

RELATED PRODUCT PAGES

1

Honeywell MC-PAOX03
51309152-175

2

Honeywell MC-TAIH12 51304337-150

3

Honeywell MC-TAOX12
51304335-175

4

Honeywell MC-TDOR12
51309148-175

5

Honeywell MU-PAOX03
51304672-100

6

Honeywell MU-TAIH12 51304337-100

7

Honeywell MU-TAOX12
51304335-125

8

Honeywell 51401496-100


9

Honeywell 51401642-150

FIELD NOTE

Confirm MU-TAOX12 51304335-100 and the installed system before release.

03 COMMISSIONING WORKFLOW



COMMISSIONING ACCEPTANCE EVIDENCE

EVIDENCE ITEM	ACCEPTANCE CONDITION
Identity	MU-TAOX12 51304335-100
Physical interface	Installed terminals, ports and signals matched to the as-found record
Configuration	Approved Honeywell hardware and system configuration restored
Functional proof	Controlled test confirms field termination for eight analog outputs in the uncoated non-CE execution

04 RETURN-TO-SERVICE RECORD

- ☐ Inspect the replacement identity, revision, interfaces and mating hardware before installation.
- ☐ Restore every conductor, cable, power path and configuration value to the approved record.
- ☐ Review host, module, channel or network diagnostics after controlled energization.
- ☐ Perform a controlled test that proves field termination for eight analog outputs in the uncoated non-CE execution before release.

VERIFICATION RECORD

PRODUCT IDENTITY	MU-TAOX12 51304335-100
INSTALLED POSITION	Documented PM/APM/HPM Process Manager I/O position
VERIFICATION METHOD	Controlled inspection and functional test
RELEASE RECORD	Final diagnostic state retained before service

FUNCTIONAL ACCEPTANCE CHECKLIST

- ☐ Inspect the replacement identity, revision, interfaces and mating hardware before installation.
- ☐ Restore every conductor, cable, power path and configuration value to the approved record.
- ☐ Review host, module, channel or network diagnostics after controlled energization.
- ☐ Perform a controlled test that proves field termination for eight analog outputs in the uncoated non-CE execution before release.

SOURCE IDENTIFIERS

Honeywell Experion Control Hardware Planning Guide R301.1 | Honeywell manufacturer publication