

330101-00-30-50-02-00

Proximity Probe

INSTALLATION | CONNECTION | COMMISSIONING | ACCEPTANCE

CONTROLLED WORK SEQUENCE

1

VERIFY

2

ISOLATE

3

CONNECT

4

TEST

Verify 330101-00-30-50-02-00, the installed extension cable and Proximity Sensor, target material, system length and gap before replacement.

CONTROLLED PREREQUISITES

Exact identity

Verify 330101-00-30-50-02-00 against the nameplate and controlled record.

Approved system

Confirm the documented 3300 XL 8 mm proximity transducer system system position and interfaces.

Evidence

Use 141194 Rev. AN for the published technical and installation boundary.

RELATED PRODUCTS ON APTER POWER

01	Bently Nevada 83607-00-75-05-02	OPEN
02	Bently Nevada 990-10-50-03-00	OPEN
03	Bently Nevada 86691-01780-1300-15	OPEN
04	Bently Nevada 330880-28-15-044-01-02	OPEN

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



330101-00-30-50-02-00

Exact-model technical record

Complete model	330101-00-30-50-02-00	Probe lead length	5.0 m
Manufacturer	Bently Nevada	Connector and cable option	ClickLoc standard cable
Product family	3300 XL 8 mm proximity transducer system	Approval option	No approvals
Probe part family	330101	System linear range	2.0 mm (80 mils)
Mounting thread	3/8-24 UNF	Scale factor	7.87 V/mm (200 mV/mil)
Cable armor	Unarmored	Frequency response	0 to 10 kHz
Unthreaded length	0.0 in	Nominal gap	1.27 mm (50 mils)
Overall case length	3.0 in		

OFFICIAL SOURCE COVERAGE

Source 1	3300 XL 8 mm Proximity Transducer System Datasheet — Ordering Information, 141194 Rev. AN
Source 2	3300 XL 8 mm Proximity Transducer System Datasheet — Specifications, 141194 Rev. AN
Source 3	3300 XL 8 mm Proximity Transducer System Datasheet — Description and ordering notes, 141194 Rev. AN

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



330101-00-30-50-02-00

Installation and connection sequence

STEP 1

Confirm the complete 330101-00-30-50-02-00 marking before removal.

STEP 2

Check the installed 3/8-24 UNF mounting and preserve the mechanical reference.

STEP 3

Isolate the monitoring channel and protect the probe tip from impact.

STEP 4

Record the 0.0 in unthreaded and 3.0 in case geometry.

STEP 5

Preserve the 5.0 m lead routing and minimum bend radius.

STEP 6

Protect the clickloc standard cable interface from contamination.

RELATED PRODUCTS ON APTER POWER

01	Bently Nevada 83607-00-75-05-02	OPEN
02	Bently Nevada 990-10-50-03-00	OPEN
03	Bently Nevada 86691-01780-1300-15	OPEN
04	Bently Nevada 330880-28-15-044-01-02	OPEN

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com



Commissioning and acceptance

CHECK 1

Match the probe to the documented extension cable and Proximator Sensor.

CHECK 2

Set the gap under controlled conditions and verify gap voltage and signal response.

CHECK 3

Verify 330101-00-30-50-02-00, the installed extension cable and Proximator Sensor, target material, system length and gap before replacement.

CHECK 4

Retain the final 330101-00-30-50-02-00 identity, wiring, diagnostic and acceptance record.

RELATED PRODUCTS ON APTER POWER

01	Bently Nevada 330103-02-08-50-11-00	OPEN
02	Bently Nevada 330102-00-31-05-02-00	OPEN
03	Bently Nevada 330104-00-15-50-12-00	OPEN
04	Bently Nevada 330172-08-12-50-02-00	OPEN
05	Bently Nevada 330174-00-08-50-02-05	OPEN
06	Bently Nevada 330232-01-10-12-00	OPEN

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



Acceptance reference and related products

Identity	Complete model 330101-00-30-50-02-00 verified
Installed system	3300 XL 8 mm proximity transducer system
Connections	Power, polarity, shielding, address or slot record completed
Controlled test	Diagnostics and intended process response accepted

RELATED PRODUCTS ON APTER POWER

01	Bently Nevada 148722-01	OPEN
02	Bently Nevada 330851-01-00-20-10-00-00	OPEN
03	Bently Nevada 84510-50	OPEN
04	Bently Nevada 330851-02-010-140-10-00-05	OPEN
05	Bently Nevada 330195-02-12-50-05	OPEN
06	Bently Nevada 26530-12-10-03-018-085-24-03-00	OPEN
07	Bently Nevada 135613-01-01	OPEN
08	Bently Nevada 125065-12	OPEN

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com

