


MU-TAIH12 51304337-100

MU-TAIH12 High-Level Analog Input/STI FTA

CONTROLLED ENGINEERING COPY

Honeywell MU-TAIH12 51304337-100 is the MU-TAIH12 High-Level Analog Input/STI FTA used for termination of sixteen high-level analog or smart-transmitter inputs in the uncoated execution in a documented PM/APM/HPM Process Manager I/O installation. Confirm the complete identity and installed system configuration before replacement.

INSTALLATION IDENTITY	REQUIRED VALUE
Complete model	MU-TAIH12 51304337-100
Manufacturer	Honeywell
System family	PM/APM/HPM Process Manager I/O
Record scope	Installation, application and verification



APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com

01 PRE-INSTALLATION PLAN

1

Confirm the complete MU-TAIH12 51304337-100 identity on the hardware and maintenance record.

2

Place the affected PM/APM/HPM Process Manager I/O process in the approved maintenance state.

3

Record the installed position, connectors, terminals, wiring and configuration before removal.

4

Isolate all documented power and field energy and apply ESD controls where required.

5

Inspect the replacement identity, revision, interfaces and mating hardware before installation.

MATCHED HARDWARE

- Honeywell MU-TAIH12 51304337-100 with exact visible identity
- Matched PM/APM/HPM Process Manager I/O host
- Documented power, field and communication interfaces
- Approved configuration and acceptance record

INSTALLATION CONTROL RECORD

CONTROL ITEM	REQUIRED RECORD
Identity	MU-TAIH12 51304337-100 recorded
Physical interface	Installed terminals, ports and signals matched to the as-found record
Configuration	Approved Honeywell hardware and system configuration restored
Functional proof	Controlled test confirms termination of sixteen high-level analog or smart-transmitter inputs in the uncoated execution

02 WIRING & INTERFACE CHECKS

CHECK ITEM	REQUIRED VALUE
Product type	HLAI/STI Field Termination Assembly
FTA model	MU-TAIH12
Manufacturer item number	51304337-100
Channels	16
Terminal type	Compression
Mounting size	B
Coating	Uncoated
Compliance execution	Non-CE part
Redundancy	Supported in the documented arrangement

RELATED PRODUCT PAGES

1

Honeywell MC-PAOX03
51309152-175

2

Honeywell MC-TAIH12 51304337-150

3

Honeywell MC-TAOX12
51304335-175

4

Honeywell MC-TDOR12
51309148-175

5

Honeywell MU-PAOX03
51304672-100

6

Honeywell MU-TAOX12
51304335-100

7

Honeywell MU-TAOX12
51304335-125

8

Honeywell 51401496-100


9

Honeywell 51401642-150

FIELD NOTE

Confirm MU-TAIH12 51304337-100 and the installed system before release.

03 COMMISSIONING WORKFLOW



COMMISSIONING ACCEPTANCE EVIDENCE

EVIDENCE ITEM	ACCEPTANCE CONDITION
Identity	MU-TAIH12 51304337-100
Physical interface	Installed terminals, ports and signals matched to the as-found record
Configuration	Approved Honeywell hardware and system configuration restored
Functional proof	Controlled test confirms termination of sixteen high-level analog or smart-transmitter inputs in the uncoated execution

04 RETURN-TO-SERVICE RECORD

- ☐ Inspect the replacement identity, revision, interfaces and mating hardware before installation.
- ☐ Restore every conductor, cable, power path and configuration value to the approved record.
- ☐ Review host, module, channel or network diagnostics after controlled energization.
- ☐ Perform a controlled test that proves termination of sixteen high-level analog or smart-transmitter inputs in the uncoated execution before release.

VERIFICATION RECORD

PRODUCT IDENTITY	MU-TAIH12 51304337-100
INSTALLED POSITION	Documented PM/APM/HPM Process Manager I/O position
VERIFICATION METHOD	Controlled inspection and functional test
RELEASE RECORD	Final diagnostic state retained before service

FUNCTIONAL ACCEPTANCE CHECKLIST

- ☐ Inspect the replacement identity, revision, interfaces and mating hardware before installation.
- ☐ Restore every conductor, cable, power path and configuration value to the approved record.
- ☐ Review host, module, channel or network diagnostics after controlled energization.
- ☐ Perform a controlled test that proves termination of sixteen high-level analog or smart-transmitter inputs in the uncoated execution before release.

SOURCE IDENTIFIERS

Honeywell Experion Control Hardware Planning Guide R301.1 | Honeywell manufacturer publication