

APTER POWER

PR6424-000-000-CON21

Eddy Current Sensor

It combines a PR6424 16 mm sensor identity with the CON021 signal-converter arrangement for non-contacting machinery measurements.

COMPLETE PRODUCT SNAPSHOT

MANUFACTURER	Epro
FAMILY	PR6424 16 mm eddy-current transducer system
MODEL	PR6424-000-000-CON21
DOCUMENT	PR6424 / PR642x

RELATED PRODUCTS ON APTER POWER

01	Emerson KJ4001X1-BE1-12P0818X072-VE4050S2K1C0	OPEN
02	Emerson SP4401	OPEN
03	Emerson SP3401	OPEN
04	Emerson 12P4705X062	OPEN
05	Emerson EZ1000	OPEN
06	Epro PR9268-203-000	OPEN

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



PR6424-000-000-CON21

Exact-model technical record

Complete model	PR6424-000-000-CON21	Dynamic range	0 to 1000 μ m
Manufacturer	Epro	Nominal air gap	approximately 2.7 mm
Product family	PR6424 16 mm eddy-current transducer system	Target reference	Ferromagnetic steel, 42CrMo4 reference
Sensor family	PR6424, 16 mm	Minimum shaft diameter	80 mm
Converter identity	CON021	Measurement roles	Radial/axial displacement, position, eccentricity and speed reference
Nominal sensitivity	4 V/mm	Cable construction	PTFE-insulated sensor and extension cable
Static range	approximately ± 2 mm		

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



System role and applications

Shaft radial displacement

Measures non-contacting radial motion on large rotating shafts.

Axial position

Tracks thrust or axial position in the engineered probe geometry.

Eccentricity monitoring

Observes low-speed shaft eccentricity with the matched system.

Speed and phase reference

Provides the proximity signal used by the configured monitoring channel.

ENGINEERING BOUNDARY

Treat PR6424-000-000 and CON021 as a matched installed identity. Verify system length, target material, mounting, gap and monitor scale before service.

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



Model-specific engineering questions

Q1. Which sensor family identifies PR6424-000-000-CON21?

Sensor family: PR6424, 16 mm. Match the complete catalog identity before work.

Q2. What converter identity must be matched for PR6424-000-000-CON21?

Converter identity: CON021. Preserve the installed system assignment and connector mapping.

Q3. How is the nominal sensitivity defined on PR6424-000-000-CON21?

Nominal sensitivity: 4 V/mm. Use the controlled project record during wiring checks.

Q4. Why does the static range matter when replacing PR6424-000-000-CON21?

Static range: approximately ± 2 mm. Do not substitute a neighboring family value.

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



PR6424-000-000-CON21

Acceptance reference and related products

Q5. Which dynamic range should commissioning records retain for PR6424-000-000-CON21?

Dynamic range: 0 to 1000 µm. Record the as-found setting before removal.

Q6. What should technicians verify about the nominal air gap of PR6424-000-000-CON21?

Nominal air gap: approximately 2.7 mm. Confirm the value again during controlled startup.

RELATED PRODUCTS ON APTER POWER

01	Emerson KJ4001X1-BE1-12P0818X072-VE4050S2K1C0	OPEN
02	Emerson SP4401	OPEN
03	Emerson SP3401	OPEN
04	Emerson 12P4705X062	OPEN
05	Emerson EZ1000	OPEN
06	Epro PR9268-203-000	OPEN

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313
EMAIL sales13@apterpower.com
WEBSITE www.apterpower.com

