

Exact Ordering and Housing Role

Bently Nevada 31000-28-10-00-175-01-02

Bently Nevada 31000-28-10-00-175-01-02 is an external 31000 probe housing ordered with a 3300 XL 8 mm probe with multiple-approval option, 1.0 m probe cable and one 3/4-14 NPT fitting and two plugs. The C00 standoff and D175 penetration selections define the installation geometry for accessible probe service in a matched monitoring system.

Decoded Manufacturer Ordering

ORDERING FIELD	DOCUMENTED SELECTION
A28 probe	3300 XL 8 mm probe with multiple-approval option
B10 cable	1.0 m (39 in) probe cable
C00 standoff	No standoff adapter
D175 penetration	17.5 in manufacturer-coded adjustable probe penetration
E01 fittings	One 3/4-14 NPT fitting and two plugs
F02 mounting	3/4-14 NPT outer-sleeve mounting thread

Functional boundary

The 31000 housing positions and protects the ordered probe, but the complete measuring function belongs to the matched probe, cable, Proximity sensor and monitoring channel.

System Matching Checks

CHECK	RELEASE QUESTION
Probe identity	Does the installed probe match ordering field A?
Cable route	Does field B match the retained cable path?
Geometry	Are fields C and D compatible with the approved gap?
Hardware	Do fields E and F match conduit and case mounting?

Related Bently Nevada Products on Apter Power

Bently Nevada 31000-30-05-15-049-01-02

[View Bently Nevada 31000-30-05-15-049-01-02 page](#)

Construction and Application

Published Housing Construction

AREA	MANUFACTURER-PUBLISHED FACT
Housing	Glass-reinforced PPS thermoplastic with conductive fibers.
Sleeve and retaining chain	AISI 304 stainless steel.
Outer sleeve and screws	AISI 303 stainless steel.
Environmental protection	Type 4X and IP66 for the assembled housing.
Retaining nut	Recommended torque 29.4 N.m (260 in.lb).

Model-Specific Use

ROLE	APPLICATION BOUNDARY
Radial vibration	External probe mounting for a matched radial-vibration monitoring chain.
Shaft position	Non-contact 3300 XL 8 mm probe placement where the approved setup supports it.
External gap service	Accessible probe-gap adjustment or probe replacement without opening the machine case.
Conduit transition	The E01 fittings and plugs route the cable into the installed conduit system.

Safety distinction

The plastic housing is neither explosion-proof nor a pressure enclosure. Hazardous-area suitability depends on the approved installed transducer system, barriers and drawings.

Related Bently Nevada Products on Apter Power

- Bently Nevada 31000-28-10-15-040-03-02
[View Bently Nevada 31000-28-10-15-040-03-02 page](#)
- Bently Nevada 31000-16-10-00-050-03-02
[View Bently Nevada 31000-16-10-00-050-03-02 page](#)
- Bently Nevada 31000-31-05-20-058-00-02
[View Bently Nevada 31000-31-05-20-058-00-02 page](#)

Questions, Source and Related Models

Exact-Configuration Questions

QUESTION	ANSWER
Which probe does A28 specify?	A28 selects a 3300 XL 8 mm probe with multiple-approval option in the manufacturer 31000 ordering table.
What does C00 select?	C00 specifies no standoff adapter; retain the approved mounting geometry.
What is D175?	D175 is the 17.5 in manufacturer-coded adjustable probe penetration selection; confirm the controlled installed gap.

Manufacturer source

Bently Nevada 31000 and 32000 Proximity Probe Housing Assemblies Datasheet 141610 Rev. R. Ordering codes: pages 5-6; housing purpose, materials and warnings: pages 1-4. Related links are site navigation, not technical sources.

Related Bently Nevada Products on Apter Power

Bently Nevada 31000-28-05-00-061-01-02

[View Bently Nevada 31000-28-05-00-061-01-02 page](#)

Bently Nevada 31000-16-05-00-070-03-02

[View Bently Nevada 31000-16-05-00-070-03-02 page](#)

Bently Nevada 32000-28-05-00-070-03-02

[View Bently Nevada 32000-28-05-00-070-03-02 page](#)

APTER POWER SALES TEAM

WHATSAPP / PHONE +86 180 3023 5313

EMAIL sales13@apterpower.com

WEBSITE www.apterpower.com



31000-28-10-00-
175-01-02