

INDUSTRIAL AUTOMATION PRODUCT

330101-00-36-10-01-00

3300 XL 8 mm Proximity Probe

Bently Nevada 330101-00-36-10-01-00 is an unarmored 3300 XL 8 mm proximity probe with a 3.6-inch case and 1.0 m standard cable. The ClickLoc connection includes a protector.

ORDER-CODE DETAIL	VERIFIED VALUE
Base model	330101
Mounting thread	3/8-24 UNF
Armor	Without armor
Unthreaded length	0.0 in

CONTROLLED ENGINEERING COPY

IDENTITY	VERIFIED VALUE
Manufacturer	Bently Nevada
System family	Bently Nevada 3300 XL 8 mm Proximity Transducer System
Part number	330101-00-36-10-01-00
Document status	Controlled product and system reference

DOCUMENT SCOPE

Exact article identity, official technical data, host matching, installation checks, applications, precautions and controlled acceptance evidence.

MODEL-SPECIFIC ENGINEERING NOTE

Install 330101-00-36-10-01-00 only in the documented Bently Nevada 3300 XL 8 mm Proximity Transducer System position. Preserve exact mating interfaces and the as-found record, then verify diagnostics and non-contacting shaft vibration and position measurement through a protected ClickLoc joint under controlled conditions.

System Role and Architecture

Bently Nevada 330101-00-36-10-01-00 is an unarmored 3300 XL 8 mm proximity probe with a 3.6-inch case and 1.0 m standard cable. The ClickLoc connection includes a protector.

FUNCTION 1
Exact article identity 330101-00-36-10-01-00

FUNCTION 2
3300 XL 8 mm Proximity Probe

FUNCTION 3
Documented role: non-contacting shaft vibration and position measurement through a protected ClickLoc joint

FUNCTION 4
Controlled installation, diagnostics and functional verification

RELATED APTER POWER PAGES

1 Bently Nevada 330709-000-050-10-12-05

2 Bently Nevada 330706-005-046-10-02-00

3 Bently Nevada 330705-02-18-10-02-00

4 Bently Nevada 330701-00-10-10-02-00

5 Bently Nevada 330930-060-03-05

6 Bently Nevada 330330-080-01-00

7 Bently Nevada 330330-070-00-00

8 Bently Nevada 330851-02-000-080-10-00-00

9 Bently Nevada 330851-01-000-020-10-00-00

MATCHED SYSTEM COMPONENTS

NO.	DOCUMENTED COMPONENT / ROLE
01	Bently Nevada 3300 XL 8 mm Proximity Transducer System
02	Matched Bently Nevada host module, Proximitor Sensor or rack position
03	Documented wiring, cable route, connectors, shields and grounding
04	Approved configuration and controlled acceptance record

SYSTEM INTEGRATION RECORD

INTEGRATION ITEM	DOCUMENTED ROLE
Host identity	Bently Nevada 3300 XL 8 mm Proximity Transducer System
Interface role	non-contacting shaft vibration and position measurement through a protected ClickLoc joint
Field / power context	documented machinery-monitoring rack or matched transducer-loop position
Commissioning evidence	Identity, interfaces, configuration, diagnostics and controlled functional response recorded

INSTALLATION AND CONNECTION CHECKS

1 Confirm the complete 330101-00-36-10-01-00 marking, product role and documented installation position.

2 Place the machinery protection system and connected process in the approved maintenance state.

3 Isolate power and field circuits, prove the safe state and apply ESD controls where required.

4 Record every mating component, terminal, connector, shield, cable route and configuration assignment.

Technical Specifications

Technical values below are limited to the named product record and directly applicable manufacturer documentation.

PARAMETER	VALUE	PARAMETER	VALUE
Base model	330101	Cable	Standard cable
Mounting thread	3/8-24 UNF	Approval option	No approvals
Armor	Without armor	System linear range	2.0 mm
Unthreaded length	0.0 in	Incremental scale factor	7.87 V/mm
Overall case length	3.6 in	Recommended gap	1.27 mm
Total probe length	1.0 m	Minimum cable bend radius	25.4 mm
Connector	Miniature coaxial ClickLoc	Maximum connector torque	0.565 N m
Connector protector	Included		

RELATED PRODUCT PAGES		
1 Bently Nevada 330709-000-050-10-12-05	2 Bently Nevada 330706-005-046-10-02-00	3 Bently Nevada 330705-02-18-10-02-00
4 Bently Nevada 330701-00-10-10-02-00	5 Bently Nevada 330930-060-03-05	6 Bently Nevada 330330-080-01-00
7 Bently Nevada 330330-070-00-00	8 Bently Nevada 330851-02-000-080-10-00-00	9 Bently Nevada 330851-01-000-020-10-00-00

ENGINEERING BOUNDARY

Confirm 330101-00-36-10-01-00, its matched Bently Nevada 3300 XL 8 mm Proximity Transducer System host, exact interfaces, installed position, wiring or cable route, grounding, shielding, configuration, diagnostics and controlled acceptance evidence before release.

PRE-INSTALLATION CHECKS

1 Confirm the complete 330101-00-36-10-01-00 marking, product role and documented installation position.	2 Place the machinery protection system and connected process in the approved maintenance state.
3 Isolate power and field circuits, prove the safe state and apply ESD controls where required.	4 Record every mating component, terminal, connector, shield, cable route and configuration assignment.

Applications and Engineering Context

Machinery-protection planned maintenance

Restores non-contacting shaft vibration and position measurement through a protected ClickLoc joint in the documented monitoring architecture.

3300 XL 8 mm Proximity Probe replacement

Uses exact 330101-00-36-10-01-00 identity instead of an adjacent order-code execution.

Monitoring-system refurbishment

Preserves the installed host position, mating interfaces, wiring and approved configuration.

Controlled recommissioning

Confirms diagnostics and the affected measurement or communication function before operation.

TECHNICAL NOTE

Install 330101-00-36-10-01-00 only in the documented Bently Nevada 3300 XL 8 mm Proximity Transducer System position. Preserve exact mating interfaces and the as-found record, then verify diagnostics and non-contacting shaft vibration and position measurement through a protected ClickLoc joint under controlled conditions.

MODEL-SPECIFIC ACCEPTANCE EVIDENCE

CHECK	ACCEPTANCE CONDITION
Identity	330101-00-36-10-01-00 recorded
Host / carrier	Bently Nevada 3300 XL 8 mm Proximity Transducer System
Physical interface	Installed mating components and field interfaces matched to the as-found record
Configuration	Approved rack, channel or transducer-loop configuration restored
Functional proof	Controlled test confirms non-contacting shaft vibration and position measurement through a protected ClickLoc joint

IMPORTANT NOTICE

Confirm 330101-00-36-10-01-00, its matched Bently Nevada 3300 XL 8 mm Proximity Transducer System host, exact interfaces, installed position, wiring or cable route, grounding, shielding, configuration, diagnostics and controlled acceptance evidence before

Related Products and Source Record

Brand-qualified Apter Power navigation links are provided for system planning only; manufacturer evidence remains the named source record.

RELATED PRODUCTS ON APTER POWER

1

Bently Nevada 330709-000-050-10-12-05

View Bently Nevada 330709-000-050-10-12-05 page

2

Bently Nevada 330706-005-046-10-02-00

View Bently Nevada 330706-005-046-10-02-00 page

3

Bently Nevada 330705-02-18-10-02-00

View Bently Nevada 330705-02-18-10-02-00 page

4

Bently Nevada 330701-00-10-10-02-00

View Bently Nevada 330701-00-10-10-02-00 page

5

Bently Nevada 330930-060-03-05

View Bently Nevada 330930-060-03-05 page

6

Bently Nevada 330330-080-01-00

View Bently Nevada 330330-080-01-00 page

7

Bently Nevada 330330-070-00-00

View Bently Nevada 330330-070-00-00 page

8

Bently Nevada 330851-02-000-080-10-00-00

View Bently Nevada 330851-02-000-080-10-00-00 page

9

Bently Nevada 330851-01-000-020-10-00-00

View Bently Nevada 330851-01-000-020-10-00-00 page

MANUFACTURER SOURCE RECORD

3300 XL 8 mm Proximity Transducer System Datasheet 141194 Rev. AN | Baker Hughes / Bently Nevada manufacturer datasheet

APTER POWER SALES TEAM

WHATSAPP / PHONE

+86 180 3023 5313

EMAIL

sales13@apterpower.com

WEBSITE

www.apterpower.com



RECOMMENDATION SCOPE

These links support product navigation and comparison. Technical values in this document are sourced only from the manufacturer record above.